



DUOX^{plus}

It takes 2 to connect

FERMAX

From Valencia to the rest of the world



Leading with
purpose and
passion



For more than 75 years, our **specialisation in video door entry and access control systems** has been our added value. **Our track record positions us as leaders in the industry**, offering communication and connectivity solutions adapted to any type of project anywhere in the world.

Being part of the **Leading Brands of Spain Forum** reinforces our commitment to excellence and international projection, highlighting our pride in our roots and contributing to the global recognition of Made in Spain brands.

Connecting
people and
homes with the
world

Our presence in **more than 85 countries** reflects the trust our customers place in us, which motivates us to grow, learn and constantly improve.

Our greatest achievement is the team of **more than 500 people** who are part of Fermax and whose work drives our mission and values every day.

Integrity
and respect

Customer and result
oriented

Effort and
teamwork

Corporate Social
Responsibility

Sense of belonging and
identification with the
company's culture

Versatility and a
permanent attitude of
adaptability to change

Commitment to equality,
safety, health and
environment

Our mission: To be leaders in connectivity



Presence in
over 85 countries

Headquarters in
Valencia, Spain

6 subsidiaries and
2 commercial offices

The security behind every connection



We work to contribute to the **transformation of cities, leveraging the connectivity of our products** to offer new services and businesses to different stakeholders that interact with buildings and homes on a daily basis.

Our technology guarantees **secure communications** through the use of advanced protocols, and our cloud infrastructure allows our products to be updated with new features. In addition, our **manufacturing processes, certified with ISO 9001**, and the use of approved components support the quality and reliability of our products.

But our commitment goes beyond technology: **we create connected solutions so that everyone can protect their home from anywhere**, providing them with security, peace of mind and confidence at all times. This purpose is what defines us as a brand.

Connecting people and
homes with the world

Secure
communications

Quality and reliability of the
production process



Connecting technology and sustainability

Experts in communication, leaders in innovation



Innovation and manufacturing are carried out in our **2 production centres in Valencia, Spain**, which allows us to guarantee supply in all circumstances and maintain a permanent stock of spare parts.

Our technological solutions allow for the updating of existing installations without the need for major changes, with **new functions to bring connectivity to all homes**.

In-house R&D
+ 40 engineers

Manufacturing of
electronic circuits

Mechanical manufacturing:
plastic injection, panel laser-cutting

Assembly and testing

+85% of orders shipped
within 24 hours



A green footprint on our path



As manufacturers, **we are committed to a circular economy and a production process with the least possible environmental impact** through prevention, recycling, reuse of materials and the use of renewable energy.

Our Special Employment Centre (CEEME) guarantees the professional, social and personal inclusion of people with disabilities, promoting their independence through equal and inclusive employment.

With every step we take towards the connectivity of our products, **we contribute to the development of more sustainable cities**, reducing the carbon footprint through technologies that minimise, for example, bounce rates in home parcel deliveries.

Through social, environmental and inclusive initiatives, we work to build a responsible present and a better future for all.

CEEME. Special Employment
Centre since 2000

Equality and
diversity

Training and
talent

Reduction of
environmental impact

The background of the entire image is a vibrant, abstract composition. It features a dense network of glowing blue and white nodes connected by thin lines, resembling a digital or molecular structure. This network is superimposed over a blurred, high-angle view of a city at night, with the lights of buildings and streets visible in shades of blue, purple, and orange. The overall effect is one of high-tech connectivity and urban intelligence.

DUOX^{plus}

The world's first
100% digital
Smart System
in 2 wires



The most powerful and fastest 2-wire system to install and program.



Consistent quality throughout the installation.



Up to 10 panels and 10 guard units at the general entrance.



Maximum point to point distance without regeneration: 500m.



Installation using existing wiring.



Up to 100 blocks and sub-blocks.



Up to 10 panels and 10 guard units in each building or block of apartments.



2 communication channels within the same block.



Smart accessories for installations of all sizes.



Maximum distance between extremes of the installation: 3.000m.

DUOX^{plus}

A **simplified 2-wire installation** without polarity throughout the entire installation. DUOX PLUS is a highly flexible system that can be **installed with most of the existing cables**. It is a digital system and hence it enables to avoid electrical interferences or noise, and maintains the same **optimum audio and video quality throughout the entire installation**, from the first apartment in the project to the most distant one.

The DUOX PLUS system **is installed in the same way for both audio and video**, allowing the users to choose which terminal they prefer to have it at home. Additionally, it is the only **2-wire system that can allow two communication channels in the same block**, i.e. two panels calling two different apartments at the same time. It has a built-in voice guided **programming system in pushbutton outdoor panels** and configuration via **graphic menu in digital panels and monitors**. Its digital technology adapts to all types of topologies and distances, making it possible to successfully install any project: **from small individual buildings to large residential projects**.

All these features make DUOX PLUS the **fastest system to quote, install and program**.

A system that can be perfectly adapted to all situations, both for new construction and retrofit.



A system designed for the **professional installer** ...

Wiring **flexibility**

2 NON-POLARISED WIRES

Compatible with a wide variety of wiring.

In retrofit installations, DUOX PLUS can be installed using existing wiring. Reduced errors, simplified installation on only 2 non-polarised wires.

Simplicity of installation

It saves time during installation and maintenance.

Easy **programming**

Monitors: one person can program the installation in a few seconds directly from the OSD menu.

Panels: digital panels are programmed from the keypad, while on our pushbutton panels, the amplifier includes a voice-guided programming system.

Scalable system

For all kinds of projects; large or small, simple or complex, vertical structures or horizontal installations.

Digital transmission

FULL DIGITAL. All information (audio, video and data) is fully digital, ensuring the same audio and video quality throughout the installation.

... and for **the end-user**

DUOX^{plus}



Connectivity

Our Wi-Fi video door entry systems open up the world of connectivity to every type of building and home, with call forwarding to mobile phones built into even the most basic monitors.

Security Photocaller

The video intercom automatically captures an image of the caller on the monitor, and on the mobile phone in case of Wi-Fi models.

Accessibility

Adapted and accessible products for everyone, both inside and outside the home.

Convenience

Access to the video intercom from any device, mobile or tablet, to answer calls and open the door with a single click or with voice.

PRODUCT

range

DUOX_{plus}

FERMAX



It takes...



2 to
connect



IP65 IK08

Wide-angle camera

5" graphic display

Presence sensors

LED wave with status illumination

Backlit keypad

Speaker



It has **2 digital MEMS microphones (Micro Electro Mechanical System)**, which dynamically and adaptively capture and filter out environmental noise and guarantee clean audio on the monitor or handset so that the user hears no background noise, echoes or cuts.

NEW

cora

by FERMEX



FEATURES

Duox Plus technology, **100% digital two wires**.

Free **call divert** for all apartments in the installation with a Wi-Fi monitor.

Made in strong and durable **anodised aluminium**.

Ultra-slim, only 1 cm thick when flush mounted and 3 cm when surface mounted.

Highly watertight and robust: **IP65 IK08**.

Simple and intuitive **installation** with 1 screw.

720p wide-angle camera (vertical=80°, horizontal=120°).

5" LCD screen customisable by the installer (images and messages).

Light and **presence sensor**.

Wave of LEDs with **illumination and movements that signal status**.

Backlit mechanical keypad with a dot on the key 5 and embossing on the bell key.

Advanced processor with 4-core CPU+GPU.

Multi-language voice synthesiser (32 languages), bilingual message configuration and **customisable language**.

Mirror mode (retroview). It allows the visitors to see their own image and thus to position themselves to be seen correctly.

Assisted **alphanumeric dialling**.

Possibility to create backup copies of users and configuration.

High-quality audio thanks to the **CDS (Cora Dynamic Sound)** system, which includes a speaker and 2 digital MEMS microphones.

Access control via keypad and integrated (EM 125Khz) proximity reader.

Postman access code via keypad or proximity readers restricted by hours and days.

Configuration from mobile, tablet or computer, via a web server without having to open the panel.

An optional **inductive loop** can be connected for people with hearing aids.

Built-in **DUOX PLUS installation tester**.

c^ora

by FERMAX

CORA represents the excellence and evolution of Fermax's DUOX PLUS outdoor panels, not only for its elegant aesthetics, but also for being one of the most interactive entrance panels on the market, both for the user and the installer.



CORA Panel

CAMERA

It includes a wide-angle 720p colour camera (Vertical=80°, Horizontal=120°) with integrated scene lights on both sides of the camera as well as a camera zoom adjustment system. The camera image adjustment is done from a mobile, tablet or computer using a web browser.

DISPLAY

It is a very high-tech panel with a **4-core CPU+GPU processor**.

Its **5" LCD screen with 640 x 480px resolution is customisable** by the installer (messages and images).

The display is activated by **presence sensors** or by pressing a key.

The display brightness can be set to adjust automatically according to the ambient light level.

It includes the **Retroview function**, which allows the visitors to see the video captured by the camera during calls and conversations in real time and thus better position themselves in front of the panel to be seen perfectly.

User interface with iconography for guided and intuitive use.

Calls can be made in two ways:

- **by entering** the corresponding code assigned to the home + the "bell" key.
- **by searching** in the electronic directory of the resident or concierge and once found, by pressing the "bell" key.

The call can be numerical, alphanumeric, by blocks, etc.

It is **possible to call the concierge directly by pressing the BELL key**. If there is more than one, the list is displayed for selection.

WAVE

A wave of leds separates the display from the keypad. It is not only a decorative element, but it also **interacts with the user by reinforcing the status that appears on the display**, giving personality to our panel.

Status: Calling, In communication, Door Open, Channel Busy and In maintenance.



AUDIO QUALITY

High-quality audio thanks to the CDS (Cora Dynamic Sound) system.

It incorporates a speaker and 2 digital MEMS microphones, which dynamically and adaptively capture and filter out environmental noise and guarantee clean audio on the monitor or handset so that the user hears no background noise, echoes or cuts. **The speaker volume can be self-regulated** to adapt to different environment noise sound levels (**day-night**).





KEYPAD

Backlit mechanical keypad with embossing on the key 5, so that blind people can locate themselves in the centre of the keypad, and a counter-embossing on the Bell to identify the call key.

The illumination of the Call  and Cancel  keys changes colour depending on the status.

CONFIGURATION AND PROGRAMMING

The configuration is very simple and can be done from a mobile/tablet/PC, using a browser and without having to open the panel. To do this, the installer must stand close to it and connect to the **Wi-Fi access point** generated by it. In this way, it will be **possible to set it up**:

- Configuration parameters.
- Directory of residents and concierges.
- Access control (keypad codes, proximity key fobs).
- Installation test.
- Firmware version update.
- Uploading and **customising** images, logos, text and voice messages (2 languages can be selected to be played consecutively).
- Possibility to configure a postman access code, for the configured days of the week and timetable.
- Possibility to create backup files of users (on mobile/tablet/PC via browser) and configuration.

ROBUSTNESS

CORA is made in **anodised aluminium with no visible screws**. It has an **IP65** degree of watertightness and maximum protection against dust and rain. It has a very high mechanical impact resistance rating of **IK08**, making it practically vandal-proof.

ACCESS CONTROL

- Door opening via **keypad code** (up to 10,000 different users / codes).
- Door opening using RFID (EM 125Khz) **proximity key fob** via the proximity reader included as standard in the panel (up to 10,000 fobs).
- **Combination of the previous two** for greater security.

VILLA MODE

It is possible to configure the panel to operate as a villa panel. In this case, the call will be made by pressing the BELL key directly. This makes CORA the video door entry solution for villas that look for distinction, elegance and technology, as well as security, as the access control functions by keypad code, proximity key fobs or a combination of both will still be available.



MOUNTING

CORA is installed with only 1 screw.

Ultra-slim, **only 1 cm thick when flush mounted and 3 cm when surface mounted.**

The installation boxes for the CORA panel must be ordered separately.

Its size fits perfectly into the **Fermax S6 flush box of the Cityline and CityClassic panels.**

Its small size allows for replacing older installations with more advanced technology and **with virtually no work.**

For retrofits, an existing City/Skyline flush box (S6 or S8 depending on the CORA size) can be adapted by ordering a separate flush mounting set ref. 7708.

Other accessories are also available, such as decorative frame, angular complement, hood and directory panel (the latter only for CORA S6). It is possible to combine two or more panels, as long as they are from the same series. In the case of flush mounting, to fit them perfectly, you must use a set of joining bolts ref. 8829 for every two panels that are installed.

ACCESSIBILITY

CORA offers **visual and audible notifications**, and there is also the possibility to connect an **inductive loop** (ref.7722) for people with hearing aids or hearing impairment.

OUTDOOR PANELS



SKYLINE Panel



SKYLINER
The wizard to
create your
SKYLINE



Modular panel.



Made in anodised
aluminium (IP43 IK07).



Chromed zamak pushbuttons
and reinforcements.



Wide angle colour camera
(Vertical=80°, Horizontal=120°).



Illumination for vision in low-light
conditions.

3.5" graphic display on digital panels:

- Display activation by presence sensors.
- Electronic directory agenda of residents.
- Menu-driven configuration from the keypad.
- Information pictograms (One-To-One) with the communication status (calling, in communication, door open, channel busy).
- Upload images, logos and personalised messages.
- Alphanumeric call to apartment.

Keypad:

- The metallic keys are made of zamak. It has permanent backlighting.
- Through the keypad it is possible to activate the installation's electric lock with a previously programmed PIN. 10,000 different users/ codes in DUOX PLUS system.

Proximity reader:

- 125KHz (EM) or 13,56MHz (Mifare / Desfire) technology.
Recommended: Desfire.
- Two configuration modes: standalone (up to 400 users).
- Wiegand-26 (up to 10,000 users if connected to the display).



SKYLINE consists of 9 different-sized frames where different modules can easily be fitted. Modules come in 2 sizes, designated V and W. W is twice the size of V.



ACCESSIBILITY

Voice synthesiser with the "The door is open" message in 32 languages.

Integrated One-To-One. Visual information of the communication status (calling, in communication, door open, channel busy). In the One-to-One module with inductive loop, the induction system included in this module allows to transform the audio signal into a magnetic field adapted to the hearing aids or prostheses of hearing impaired persons.

Numeric keypad backlighted in blue, with marking for blind people on the keys ⑤ and 🔔.

IP65
IK09



MARINE Panel



IP65 IK09 vandal-proof door entry panel.

Made in **stainless steel**, 2.5mm-thick.

AISI 316L

AISI 316L steel, of high quality and resistant to extreme or adverse climatic conditions, wet or corrosive climates.





PROELITE
The wizard to create
your Marine Elite
panels



Wide angle colour
camera (Vertical=85°,
Horizontal=125°).



Illumination for vision in
low-light conditions.

3.5" graphic display on digital panels:

- Display activation by presence sensors.
- Electronic directory agenda of residents.
- Menu-driven configuration from the keypad.
- Information pictograms (One-To-One) with the communication status (calling, in communication, door open, channel busy).
- Upload images, logos and personalised messages.
- Alphanumeric call to apartment.

Keypad:

- The metallic keys are made of zamak. It has permanent backlighting.
- Through the keypad it is possible to activate the installation's electric lock with a previously programmed PIN. 10,000 different users/codes in DUOX PLUS system.

Proximity reader:

- 125KHz (EM) or 13,56MHz (Mifare / Desfire) technology. Recommended: Desfire.
- Two configuration modes: standalone (up to 400 users).
- Wiegand-26 (up to 10,000 users if connected to the display).

MARINE ELITE Panel

Our
differentiating
proposal to
make **your**
projects
unique

- Special formats and dimensions.
- Available in all RAL colours.
- Laser logo or text marking. The engraving is only available on the panels in stainless steel colour.



NEW
Brass finish



ACCESSIBILITY

Voice synthesiser with the "The door is open" message in 32 languages.

Integrated One-To-One. Visual information of the communication status (calling, in communication, door open, channel busy).

Numeric keypad backlit in blue, with marking for blind people on the keys 5 and .

VEO monitor


4.3" (16:9) colour screen
With handset



200x200x23 mm
(44 mm with handset)

VEO-XS monitor

4.3" (16:9) colour screen
Hands-free



125x165x21 mm

Made of high-impact ABS
white plastic.

Silicone buttons.

Surface installation.

Additional configurable
functions such as activating
second access, courtesy light,
etc. (DUOX PLUS relay required).

Colour screen
with OSD menu.

Do not disturb function.

Settings: contrast, brightness,
colour and volume.

Date and time setting.

Apartment entrance
doorbell.

Automatic image capture per call
(memory up to 150 photos).

Auto-on: activate the outdoor panel
and switch the display to another
panel or camera.

Doormatic function (VEO-XS y VEO-XL):
Automatic door opening for
professionals (offices, clinics, etc.).

The same wall mounting connector is used for all monitor models. This makes the installer's job easier and provides great flexibility, allowing each resident in the building to choose the monitor they prefer.

VEO-XL monitor

7" (16:9) colour screen
Hands-free



185x185x21 mm



BLUE is now....

DuoxMe
FERMAX



Call divert to mobile

All Wi-Fi monitors are equipped with Wi-Fi connection that allows forwarding calls to mobile devices to enjoy the DuoxMe service free of charge.

The **DuoxMe** application allows end-users to manage the functions of the video door entry system and much more directly from their smartphone or tablet.



ACCESIBILIDAD

Mechanical buttons allow visually impaired people to locate the buttons to talk and open the door before pressing them.

All Duox Plus monitors are available in a model with inductive loop. In this case, the induction system included in the monitors transforms the audio signal into a magnetic field adapted to the hearing aids or prostheses of the hearing impaired people.





Call divert to mobile/tablet

Free application
DuoxMe
FERMAX



With the DUOX PLUS Wi-Fi monitors, the **call divert to mobile phones comes as standard.**

It allows to **establish communication with the outdoor panels and open the door.**

It allows to **see who is calling** before answering and **open a second auxiliary door.**

Automatic image capture of the caller and their **register in the call log.**

Up to **8 smartphones/tablets in the same apartment** can receive the call **simultaneously.**

It is as simple as downloading the **DuoxMe** app from Google Play or the Apple Store.



Pretend you are at home.

Answer calls from the video intercom on your smartphone.



See who called.

Check the images of those who called while you were away. Download and share them.



Open without keys.

Open the door directly from the app.



Activate the camera.

See what is happening outside your house whenever you want.



Share the access.

Invite family, friends or tenants to receive calls and open for you.



Open with your voice.

DuoxMe is compatible with Android, Siri and Apple Watch widgets.

Smart speakers


By connecting to **Alexa and Google Home**, you can receive call notifications from the video intercom on a smart speaker or display.

You can also **use your voice to open the door**, either with smart speakers or displays or with Siri from your iOS device (iPhone, iPad or Apple Watch).



DuoxMe

FERMAX



Door opening without the keys



Change the camera

Hang up the call




Image capture and call history



More information about **DuoxMe**



Answer the call

Open the door



Your voice is the key!

Open the door without stopping what you are doing.



Don't wait for the delivery man!

Open the door with DuoxMe and don't miss that package you've been waiting for.



No one will know you're away


No matter where you are. You'll always have your intercom with you on your smartphone.

Telephones

Made of high-impact ABS with a texturised finish for easy cleaning and ultraviolet protection.



VEO
by FERMAX



LOFT
by FERMAX



iLOFT
by FERMAX

VEO and **LOFT** telephones have a coiled cord with telephone plug connectors. A magnet located within the handset facilitates correct hangup position.

iLOFT telephone allows communication with the outdoor panel in hands-free mode.

VEO, LOFT and iLOFT telephones include the following features:

- Door opener button and call to guard.
- 5 selectable ringtones.
- Ring volume control and "do not disturb" function.
- Doorbell.

Loft Extra and iLOFT phones include buttons for additional functions:

- Lights on, 2nd door opening.
- Loft Extra: 2 additional buttons.
- iLOFT: 1 additional button.

NOTE: Only the iLOFT telephone ref.3450 with version v.44.15 or later is compatible with the CORA panel.



Video Guard Unit

Duox Plus Wi-Fi video guard unit has a multi-functional 4,3" capacitive touch screen and quick function access buttons for easy and convenient management.

Its unique handset design incorporating a magnet enables the end-user to put it back into position correctly. It includes a stainless steel desktop support. It allows a surface installation.



ref.9424
Dimensions: 200x200mm
Desktop support included

Call divert to mobile/tablet



DuoxMe
FERMAX



DUOX_{plus}



In addition to all the standard functions of a DUOX PLUS audio guard unit, this new Wi-Fi video guard unit allows:

- Visualise **video upon receiving a call from the entrance panel** (both in preview and in conversation).
- Visualise **video when selecting a panel** to connect with (Auto-on).
- **Switch the camera** during image visualisation.
- **Receiving and answering** calls from the households.
- **Easy agenda transfer from mobile/tablet/PC/Mac (web server)** by uploading a file with the agenda.
- **Call divert to mobile/tablet (DuoxMe App)** as in DUOX PLUS Wi-Fi monitors.
- **Automatic image capture** (Photocaller).
- Manual image capture.
- **Reception of Panic calls** (configuration as guard unit in Panic mode).
- **Warning** at the guard unit of a **forced outdoor panel** (only with CORA outdoor panel), via door sensor.

References

DUOX^{plus}

FERMAX





Kits references

All the Fermax video kits are Plug & Play (they don't require programming).




Video kits for residences and businesses


STANDARD SOLUTION



94411 1/W DUOX PLUS VEO Wi-Fi KIT
94421 2/W DUOX PLUS VEO Wi-Fi KIT



94511 1/W DUOX PLUS VEO-XS Wi-Fi KIT
94521 2/W DUOX PLUS VEO-XS Wi-Fi KIT



9471 1/W DUOX PLUS VEO-XL Wi-Fi KIT
9472 2/W DUOX PLUS VEO-XL Wi-Fi KIT

ACCESSIBILITY FOR ALL



49081 1/W DUOX PLUS CITY
ONE TO ONE VEO-XS Wi-Fi KIT




50781 1/W DUOX PLUS MARINE ONE TO ONE
VEO-XS Wi-Fi KIT

WITH VANDAL-PROOF PANEL MADE IN STAINLESS STEEL



50731 1/W DUOX PLUS MARINE
VEO-XS Wi-Fi KIT



50831 1/W DUOX PLUS MARINE BLACK
VEO-XS Wi-Fi KIT


WITH KEYPAD ACCESS CODE



49071 1/W DUOX PLUS MEMOVISION
VEO Wi-Fi KIT



49121 1/W DUOX PLUS MEMOVISION
VEO-XS Wi-Fi KIT



49171 1/W DUOX PLUS MEMOVISION
VEO-XL Wi-Fi KIT

Audio kits



**49202 1/W DUOX PLUS AUDIO
CITY VEO KIT**

**49212 2/W DUOX PLUS AUDIO
CITY VEO KIT**



**50772 1/W DUOX PLUS AUDIO
CITY iLOFT KIT**



**50762 1/W DUOX PLUS AUDIO
MARINE iLOFT KIT**



**49132 1/W DUOX PLUS AUDIO
MEMOPHONE CITY VEO KIT**

Outdoor panels and accessories references

Cora Panels



ref.7701



ref.7711

CORA PANEL S6

- 7701 DUOX PLUS CORA PANEL S6**
Dimensions S6: 130x295,5x27,6 mm
- 7702 CORA DIRECTORY PANEL S6**
Dimensions S6: 130x295,5x27,6 mm

It can be mounted on both sides of the CORA panel, even several together (up to 3).
1 directory can be powered from the panel. If there are 2 or 3 directory panels, these must be supplied with an additional power supply.

A directory panel can be installed together with CORA S6 panels in order to record the name corresponding to each apartment code or any other additional information. It includes LEDs for illumination.

CORA PANEL S8

CORA in size SERIE 8 facilitates retrofits in existing Cityline/Skyline S8 flush boxes (in this case, the CORA PANEL FLUSH MOUNTING SET ref.7708 must be ordered separately).

It can also accommodate the DESFIRE SKYLINE PROXIMITY READER (ref.7463) or RFID proximity readers from other manufacturers, if required.

The black front part can be replaced by the front display with proximity iconography (ref. 7720), which includes a fixing element for these additional readers.

The additional proximity reader can be connected to an external door controller or the Wiegand input of the panel, or send the identifiers read from the integrated EM 125KHz reader to an external controller, such as AC-MAX (ref.5223 or ref.5224).

- 7711 DUOX PLUS CORA PANEL S8**
Panel dimensions S8: 130x390,5x27,6 mm
- 7720 CORA PROXIMITY FRONT VISOR**
- 7722 CORA PANEL INDUCTIVE LOOP**
- 7708 CORA PANEL FLUSH MOUNTING SET**
Only necessary when retrofitting into standard City / Skyline S6 (ref.8856) or S8 (ref.8858) flush boxes. This accessory is NOT necessary when using the CORA S6 (ref.7703) or S8 (ref.7713) flush boxes.
- 8829 JOINING BOLTS SET**
It allows to combine two or more frames. One set is required for each additional frame installed on flush box.



	FLUSH BOX	SURFACE BOX	HOOD SINGLE	FRAME		ANGULAR COMPLEMENT
				SINGLE	DOUBLE	
S6	ref.7703 115x280x45	ref.7709 130x295,5x20	ref.7705 130x12x31	ref.7706 225x415x3	ref.7707 355x415x3	ref.7704
S8	ref.7713 115x375x45	ref.7719 130x390,5x20	ref.7705 130x12x31	ref.7716 225x510x3	---	ref.7714

NOTE: Only the iLOFT telephone ref.3450 with version v.44.15 or later is compatible with the CORA panel.

Dimensions: (width) x (height) x (depth) mm.

Outdoor panels and accessories references

Skyline Panels



SKYLINER
The wizard to
create your
SKYLINE

FRAMES



VIDEO



ref.73911
Video W

ref.73902
Audio W

DOUBLE PUSHBUTTONS



ref.7371
8 PUSH. 2x4 W

ref.7372
4 PUSH. 2x2 V

ref.7376
2 PUSH. 2x1 V

SIMPLE PUSHBUTTONS



ref.7367
4 PUSH. 1x4 W

ref.7368
2 PUSH. 1x2 V

ref.7375
1 PUSH. 1x1 V

INFORMATIVE MODULES



ref.7445
Panoramic
cardholder W

ref.7444
Panoramic
cardholder V

ref.7448
One-To-One V

ref.7452
One-To-One V
w/inductive loop

ACCESS CONTROL



ref.7438
Memokey
keypad W

ref.7463/7440
Proximity reader V
Desfire / EM


DIGITAL MODULES

DIRECT PANEL



ref.7439
Direct keypad W


DIGITAL PANEL



ref.7470
Graphic display W

ref.7457
Digital keypad W

ACCESSORIES



ref.7443
Metallic complement W

ref.7442
Metallic complement V

Dimensions: (width) x (height) x (depth) mm.

Outdoor panels and accessories references

Skyline panel



	FLUSH BOX	SURFACE BOX	HOOD		MODULAR FRAME*	CITY FRAME		ANGULAR COMPLEMENT
			SINGLE	DOUBLE		SINGLE	DOUBLE	
S1	ref.8851 115x114x45	ref.7061 130x128x33	ref.8400 135x130	-	ref.9191 211x210	ref.8251 225x310	-	ref.8378
S2	ref.8852 115x138x45	ref.7062 130x151x33	ref.8401 135x155	-	ref.9192 211x234	ref.8252 225x310	-	ref.8379
S3	ref.8853 115x162x45	ref.7063 130x175x33	ref.8402 135x177,5	-	ref.9193 211x257	ref.8253 225x375	-	ref.8380
S4	ref.8854 115x185x45	ref.7064 130x199x33	ref.8403 135x203	ref.8411 265x203	ref.9194 211x281	ref.8254 225x375	ref.8427 355x385	ref.8381
S5	ref.8855 115x233x45	ref.7065 130x246x33	ref.8404 135x250	ref.8412 265x250	ref.9195 211x329	ref.8255 225x375	ref.8428 355x385	ref.8382
S6	ref.8856 115x280x45	ref.7066 130x294x33	ref.8405 135x300	ref.8413 265x300	ref.9196 211x376	ref.8256 225x450	ref.8429 355x460	ref.8383
S7	ref.8857 115x328x45	ref.7067 130x341x33	ref.8406 135x345	ref.8414 265x345	ref.9197 211x424	ref.8257 225x450	ref.8430 355x460	ref.8384
S8	ref.8858 115x375x45	ref.7068 130x389x33	ref.8407 135x393	ref.8415 265x393	ref.9198 211x471	ref.8258 225x450	ref.8431 355x460	ref.8385
S9	ref.8982 115x420,5x45	ref.7069 130x436,5x33	ref.8480 135x440,5	ref.8483 265x440,5	ref.9199 211x519	ref.8259 225x495	ref.8474 355x500	ref.8386
S10	ref.8983 115x471x45	ref.7081 130x486x33	ref.8481 135x488	-	-	ref.8264 225x543	-	ref.8387

* To make DOUBLE modular frames, add to the SINGLE frame a DOUBLE PANEL MODULAR FRAME KIT (ref.9200). Horizontal: 341mm.


* To make TRIPLE modular frames, add to the SINGLE frame a TRIPLE PANEL MODULAR FRAME KIT (ref.9201). Horizontal: 471mm.

If the configuration requires more than one panel



8829 JOINING BOLTS SET

It allows to combine two or more frames. One set is required for each additional frame installed on flush box.



A cable is required per each additional frame in order to connect the pushbutton modules between both frames (70 cm).

2541 DUOX PLUS/VDS CONNECTION CABLE (6W)

2542 DUOX PLUS/VDS CONNECTION CABLE (5W)

Dimensions: (width) x (height) x (depth) mm.



PROELITE
The wizard to create
your Marine Elite
panels

Marine panel



ref.44438
1 Pushbutton



ref.44338
1 Pushbutton



ref.44348
2 Pushbuttons

Dimensions: 150x180mm



ref.55261

ref.5471

Dimensions: 150x360mm



ref.55282

Dimensions: 150x420mm



ref.55289

Dimensions: 150x485mm



Dimensions: (width) x (height) x (depth) mm.

PUSHBUTTON PANELS

The MARINE outdoor panels with pushbuttons (except 1 and 2 ways panels), always require a call extension module, depending on the number of pushbuttons. (ref. 2008 - 8 call extension module, ref. 2441 - 16 call extension module).

	FLUSH BOX	SURFACE BOX (with hood)	SIMPLE HOOD (for flush box)
ST1	ref.4641 130x160x55	ref.4645 154x184x96	ref.4701

DIGITAL PANELS

- The DIGITAL MARINE panel includes a keypad to call the apartments by dialling the door number or the corresponding code.
- The DIRECTORY DISPLAY allows the user to search for residents and their door number.
- Once the code is dialled, press the BELL KEY to call.
- The metallic keys are made of zamak. It has permanent back lit keys.
- Through the keypad it is possible to activate the installation's electric lock with a previously programmed PIN. 10.000 different users/codes in DUOX PLUS system.

55261 DUOX PLUS DIGITAL MARINE VIDEO PANEL ST3

5471 DIRECTORY PANEL ST3

55282 DUOX PLUS DIGITAL MARINE VIDEO PANEL DESFIRE ST3+

55289 DUOX PLUS DIGITAL 1/W MARINE VIDEO PANEL DESFIRE ST4

If the configuration requires more than one panel, they will need to be connected together with a connection cable (ref. 2541) (1 cable for each additional panel) and a set of joining bolts (ref. 2289) to attach them to unite the flush boxes.

	FLUSH BOX	SURFACE BOX (with hood)	SIMPLE HOOD (for flush box)
ST3	ref.4643 130x340x55	ref.4647 154x364x96	ref.4703
ST3+	ref.4653 130x400x55	ref.4654 154x423x96	ref.4655
ST4	ref.4644 130x465x55	ref.4648 154x489x96	ref.4704

Marine Elite panel

31728 DUOX PLUS MARINE ELITE PANEL

4579 MARINE ELITE RAINHOOD FOR FLUSH BOX PANEL

4580 MARINE ELITE FLUSH BOX


4581 MARINE ELITE SURFACE BOX WITH HOOD

Indoor terminals and complements references


VEO and VEO-XS 4.3" colour monitors and VEO-XL 7" colour monitors are made from high-impact ABS plastic. They include automatic capture of images with the call (memory up to 150 photos), adjustment of contrast, brightness, colour, audio volume and call tone volume, "do not disturb" function, doorbell, date and time settings, silicone door opener buttons to activate the door opener, access the on-screen OSD menu, activate the outdoor panel camera or any another additional function that can be configured as for example activate a second access, courtesy light, etc. Available in white and surface installation.



VEO 



VEO XS 



VEO XL 



ref.9447

VEO, VEO-XS and VEO-XL Wi-Fi monitors



DUOX PLUS VEO, VEO-XS and VEO-XL Wi-Fi monitors are equipped with Wi-Fi connection that allows to forward calls to mobile devices. Thanks to Ferman DuoxMe app, the functions of the video door phone and much more can be managed from a smartphone or a tablet.

- 9446 DUOX PLUS VEO Wi-Fi MONITOR**
-  **9456 DUOX PLUS VEO Wi-Fi MONITOR WITH INDUCTIVE LOOP**
Dimensions: 200x200x23mm (44 mm with handset).
- 9449 DUOX PLUS VEO-XS Wi-Fi MONITOR**
-  **9459 DUOX PLUS VEO-XS Wi-Fi MONITOR WITH INDUCTIVE LOOP**
Hands-free. Dimensions: 125x165x21 mm.
- 9469 DUOX PLUS VEO-XL Wi-Fi MONITOR**
-  **9479 DUOX PLUS VEO-XL Wi-Fi MONITOR WITH INDUCTIVE LOOP**
Hands-free. Dimensions: 185x185x21mm.

9447 DUOX PLUS CONNECTOR

The same wall mounting connector is used for all monitor models. This makes the installer's job easier and provides great flexibility, allowing each resident in the building to choose the monitor they prefer.

Note: The Wi-Fi option does not require additional power supply compared to the non-Wi-Fi alternative.

VEO, VEO-XS and VEO-XL monitors

- 9445 DUOX PLUS VEO MONITOR**
-  **9455 DUOX PLUS VEO MONITOR WITH INDUCTIVE LOOP**
Dimensions: 200x200x23mm (44 mm with handset).
- 9448 DUOX PLUS VEO-XS MONITOR**
-  **9458 DUOX PLUS VEO-XS MONITOR WITH INDUCTIVE LOOP**
Hands-free. Dimensions: 125x165x21 mm.
- 9468 DUOX PLUS VEO-XL MONITOR**
-  **9478 DUOX PLUS VEO-XL MONITOR WITH INDUCTIVE LOOP**
Hands-free. Dimensions: 185x185x21mm.

9447 DUOX PLUS CONNECTOR

The same wall mounting connector is used for all monitor models. This makes the installer's job easier and provides great flexibility, allowing each resident in the building to choose the monitor they prefer.




Note: In models with inductive loop, the induction system included in the monitors allows to transform the audio signal into a magnetic field adapted to the hearing aids or prostheses of hearing impaired persons.

Dimensions: (width) x (height) x (depth) mm.

TELEPHONES



VEO



LOFT
by FERMAX



iLOFT
by FERMAX

3444 DUOX PLUS VEO TELEPHONE

Dimensions: 82x214x43mm

3452 DUOX PLUS LOFT EXTRA TELEPHONE

Dimensions: 85x220x40mm

3450 DUOX PLUS iLOFT TELEPHONE

Dimensions: 90x146,5x20mm.

NOTE: Only the iLOFT telephone ref.3450 with version v.44.15 or later is compatible with the CORA panel.

GUARD UNIT



DUOX PLUS VIDEO Guard Unit has a multi-functional 4,3" capacitive touchscreen and quick function access buttons for easy convenient management. Its unique handset design incorporating a magnet enables the end-user to put it back into position correctly. It includes a stainless steel desktop support. It allows a surface installation.

9424 DUOX PLUS VEO WI-FI VIDEO GUARD UNIT

Dimensions: 200x200mm

Monitors and telephones COMPLEMENTS



ref.9410



ref.9420



ref.5636



ref.3749

9410 VEO MONITOR DESKTOP SUPPORT

9420 VEO-XS AND VEO-XL MONITOR DESKTOP SUPPORT

3749 VEO/LOFT TELEPHONE DESKTOP SUPPORT


5636 iLOFT TELEPHONE DESKTOP SUPPORT

FERMAX desktop supports allow to answer a call to the entrance panel from the office desktop. Made of stainless steel (AISI 316L).

3388 UNIVERSAL DECORATIVE FRAME. 120X240

3389 UNIVERSAL LARGE DECORATIVE FRAME. 210X240

FERMAX Decorative Frames are aesthetic complements. Useful in retrofitting applications or replacement of previous equipment.



ref.3388



ref.3389




3441 LOFT HANDSET WITH INDUCTIVE LOOP

3443 VEO HANDSET WITH INDUCTIVE LOOP

Dimensions: (width) x (height) x (depth) mm.

SIMPLE INSTALLATION (1 Building)

LESS COMPONENTS REQUIRED FOR INSTALLATION.
NO FLOOR DISTRIBUTORS. NO DECODERS. NO SWITCHERS



The only materials required are:

- Panel
- Power Supply
- Monitors and telephones
- Line adaptors

Apartments are easily connected at each level using simple terminal strips.

NOTE: Depending on the type and condition of cable and distances, additional regenerators, decoders or power supply might be required.

Power supply and Adaptors

For most common cases

In the most common installations, DUOX PLUS does not require any installation devices other than the power supply and a pair of line adapters per riser. The maximum number of monitors that can be connected to each power supply ref. 4825 depends on the installation topology, cable type and monitor model, as shown in the tables below.



ref.3255



ref.4825

3255 DUOX PLUS LINE ADAPTOR

Necessary at the beginning and the end of every riser.

4825 POWER SUPPLY + FILTER 24Vdc-2.5A DIN10

TERMINAL CONSUMPTION TABLE PER POWER SUPPLY IN **DISTRIBUTION (6 PER FLOOR)**

	NO Wi-Fi			Wi-Fi		
	VEO	VEO-XS	VEO-XL	VEO	VEO-XS	VEO-XL
1.0mm	40	40	34	28	28	24
0.5mm ²	40	38	30	24	24	18
0.2mm ²	32	26	20	18	18	12

TERMINAL CONSUMPTION TABLE PER POWER SUPPLY **IN CASCADE**

	NO Wi-Fi			Wi-Fi		
	VEO	VEO-XS	VEO-XL	VEO	VEO-XS	VEO-XL
1.0mm	40	38	30	26	22	20
0.5mm ²	32	28	22	20	18	14
0.2mm ²	16	14	10	12	10	8

For specific cases



ref.4840



ref.3289

4840 POWER SUPPLY DIN-6 100-240VAC/24VDC-2A

To be used exclusively with the filter ref. 3289 or with the 2-way regenerator ref. 3269.

3289 DUOX PLUS FILTER 24VDC

In case the ref. 4825 cannot be installed due to lack of space. This filter can be used only with 24Vdc power supply (ref. 4840). Do not use it with 18Vdc. power supply.



ref.4802



ref.4800

4802 POWER SUPPLY DIN4 230VAC 12VAC/1A

12Vac for altern current lock release.

4800 POWER SUPPLY DIN4 230VAC 12VAC/1.5A

12Vac for altern current lock release.

Door lock release



UNIVERSAL DOOR LOCK RELEASE

67501 UNIV. LOCK RELEASE 990N-P22 MAX 10-24Vac/dc

UNIVERSAL ELECTRIC STRIKE


6750 UNIV. ELECTRIC STRIKE 990N MAX 10-24Vac/dc

6752 UNIV. ELECTRIC STRIKE 990A MAX 12-24Vac/dc

Note: If other models of door lock release are used and their power consumption is greater than 250mA, an additional separate power supply must be used.

EXTENDED INSTALLATION (multiple buildings or longer distances)

FOR ALL KINDS OF PROJECTS WITH LONGER DISTANCES, VERTICAL STRUCTURES OR HORIZONTAL INSTALLATIONS




DUOX PLUS allows you to push the boundaries of digital technology.

Thanks to the digitalisation of the system, it can now be used in all kinds of installations. The more complex the installation is, the more powerful DUOX PLUS will be. Regenerators and decoders are the only elements to be added for large installations or long distances.

Regenerators and Decoders

Regenerators and decoders take scalability to the next level. No installation, no matter how large, can resist DUOX PLUS.



ref.3269



ref.3268

REGENERATORS

It allows to regenerate and amplify the signal in both ways, as well as amplify distances and number of indoor terminals. Moreover, the connected sections to input and output protect against short-circuit, charge and signal reflections mutually. Maximum 5 units in cascade. Up to 99 if connected in parallel.

3269 2/W DUOX PLUS REGENERATOR

It has 1 input and 2 outputs. By having 2 outputs (also isolated from each other) it enables the number of risers to be increased. Requires 24Vdc power supply without filter (ref. 4840).

For more information: <https://fermax.com/intl-en/documents>

3268 1/W DUOX PLUS DUAL REGENERATOR

It has 1 input and 1 output. As per factory default settings, electrical energy does not flow, but this can be configured via a dipswitch so that the data (which regenerates) as well as the power supply can pass through. That way there is no need to always install a power supply at the output. The number of devices that can be fed at the output without an additional power supply units will depend on the power that reaches the regenerator. For more information: <https://fermax.com/intl-en/documents>

	3269	3268
Number of inputs	1	1
Number of outputs	2	1
Regenerates	YES	YES
Isolates	YES	YES
Incorporates power supply filter	YES	NO
Additional conversation channel per riser	NO	YES
		(in multichannel mode)

DECODERS

9419 10/W DUOX PLUS DECODER/ISOLATOR

10-outputs floor decoder. One output per home, allowing up to 3 terminals (monitors/telephones) per home. Multiple decoders can be installed on each floor. Each output allows to increase the diversion distances on a floor up to 100 m.

In the event of a malfunction (short circuit) of any of the decoder's outputs, both the input DUOX PLUS bus and the rest of the outputs will continue to operate normally. In addition, when a short-circuit occurs on an output, the red LED associated with the output will light up, indicating the output on which the fault has occurred.

It is not necessary to enter a house to program the address of the terminal since the decoder includes a group of microswitches (dipswitches) to program the addresses of each of its outputs (sequential programming). Also, the decoder addresses can be programmed non-sequentially (open programming).

The decoder is powered directly from the DUOX PLUS bus. With DIN10 rail mounting and removable terminal strips for easy wiring and installation.

9425 4/W DUOX PLUS DECODER/ISOLATOR

Same as ref. 9419 but this is a 4-outputs floor decoder (DIN4) and the terminal strips are not removable.

WHEN IS IT RECOMMENDED TO INSTALL THE SMART DECODER?

- When we have to install more than 6 terminals per floor in the building.
- When the distance between the terminals and the riser is greater than 25 metres or when this distance is unknown.
- When different types of wires are mixed in the same installation or all the cables go to the same point.

ADDITIONAL FUNCTIONS

MORE SECURITY

Add IP cameras to monitor specific areas of the building

Bring security
to all your
installations!



9453 IP/DUOX PLUS INTERFACE+CAMERA KIT



It includes the IP/DUOX PLUS camera interface (ref.9454) and the IP camera (ref.9985) already pre-configured for the most common case of an outdoor panel and an additional camera. It also includes the camera power supply (ref.9982) and its adapter (ref.9984).

IMPORTANT: Check compatibility with the technical department.

9454 IP/DUOX PLUS CAMERA INTERFACE


Allows the integration of IP video CCTV cameras into a DUOX PLUS installation. It transforms the IP video signal (standard RTSP) into a DUOX PLUS signal that is connected directly to the DUOX PLUS bus.

- Generally, one interface will be required for each camera installed in the DUOX PLUS installation. However, in the particular case of 2 cameras in the same block, up to 2 cameras can be configured on the same interface (in this case a PoE switch is required).
- Each camera will be powered externally with its additional power supply (ref. 9982+ref. 9984) or via a PoE switch.
- The interface is powered directly from the DUOX PLUS bus.

An outdoor panel can be associated to the interface, so that, while the IP camera is being viewed, it is possible to activate the opening of this panel.

DIN 6 rail mounting (including lateral fixing brackets for screws, width 106 mm). If the lateral fixing brackets for screws are removed, the width is 89 mm (DIN 5).

IMPORTANT: Check compatibility with the technical department.



9985 PERIPHERAL IP DOME CAMERA

IP minidome camera (ceiling mount), 2MP resolution, 2.8mm fixed lens, IR LEDs, 30m range.

9982 POWER SUPPLY PERIPHERAL CCTV CAMERA

Power supply for analogue or IP auxiliary cameras.

9984 POWER ADAPTOR PERIPHERAL CCTV CAMERA

Power adaptor, with a jack plug to connect the power supply to the camera.

1586 4 POE PORTS SWITCH



ref.9985



ref.1586

MORE FUNCTIONS

Activate a second gate, garden gate, or garage entrance door with DUOX PLUS relays that connect directly to the system bus, without additional wiring



ref.3233

3233 DUOX PLUS BASIC RELAY


Basic functions. Allows you to activate an additional function from F1 or F2 of the DUOX PLUS terminals, without additional wiring. The relay can also be activated by the call or by activating the lock release. It can be connected at any point of the bus.



ref.3267

3267 DUOX PLUS RELAY MODULE

Advanced functions. Allows you to pair 2 relays, 1 as a transmitter and other as a receiver, to perform remote activations. An address can be programmed with the address assistance (001-999) using the DUOX PLUS Programmer ref. 3254 via the relay's telephone connector.



ref.2040

CALL ACCESSORIES

2040 ELECTRONIC CALL EXTENSION BELL



ref.5925

CABLES

5925 DUOX PLUS PARALLEL CABLE 2x1mm2

TESTER



ref.9404

9404 DUOX PLUS TESTER

The DUOX PLUS Tester is the ideal tool for the installer. It is used to assess the operation of each outdoor panel with the DUOX PLUS terminals in an installation, without the need to enter the apartments.

A test is initiated from a panel to one or more terminals and the operation of that panel with those terminals is checked.

This action is performed from a user interface on a web browser. From a mobile phone, tablet or computer we can connect to the installation through the Wi-Fi generated by the TESTER DUOX PLUS.



www.fermax.com | www.fermax.com/duoxme/en

