

mammut.de


All data, information, statements, photographs and graphic illustrations in this leaflet are without any obligation and raise no liabilities to or form part of any sales contracts of Nähmaschinenfabrik Emil Stutznacker GmbH & Co.KG or any affiliates for equipment and/or systems referred to herein. © Nähmaschinenfabrik Emil Stutznacker GmbH & Co.KG 2023. All rights reserved. No part of this copyrighted work may be reproduced, modified or distributed in any form or by any means, or stored in any database or retrieval system, without the prior written permission of Nähmaschinenfabrik Emil Stutznacker GmbH & Co.KG or its affiliates. Any such unauthorized use for any purpose is a violation of the relevant copyright laws. Nähmaschinenfabrik Emil Stutznacker GmbH & Co.KG, Max-Planck-Straße 3, 50858 Cologne, Germany



mammut.de

MAMMUT P2S/P1S

combines variety of patterns and accuracy



The single-needle sewing machine with tenting frame for exclusive quilting. It combines the best in sewing qualities with extreme speed and excellent pattern precision. It is especially well suited for mattress or quilt production in smaller batch sizes.



Video MAMMUT P2S/P1S

The illustration shows MAMMUT P2S/P1S with optional equipment.

For demanding applications

- » A Double-sided guidance system ensures highly precise movements of the tenting frame, even with frequent or oscillating changes of direction.
- » Especially large needle stroke of 53 mm instead of the standard 40 mm allowing sewing without wrinkles of elastic or very thick materials.
- » Presser foot pause manoeuvre allows for pin-point accuracy with thinner needles.
- » A second variable use sewing head is available for even shorter quilting times. This way two pieces of fabric can be processed in parallel or one piece can be processed with two sewing heads simultaneously.
- » Large bobbin capacity; Optional automatic bobbin changer.



Double Lockstitch
Featuring a threefold revolving hook with a floating bobbin case, thereby providing non-sensitive settings and a high degree of sewing precision.



Versatile handling
Easy accessibility to all operating and setup functions.



Productivity
High output quantity achieved by utilizing a paralleled working process with a double sewing head.



Flexibility
Ideally designed for small batch sizes and frequent changes in terms of the materials used.



Innovation
Singular and specially designed industrial sewing heads for the processing of multi-layered and large surface materials.



Durability
Extremely stable design of all parts for long lasting durability and a low level of maintenance work.

FURTHER INFORMATION

ELECTRICAL DATA	MECHANICAL DATA	GENERAL MACHINE DATA
<ul style="list-style-type: none">▪ 3 Phase / 400 V▪ 50-60 Hz▪ 3.5 KW	<ul style="list-style-type: none">▪ 8,350 x 4,550 mm (L x W)▪ Weight approx. 1,500 kg▪ Compressed air 6 bar▪ Air consumption 250 l / min	<ul style="list-style-type: none">▪ up to 2.650 stitches / minute▪ max. sewing area 3,500 x 3,600 mm▪ Stitch length 2-8 mm