

BRIO TOP

PRESSURE DROP:

Connection 1": 150 lt/min 0,4 bar
Connection 1 1/4": 150 lt/min 0,3 bar

AUXILIARY CONNECTION

For connection in twin booster sets, remote control systems and/or float switch

AUTOMATIC FLOW AND PRESSURE CONTROL MODE (P+F)

PRESSURE SWITCH MODE (P+P)

P+F: adjustment range of starting pressure 0,5-8 bar

P+P:

adjustable starting pressure 0,5 - 8 bar
adjustable stopping pressure 0,8 - 9 bar
minimum differential 0,3 bar

PROTECTION:

Anti-locking
Anti-freeze
Severe teak

CAPACITOR COMPARTMENT
FOR INSTALLATIONS WITH
SUBMERSIBLE PUMPS

INSPECTIONABLE
CHECK VALVE

1" 1/4 - 1"



POWER SUPPLY

115-230V 50 - 60 Hz



MAX RATED CURRENT

16A



FUNCTIONING

FLOW AND PRESSURE
CONTROLLER or
DIGITAL PRESSURE SWITCH



STANDARD
SETTING

1,5 bar



PROTECTION
DEGREE

IP 65



MAX ALLOWABLE
PRESSURE
(not adjustable)

10 bar

BRIO TOP



PRESSURIZATION



WASHING



IRRIGATION



WATER SUPPLY



PUMP:

CENTRIFUGAL
SELF-PRIMING
SUBMERSIBLE