



KOTAR

MANUFACTURER OF INSULATION MATERIALS

POLYPROPYLENE FABRIC

Kotar's polypropylene fabric protects styrofoam boards against moisture and provides them with support in proper anchoring of the floor heating pipe fixing clamps.

OUR PRODUCT IS COATED, WHICH MAKES THE FABRIC THE PERFECT INSULATION AGAINST MOISTURE.

Fabric width:

Thickness:

103 cm ± 1%

0,12mm ± 10%

The best effects can be achieved by using the fabric with Kotar's EPS boards and pipe fixing clamps.

TO HAVE THE FABRIC'S PROPERTIES CUSTOMIZED, PLEASE CONTACTING US VIA E-MAIL OR TELEPHONE.

THE FABRIC IS DELIVERED IN THE FORM OF A RIBBON WITH 50 RUNNING METRES IN LENGTH.

TECHNICAL SPECIFICATION	STANDARD	UNIT	RESULT	TOLERANCE
Coated fabric surface density	EN ISO 2286-2	g/m ²	72	(+/-) 5 %
Coating surface density	EN ISO 2286-2	g/m ²	20	(+/-) 5 %
Non-coated fabric surface density	EN ISO 2286-2	g/m ²	52	(+/-) 5 %
Tensile strength (warp)	EN ISO 527-3	N/5cm	668	(+/-) 10 %
Tensile strength (weft)	EN ISO 527-3	N/5cm	590	(+/-) 10 %
Elongation (warp)	EN ISO 527-3	%	20	(+/-) 10 %
Elongation (weft)	EN ISO 527-3	%	20	(+/-) 10 %
Shrinkage 2h - 50°C		%	1	1%>
Shrinkage 2h - 60°C		%	1	1%>
Shrinkage 2h - 70°C		%	1	1%>
Crest		mN/m	40	-2/2
Warp tape width		mm	3	(+/-) 0,15 mm
Weft tape width		mm	4	(+/-) 0,15 mm

REEL DATA

Core	76 mm
Standard width	1030 mm
Packaging	pallet

RELATED PRODUCTS



IZOROL-PP PACK



IZOROL-PP DUO

FOLLOW US



30 years KOTAR

KOTAR Sp. z o.o.

ul. Kościuszki 33
56-100 Wołów

e-mail: sekretariat@kotar.pl

phone +48/71 389 23 16

www.kotar.pl