

THREE-IN-ONE ENTERPRISES Co.,LTD

No.34, Guang Hua Rd, San Chung Dist, New Taipei City, 241 Taiwan.

www.endoscope.com.tw



Basic Information

Business Started: 1974

President: Mr. Edward Chen

General Manager: Ms. Victoria Lin

Employees Number: 63 persons

Business Type: Manufacturer (OEM / ODM)

Address: 34 Sanchong Dist., New Taipei City,

241, Taiwan



Mr. Edward Chen

We believe our future is developing related products and putting more focus in R&D we will do our best, thank you for your supporting.

Product Development







Started with plastic injection mold



2004

Fiber Optical Endoscopes



1977

Auto Testers



2005

USB Type Video Endoscopes



1980

Windshield Tools



2006

Monitor Type Endoscopes



1995

Refractometers




2016

Medical Type Endoscopes



Organization Chart



Company Strengths



R&D Partnership with Leading Institutes







Company Strengths



Certifications



ISO 9001:2015



Certificate

Certificate of Registration

THREE-IN-ONE ENTERPRISE CO., LTD.

Scope: Manufacturing of Maintenance Tool, Tester and Industrial Borescope for Automobiles

No. 34, Guanghua Rd., Sanchong Dist., New Taipei City,241 Taiwan, R.O.C.

AFNOR ASIA certifies that all the arrangements covering the above mentioned activities and locations are established to meet the requirements of the international standard:

ISO 9001: 2015 (CNS 12681)

CERTIFICATION



afrior

Taiwan Small & Medium Enterprises Innovation Award

中小企業創新研究獎證書

全崴科技有限公司

長期從事創新研究,以

電子式工業用內視鏡

申請第15屆中小企業創新研 究獎,經評審通過,特頒此 證,以資鼓勵。

經濟部中小企業處處長

中華民國 97年 11月 28日

MEDIUM ENTERPRISES INNOVATION AWARD

This is to certify that

THREE-IN-ONE ENT CO., LTD. has won the 15th Small and Medium Enterprises Innovation Award for its MONITOR-

TYPE BORESCOPE

Director General

Lai, Sem-Quae 2008.11.28











Company Strengths



Patents



More than 100 patents around the world!

Professional Industrial inspection camera Manufacturer



Main Features

- ▶ 3.5" 320 x240 pixel color LCD TFT display for real time monitoring
- ► 640 x 480 pixel resolution in storage
- ▶ Brightness adjustment of LED lamps
- ▶ Digital zoom in/out, photo comparison and image rotation
- Video and images can be saved in SD card or transferred to a PC via AV output or USB output
- Snap-shot while recording / replaying

















▶ Built-in rechargeable Li-ion battery can last up to 2 hours

▶ Ideal for industrial maintenance, aircraft inspection, construction

▶ Record voice-over audio in video recording mode

inspection, vehicle service and HVAC repair, etc

▶ On-screen menus support 26 languages









Professional Industrial inspection camera Manufacturer



Controllers **5"Series**

Controllers **7"Series**



RS Series

RS Special Features

▶5" 800x480 pixel color LCD TFT monitor



MEGA Series

MEGA Special Features

- 7" 720x480 pixel color LCD TFT monitor
- ▶Built-in rechargeable Li-ion battery can last up to 8 hours





























Camera Cables




Cameras & Cables





Wireless Handset







Camera Cables



Self levelling Camera



TX locate track system

Self levelling image always upright





Camera Cables



Lens Cover For Ø25mm, Ø28mm

Big Tube Adapters



Guide Body ► OD Ø 170mm For cameras Ø25mm

Ø28mm

Guide Body ► OD Ø 100mm For cameras Ø25mm

Ø28mm

Accessories



Type B ▶ Handheld Style (Deluxe)



Type D ► Standing Style















Features

► Curvature angle allow to get smoothly tho the throat, reducing the internal damage in the patient's throat.

► Easy insertion in to the patient's throat. Special shape to allow medical team handle the device easy.

> Tube exterior diameter: Ø28mm ▼ Visual distance: 20-100mm Image resolution: 300,000px



Video Laryngoscope


















▶ Size of the auralspeculum: 2.5/3/4/5 mm

Otoscopes

► Magnification: 2 times

► Lamp bulb: 2.5V × O.45A

► Power Supply: 1.5V × 2 "AA"



Hand Slit lamp



- ▶ Slit width: 0.3-4mm Slit length 8-12mm
- ▶ Adds the 20D mirror to be possible to enlarge 6 times more.
- Adds the blue filter can be used for corneal check.
- ▶ Multi-coated optical lens pass rate of increase of light.
- ▶ Parallelism: ≤0.5°
- ▶ The brightness can be adjusted continuously
- ▶ Power Supply: 1.5V × 2 "AA" type
- ► Lamp bulb: 2.5V × 0.45A

Skiascope, Retinoscope



► Illuminance: 80LX

► Minimum width: 1.5mm

▶ Minimum length: 30mm

► Parallelism: ≤0.5°

Form the point spot is less than 25mm

The brightness can be adjusted

continuously

Power Supply: 1.5V × 2 "C" type Lamp bulb: 2.5V X O.45A













Contact Information





THREE-IN-ONE ENTERPRISES Co.,LTD

No. 34, Guang Hua Rd, SanChung Dist, New Taipei City, 241 Taiwan.

www.endoscope.com.tw









+886-2-2999-0096



+886-2-2995-1329 +886-2-2995-6882



endoscope@mr-tools.com.tw

