


PLUG - IN FUSES
(BLADE FUSES)



Fast Acting

- Voltage Rating: DC58V or less
- Interrupting Rating: 1000A @58VDC
- Operating Temperature Range: -40°c to +125°c
- Materials: 1. Zinc Alloy
- 2. Plastic

Complies with SAE J1284 / JASO D612 / ISO 8820-3 / GB/T31465.3
Characteristics of fuses according to use conditions may change.



TIME-CURRENT CHARACTERISTICS

Timing Time	Max.
	5 s

Item No.	Ampere	Color
ATS 1	1 A	Black
ATS 2	2 A	Grey
ATS 3	3 A	Purple
ATS 4	4 A	Pink
ATS 10	10 A	Red
ATS 15	15 A	Blue
ATS 20	20 A	Yellow
ATS 25	25 A	White



Packing No.: 610100
100 pcs / color box,
10,000 pcs / ctn / 1.0’
16 / 17 kgs.



Packing No.: 617010
10 pcs / plastic box,
100 pcs / color box,
5,000 pcs / ctn / 0.7’
11 / 12 kgs.



Packing No.: 630050
50 pcs / plastic box,
5,000 pcs / inner ctn,
10,000 pcs / ctn / 1.6’
19 / 20 kgs.



Packing No.: 630100
100 pcs / plastic box,
5,000 pcs / inner ctn,
10,000 pcs / ctn / 1.3’
19 / 20 kgs.

