

MINI PLUG-IN FUSES
(MINI BLADE FUSES)




Fast Acting

- Voltage Rating : DC58V or less
- Interrupting Rating: 1000A @58VDC
- Operating Temperature Range: -40°c to +125°c
- Materials: 1. Zinc Alloy
- 2. Plastic

Complies with SAE J2077 / JASO D612 / ISO 8820-3 / GB/T31465.3

Characteristics of fuses according to use conditions may change.



TIME-CURRENT CHARACTERISTICS

Timing Time		Item No.	Ampere	Color	Item No.	Ampere	Color
	Max.						
5 s.	---	ATN 2	2 A	●	ATN 15	15 A	●
5 s	600 s	ATN 3	3 A	●	ATN 20	20 A	●
5 s	50 s	ATN 4	4 A	●	ATN 25	25 A	○
5 s	5 s	ATN 5	5 A	●	ATN 30	30 A	●



Packing No.: 910100

100 pcs / color box,

10,000 pcs / ctn / 1.0'

8 / 9 kgs.



Packing No.: 917010

10 pcs / plastic box,

100 pcs / color box,

10,000 pcs / ctn / 1.6'

15 / 16 kgs.



Packing No.: 930100

100 pcs / plastic box,

10,000 pcs / inner ctn,

20,000 pcs / ctn / 1.6'

19 / 20 kgs.



Packing No.: 930200

200 pcs / plastic box,

10,000 pcs / inner ctn.