19	Oksys
HD 202	

CHARACTERISTICS		HD 202
		HD202
	TYPE OF REFRIGERANT	R134
95%	AUTOMATIC WORKING CYCLE No manual taps	•
	HIGH PRECISION RECOVERY FUNCTION	•
	AUTOMATIC OIL INJECTION with scale	•
	AUTOMATIC DYE INJECTION with scale	•
	HEATER BELT INCLUDED	•
,	USB PORT	•
	INTERNAL DATA BASE including commercial and agricultural vehicles	•
(D) (a)	INTEGRATED AUTOMATIC NITROGEN AND FORMING GAS LEAK CHECK (CFU-NITRO / CFU-NITRO.HD.XX)	V

INTERNAL FLUSHING

READY TO USE ON HYBRID OR ELECTRIC CARS with rapid oil decontamination system

A/C SYSTEM PROFESSIONAL FLUSHING (ACC-FLUSHING / EASYFLUSH)



ACCESSORIES HD				
	CODE	DESCRIPTION	202	
	ACC-88.072	Gas bottle adapter ¼	V	
	ACC-88.011	Straight adapter HP ¼	V	
	GEAR PUMP	Gear pump 1 L/min.	V	
	O-PK00051 O-PK00051 OPZ	Printer kit	V	

NITROGEN LEACK CHECK OR HYDRO-NITROGEN

CODE **CFU-NITRO**

Kit for the connection of 1 or 2.2 liter cylinders to the A/C station - Including:

- Carrying case
 Pressure reducer for 1 and 2.2 liter bottles
 Manifold for the A/C service station connection

CODE CFU-NITRO.HD.XX

- Inclusive of:

- Carrying case
- Pressure reducer 200 Bar
- Adapeter for the connection to 1 ans 2,2 L bottles
- Manifold for the A/C service station connection

FLUSHING



Professional Refrigerant R134a or 1234y Flushing Kit. Including expansion cylinder.

RANGE

R134a



MODEL

HD 202

TECHNICAL FEATURES

Display	Graphic LCD 264x64 Pixel
Full Recovery Function	YES
Tank Capacity	40 Kg
Heater Belt	YES
Scale Accuracy	+/- 5 g
Compressor	20 cc
Vacuum Pump	200 L/min Dual Stage
Air Purge	Automatic
Power Supply	220V 50 Hz
Dimensions	55x60x120 cm
Weight	117/126 Kg
Packaging dimensions	80x60x145 cm

SCOPE OF DELIVERY

OOO! E O! DEE!VE!!!	
Hp LP Quick Couplers	Included
Hoses	3 m
Blanket	NO
Power Cord	YES
Calibration Handle	YES
Extra oil bottle	YES
2 x temperature probes	NO

