

DRY

MOTORCYCLE BATTERIES

CONVENTIONAL BATTERY

ROBUST TECHNOLOGY. RELIABLE STARTING POWER.

Landport DRY is a conventional battery with robust technology which delivers reliable starting power and ensures a long life. This lead-acid battery is dry pre-charged and comes with or without a separate acid pack for initial filling. Suitable for almost any motorcycle or scooter with basic power needs. Best choice for customers who are looking for a cheap, reliable starter battery. Available in a range of 6V and 12V batteries from 2Ah to 30Ah.




FEATURES

CONVENTIONAL BATTERY

ROBUST TECHNOLOGY

RELIABLE STARTING POWER

OFFICIAL DISTRIBUTOR



power on command



MODELS AND SPECIFICATIONS

Model	Article number	Voltage (V)	Capacity Ah (10hr)	CCA A (EN)	Length (mm)	Width (mm)	Height (mm)	Total height (mm)	Layout	Terminal
6N2-2A	MA 6N2-2A	6	2	10	70	46	97	97		
6N2A-2C-3	MA 6N2A-2C-3	6	2	10	71	47	105	105		
6N4A-4D	MA 6N4A-4D	6	4	10	60	60	130	130		
6N4C-1B	MA 6N4C-1B	6	4	10	69	70	104	104		
6N4-2A	MA 6N4-2A	6	4	10	71	71	94	94		
6N4-2A-4	MA 6N4-2A-4	6	4	10	71	71	94	94		
6N4-2A-7	MA 6N4-2A-7	6	4	10	71	71	94	94		
6N4B-2A	MA 6N4B-2A	6	4	10	101	47	95	95		
6N4B-2A-3	MA 6N4B-2A-3	6	4	10	101	47	95	95		
6N5,5-1D	MA 6N5,5-1D	6	5,5	10	88	70	98	98		
6N6-1D-2	MA 6N6-1D-2	6	6	30	99	56	109	109		
6N6-3B	MA 6N6-3B	6	6	30	99	58	109	109		
6N6-3B-1	MA 6N6-3B-1	6	6	30	99	58	109	109		
6N7-1 (B39-6)	MA 6N7-1 (B39-6)	6	7	30	125	48	125	125		
B49-6	MA B49-6	6	10	40	90	83	161	161		
6N11A-1B	MA 6N11A-1B	6	11	80	120	60	131	131		
6N11A-3A	MA 6N11A-3A	6	11	80	120	60	131	131		
6N11A-4	MA 6N11A-4	6	11	80	120	60	131	131		
6N12A-2C	MA 6N12A-2C	6	12	80	154	55	115	115		
6N12A-2D	MA 6N12A-2D	6	12	80	154	55	115	115		
B38-6A	MA B38-6A	6	13	30	117	82	160	160		
YB2,5L-C2	MA YB2,5L-C2	12	2,5	10	80	70	106	106		
YB3L-A	MA YB3L-A	12	3	30	100	57	110	110		
YB3L-B	MA YB3L-B	12	3	30	100	57	110	110		
YB4L-A	MA YB4L-A	12	4	50	121	71	92	92		
YB4L-B	MA YB4L-B	12	4	50	121	71	92	92		
YB5L-B	MA YB5L-B	12	5	60	120	60	130	130		
12N5,5A-3B	MA 12N5,5A-3B	12	5,5	55	105	91	115	115		
12N5,5-3B	MA 12N5,5-3B	12	5,5	55	135	60	130	130		
12N5,5-4A	MA 12N5,5-4A	12	5,5	55	135	60	130	130		
12N5,5-4B	MA 12N5,5-4B	12	5,5	55	135	60	130	130		
YB7C-A	MA YB7C-A	12	7	110	132	92	116	116		
12N7-3B-2	MA 12N7-3B-2	12	7	70	137	76	133	133		
12N7-4B	MA 12N7-4B	12	7	70	137	76	133	133		

Model	Article number	Voltage (V)	Capacity Ah (10hr)	CCA A (EN)	Length (mm)	Width (mm)	Height (mm)	Total height (mm)	Layout	Terminal
YB7-A	MA YB7-A	12	7	110	137	76	133	133		
YB7L-B	MA YB7L-B	12	7	110	137	76	133	133		
YB9A-A	MA YB9A-A	12	9	115	137	76	152	152		
YB9B	MA YB9B	12	9	115	137	76	139	139		
YB9L-A2	MA YB9L-A2	12	9	120	137	76	139	139		
YB9L-B	MA YB9L-B	12	9	115	137	76	139	139		
YB10L-A2	MA YB10L-A2	12	11	140	135	90	145	145		
YB10L-B	MA YB10L-B	12	11	140	135	90	145	145		
YB10L-B2	MA YB10L-B2	12	11	140	135	90	145	145		
YB12A-A	MA YB12A-A	12	12	160	134	80	160	160		
YB12A-B	MA YB12A-B	12	12	160	134	80	160	160		
YB12AL-A	MA YB12AL-A	12	12	160	134	80	160	160		
YB12AL-A2	MA YB12AL-A2	12	12	160	134	80	160	160		
YB12C-A	MA YB12C-A	12	12	160	135	80	174	174		
YB12B-B2	MA YB12B-B2	12	12	160	160	90	131	131		
YB14-A2	MA YB14-A2	12	14	180	135	91	166	166		
YB14A-A2	MA YB14A-A2	12	14	180	135	90	177	177		
YB14-B2	MA YB14-B2	12	14	180	135	91	166	166		
YB14L-A2	MA YB14L-A2	12	14	180	135	91	166	166		
YB14L-B2	MA YB14L-B2	12	14	180	135	91	166	166		
HYB16A-A	MA HYB16A-A	12	16	200	148	88	180	180		
YB16B-A	MA YB16B-A	12	16	200	157	89	162	162		
YB16B-A1	MA YB16B-A1	12	16	200	157	89	162	162		
YB16AL-A2	MA YB16AL-A2	12	16	200	206	70	164	164		
YB18A	MA YB18A	12	18	200	181	90	160	160		
YB18L-A	MA YB18L-A	12	18	200	181	90	160	160		
YB16B	MA YB16B	12	19	240	175	99	155	155		
YB16CL-B	MA YB16CL-B	12	19	240	175	100	175	175		
YB16L-B	MA YB16L-B	12	19	240	175	99	155	155		
12Y16A-3B	MA 12Y16A-3B	12	19	240	185	81	169	169		
Y50N18LA2	MA Y50N18LA2	12	20	260	205	90	162	162		
Y60-N24L-A	MA Y60-N24L-A	12	24	260	187	128	167	167		
YHD4-12	MA YHD4-12	12	29	260	202	131	163	163		
YB30CL-B	MA YB30CL-B	12	30	300	167	131	192	192		
YB30L-B	MA YB30L-B	12	30	300	167	131	176	176		
Y60-N30-A	MA Y60-N30-A	12	30	300	187	128	167	167		
Y60-N30L-A	MA Y60-N30L-A	12	30	300	187	128	167	167		

MODELS AND SPECIFICATIONS

Model	Article number	Voltage (V)	Capacity Ah (10hr)	CCA A (EN)	Length (mm)	Width (mm)	Height (mm)	Total height (mm)	Layout	Terminal
YB3L-A	MB YB3L-A	12	3	30	100	57	110	110		
YB3L-B	MB YB3L-B	12	3	30	100	57	110	110		
YB4L-B	MB YB4L-B	12	4	50	121	71	92	92		
YB5L-B	MB YB5L-B	12	5	60	120	60	130	130		
YB7C-A	MB YB7C-A	12	8	110	132	92	116	116		
YB7-A	MB YB7-A	12	8	110	137	76	133	133		
YB7L-B	MB YB7L-B	12	8	110	137	76	133	133		
YB9B	MB YB9B	12	9	115	137	76	139	139		
YB9L-B	MB YB9L-B	12	9	115	137	76	139	139		
YB10L-A2	MB YB10L-A2	12	11	140	135	90	145	145		
YB10L-B	MB YB10L-B	12	11	140	135	90	145	145		
YB10L-B2	MB YB10L-B2	12	11	140	135	90	145	145		
YB12A-A	MB YB12A-A	12	12	160	134	80	160	160		
YB12A-B	MB YB12A-B	12	12	160	134	80	160	160		
YB12AL-A	MB YB12AL-A	12	12	160	134	80	160	160		
YB12AL-A2	MB YB12AL-A2	12	12	160	134	80	160	160		
YB14-A2	MB YB14-A2	12	14	180	135	91	166	166		
YB14A-A2	MB YB14A-A2	12	14	180	135	90	177	177		
YB14-B2	MB YB14-B2	12	14	180	135	91	166	166		
YB14L-A2	MB YB14L-A2	12	14	180	135	91	166	166		
YB14L-B2	MB YB14L-B2	12	14	180	135	91	166	166		
HYB16A-A	MB HYB16A-A	12	16	200	148	88	180	180		
YB16B-A	MB YB16B-A	12	16	200	157	89	162	162		
YB16B-A1	MB YB16B-A1	12	16	200	157	89	162	162		
YB16AL-A2	MB YB16AL-A2	12	16	200	206	70	164	164		
YB18L-A	MB YB18L-A	12	18	200	181	90	160	160		
YB16CL-B	MB YB16CL-B	12	19	240	175	100	175	175		
Y50N18LA2	MB Y50N18LA2	12	20	260	205	90	162	162		
Y60-N24A-LB	MB Y60-N24A-LB	12	24	260	187	128	167	167		
Y60-N24L-A	MB Y60-N24L-A	12	24	260	187	128	167	167		
YB30CL-B	MB YB30CL-B	12	30	300	167	131	192	192		
YB30L-B	MB YB30L-B	12	30	300	167	131	176	176		
Y60-N30-A	MB Y60-N30-A	12	30	300	187	128	167	167		
Y60-N30L-A	MB Y60-N30L-A	12	30	300	187	128	167	167		
Y60-N35L-A	MB Y60-N35L-A	12	30	300	233	131	167	167		

AGM

MOTORCYCLE BATTERIES

ABSORBENT GLASS MAT TECHNOLOGY ADVANCED STARTING POWER. EXCELLENT VIBRATION RESISTANCE.


Landport AGM is a starter battery with Absorbent Glass Mat technology which features advanced cranking performance and excellent vibration resistance. This lead-acid battery is dry pre-charged and comes with a fitting acid pack. Simply fill and charge the battery and it is ready to use! Once activated Landport AGM is completely spill-proof and 100% maintenance free. Suitable for motorcycles, scooters and powersport vehicles used all year round. Available in a range of 12V batteries from 2.3Ah to 21Ah.



FEATURES

- ABSORBENT GLASS MAT TECHNOLOGY
- ADVANCED STARTING POWER
- EXCELLENT VIBRATION RESISTANCE
- 100% MAINTENANCE FREE ONCE ACTIVATED

OFFICIAL DISTRIBUTOR



power on command



MODELS AND SPECIFICATIONS

Model	Article number	Voltage (V)	Capacity Ah (10hr)	CCA A (EN)	Length (mm)	Width (mm)	Height (mm)	Total height (mm)	Layout	Terminal
YT4B-BS	MB YT4B-BS	12	2,3	-	113	38	86	86		
YTR4A-BS	MB YTR4A-BS	12	2,3	40	113	48	85	85		
YTX4L-BS	MB YTX4L-BS	12	3	-	113	70	85	85		
YTX5L-BS	MB YTX5L-BS	12	4	-	113	70	105	105		
YTX7L-BS	MB YTX7L-BS	12	6	100	113	70	130	130		
YTZ7S-BS	MB YTZ7S-BS	12	6	100	113	70	105	105		
YTX7A-BS	MB YTX7A-BS	12	6	105	150	87	93	93		
YT7B-BS	MB YT7B-BS	12	6,5	110	150	66	93	93		
YT9B-BS	MB YT9B-BS	12	8	115	150	70	105	105		
YTX9-BS	MB YTX9-BS	12	8	110	150	87	105	105		
YTZ10S-BS	MB YTZ10S-BS	12	8,6	150	150	88	93	93		
YTX9A-BS	MB YTX9A-BS	12	9	140	135	75	139	139		
YT12A-BS	MB YT12A-BS	12	10	-	150	88	105	105		
YT12B-BS	MB YT12B-BS	12	10	-	150	70	130	130		
YTX12-BS	MB YTX12-BS	12	10	150	150	87	130	130		
YTZ12S-BS	MB YTZ12S-BS	12	11	190	151	87	110	110		
YTZ14S-BS	MB YTZ14S-BS	12	11,2	200	151	87	110	110		
YTX14AH-BS	MB YTX14AH-BS	12	12	200	134	89	166	166		
YTX14AHL-BS	MB YTX14AHL-BS	12	12	200	134	89	166	166		
YTX14-BS	MB YTX14-BS	12	12	190	150	87	145	145		
YTX14L-BS	MB YTX14L-BS	12	12	190	150	87	145	145		
YT14B-BS	MB YT14B-BS	12	12	190	150	70	145	145		
YTX15L-BS	MB YTX15L-BS	12	13	210	175	87	130	130		
YTX16-BS	MB YTX16-BS	12	14	220	150	88	161	161		
YTX16-BS-1	MB YTX16-BS-1	12	14	220	150	88	161	161		
YTX18L-BS	MB YTX18L-BS	12	17,7	300	206	89	162	162		
YTX20CH-BS	MB YTX20CH-BS	12	18	270	150	87	161	161		
YTX20-BS	MB YTX20-BS	12	18	250	175	87	154	154		
YTX20HL-BS	MB YTX20HL-BS	12	18	310	175	87	154	154		
YTX20L-BS	MB YTX20L-BS	12	18	250	175	87	154	154		
YTX24HL-BS	MB YTX24HL-BS	12	21	340	206	89	162	162		

SLA

MOTORCYCLE BATTERIES

ABSORBENT GLASS MAT TECHNOLOGY
ADVANCED STARTING POWER.
EXCELLENT VIBRATION RESISTANCE. READY TO USE!


Landport SLA is a starter battery with Absorbent Glass Mat technology which features advanced cranking performance and excellent vibration resistance. This lead-acid battery is already factory activated (filled and charged) and therefore ready to use! It is 100% maintenance free, completely sealed, spill-proof and leak-proof which makes this battery ultra-safe. Ideal for motorcycles and powersport vehicles on rough terrain and in all weather conditions such as all-terrain vehicles, jet-skis and snowmobiles. Available in a range of 12V batteries from 2.3Ah to 30Ah.



FEATURES

ABSORBENT GLASS MAT TECHNOLOGY
ADVANCED STARTING POWER
EXCELLENT VIBRATION RESISTANCE
100% MAINTENANCE FREE
FACTORY ACTIVATED, READY TO USE!

OFFICIAL DISTRIBUTOR



power on command



MODELS AND SPECIFICATIONS

Model	New	Article number	Voltage (V)	Capacity Ah (10hr)	CCA A (EN)	Length (mm)	Width (mm)	Height (mm)	Total height (mm)	Layout	Terminal
YT4B-5	-	MB YT4B-5	12	2,3	40	113	38	86	86		
YTR4A-S	New	MB YTR4A-S	12	2,3	-	113	48	85	85		
YB3-3	New	MB YB3-3	12	3	-	98	56	110	110		
YTX5-3	New	MB YTX5-3	12	4	-	113	70	105	105		
SLA 12-4S	-	MB SLA 12-4S	12	5	50	113	70	85	85		
YB5-3	-	MB YB5-3	12	5	-	119	59	130	130		
YTX7-3	New	MB YTX7-3	12	6	-	113	70	130	130		
YTZ7-S	-	MB YTZ7-S	12	6	100	113	70	105	105		
YTX7A-4	-	MB YTX7A-4	12	6	105	150	87	93	93		
YT7B-4	-	MB YT7B-4	12	6,5	110	150	66	93	93		
YTZ8V	-	MB YTZ8V	12	7	120	113	70	130	130		
YB7-3	New	MB YB7-3	12	7	80	137	75	124	124		
YB7-4	New	MB YB7-4	12	7	80	137	75	124	124		
YT9B-4	-	MB YT9B-4	12	8	115	150	70	105	105		
YTX9-4	-	MB YTX9-4	12	8	110	150	87	105	105		
YTZ10-S	-	MB YTZ10-S	12	8,6	150	150	88	93	93		
YTX9A-3	New	MB YTX9A-3	12	9	120	135	75	138	138		
YTX9A-4	New	MB YTX9A-4	12	9	120	135	75	138	138		
YB10-3	New	MB YB10-3	12	10	160	134	89	145	145		
YT12B-4	-	MB YT12B-4	12	10	150	150	70	130	130		
YTX12-4	-	MB YTX12-4	12	10	150	150	87	130	130		
YTX12A-4	New	MB YTX12A-4	12	10	-	150	88	105	105		
YTZ12-S	-	MB YTZ12-S	12	11	190	150	88	110	110		
YTZ14-S	-	MB YTZ14-S	12	11,2	200	150	88	110	110		
YB12A-3	New	MB YB12A-3	12	12	165	135	80	160	160		
YB12A-4	New	MB YB12A-4	12	12	165	135	80	160	160		
YT14B-4	-	MB YT14B-4	12	12	190	150	70	145	145		
YTX14-3	New	MB YTX14-3	12	12	200	150	87	146	146		
YTX14-4	-	MB YTX14-4	12	12	200	150	87	146	146		
YTX14AH-3	New	MB YTX14AH-3	12	14	210	134	89	166	166		
YTX14AH-4	New	MB YTX14AH-4	12	14	210	134	89	166	166		
YTX16-4	New	MB YTX16-4	12	14	230	150	87	163	163		
YTX20-3	New	MB YTX20-3	12	18	310	175	87	155	155		
YTX20CH-4	New	MB YTX20CH-4	12	19	320	150	87	163	163		
YB16CL-B (S)	-	MB YB16CL-B (S)	12	19	-	175	100	175	175		
YTX20-4	New	MB YTX20-4	12	20	310	175	87	155	155		
YTX18-3	New	MB YTX18-3	12	21	350	205	85	162	162		
YTX24H-3	New	MB YTX24H-3	12	21	350	205	85	162	162		
SLA 12-22	-	MB SLA 12-22	12	22	230	181	76	167	167		
YTX30L	-	MB YTX30L	12	30	-	166	126	173	173		
Y60-N30-3	New	MB Y60-N30-3	12	30	300	179	125	166	166		
Y60-N30-4	New	MB Y60-N30-4	12	30	300	179	125	166	166		

GEL

MOTORCYCLE BATTERIES

GEL TECHNOLOGY

SUPERIOR STARTING POWER.

SUPERIOR VIBRATION RESISTANCE. READY TO USE!


Landport GEL is a starter battery with gel technology which features maximum cranking performance and extreme vibration resistance. This battery is already factory activated (filled and charged) and therefore ready to use! It is 100% maintenance free, completely sealed, spill-proof and leak-proof which makes this battery ultra-safe. Landport GEL has a low rate of self-discharge which makes it ideal for seasonal use and long-term storage. Best choice for the latest motorcycles and powersport vehicles which not only need to start but also need additional power for onboard energy consumers. Available in a range of 12V batteries from 3Ah to 30Ah.



FEATURES

GEL TECHNOLOGY
SUPERIOR STARTING POWER
SUPERIOR VIBRATION RESISTANCE
VERY LOW SELF-DISCHARGE
100% MAINTENANCE FREE
FACTORY ACTIVATED, READY TO USE!

OFFICIAL DISTRIBUTOR



power on command



MODELS AND SPECIFICATIONS

Model	Article number	Voltage (V)	Capacity Ah (10hr)	CCA A (EN)	Length (mm)	Width (mm)	Height (mm)	Total height (mm)	Layout	Terminal
GTX4-3	MG GTX4-3	12	3	40	114	71	86	86	- +	
GB4L-B	MG GB4L-B	12	4	40	114	71	86	86	- +	
GTX5-3	MG GTX5-3	12	4	60	114	71	107	107	- +	
GB5L-B	MG GB5L-B	12	5	60	120	60	130	130	- +	
GTZ7-S	MG GTZ7-S	12	6	70	113	70	107	107	- +	
GTX7-3	MG GTX7-3	12	6	90	114	71	130	130	- +	
GTX7A-4	MG GTX7A-4	12	6	110	151	88	94	94	+ -	
GT7B-4	MG GT7B-4	12	6,5	90	151	65	93	93	+ -	
GT9B-4	MG GT9B-4	12	8	100	151	70	105	105	+ -	
GTX9-4	MG GTX9-4	12	8	100	151	88	107	107	+ -	
GTZ10-S	MG GTZ10-S	12	8,6	170	151	87	94	94	+ -	
GB9B	MG GB9B	12	9	100	136	75	141	141	+ -	
GB10L-A2	MG GB10L-A2	12	10	160	134	89	145	145	- +	
GT12B-4	MG GT12B-4	12	10	150	151	70	130	130	+ -	
GTX12-4	MG GTX12-4	12	10	160	151	87	131	131	+ -	
GTZ12-S	MG GTZ12-S	12	11	190	151	87	110	110	+ -	
GTZ14-S	MG GTZ14-S	12	11,2	200	151	87	110	110	+ -	
GB12A-A	MG GB12A-A	12	12	120	136	81	158	158	+ -	
GB12AL-A	MG GB12AL-A	12	12	120	136	81	158	158	- +	
GT14B-4	MG GT14B-4	12	12	190	151	70	147	147	+ -	
GTX14-4	MG GTX14-4	12	12	180	151	87	147	147	+ -	
GB14L-A2	MG GB14L-A2	12	14	180	134	90	166	166	- +	
GB16AL-A2	MG GB16AL-A2	12	16	215	205	70	162	162	- +	
GTX20-3	MG GTX20-3	12	18	250	175	87	156	156	- +	
GTX20-4	MG GTX20-4	12	18	250	175	87	156	156	+ -	
GB16B	MG GB16B	12	19	200	177	101	157	157	+ -	
GB16L-B	MG GB16L-B	12	19	200	177	101	157	157	- +	
G12-19	MG G12-19	12	21	230	181	76	167	167	- +	
G50N18LA2	MG G50N18LA2	12	22	300	205	89	164	164	- +	
G60-N30-A	MG G60-N30-A	12	30	330	179	125	166	166	+ -	
G60-N30L-A	MG G60-N30L-A	12	30	325	178	123	166	166	- +	

HVT

MOTORCYCLE BATTERIES

ABSORBENT GLASS MAT TECHNOLOGY SPECIALLY DESIGNED FOR HEAVY V-TWIN MOTORCYCLES


Landport HVT is a starter battery with Absorbent Glass Mat technology which features advanced cranking performance and excellent vibration resistance. With its extremely robust and heat resistance casing this battery is specially designed for heavy V-twin motorcycles that require higher starting power than other motorcycles. This lead-acid battery is already factory activated (filled and charged) and therefore ready to use! It is 100% maintenance free, completely sealed, spill-proof and leak-proof which makes this battery ultra-safe. Best choice for all heavy V-twin motorcycles, especially Harley Davidson. Available in a range of 6V and 12V batteries from 14Ah to 30Ah.



FEATURES

- ABSORBENT GLASS MAT TECHNOLOGY
- ADVANCED STARTING POWER
- EXCELLENT VIBRATION RESISTANCE
- EXTREMELY ROBUST AND HEAT RESISTANCE CASING
- 100% MAINTENANCE FREE
- FACTORY ACTIVATED, READY TO USE!

OFFICIAL DISTRIBUTOR



power on command



MODELS AND SPECIFICATIONS

Model	Article number	OEM Code ¹	Voltage (V)	Capacity Ah (10hr)	CCA A (EN)	Length (mm)	Width (mm)	Height (mm)	Total height (mm)	Layout	Terminal
HVT-3	MB HVT-3	65948-04	12	14	220	148	87	145	145		
HVT-8	MB HVT-8	65948-00	12	14	220	149	87	145	145		
HVT-1	MB HVT-1	65989-97	12	20	320	175	87	155	155		
HVT-4	MB HVT-4	65989-90	12	22	325	173	98	155	155		
HVT-5	MB HVT-5	65991-82	12	22	325	173	98	155	155		
HVT-6	MB HVT-6	66010-82	12	23	300	203	88	162	162		
HVT-2	MB HVT-2	66010-97	12	30	450	169	131	175	175		
HVT-10*	MB HVT-10	66006-29	6	22	-	115	100	214	214		
GHD14H-3**	MG GHD14H-3	65948-04	12	14	220	149	87	144	144		
GHD20H-3**	MG GHD20H-3	65989-97	12	19	290	176	87	154	154		
GHD30H-3**	MG GHD30H-3	66010-97	12	30	430	166	130	175	175		

¹ Original equipment manufacturer battery-code for Harley Davidson

* Please note that HVT-10 is a 6V conventional dry pre-charged battery without acid pack, suitable for classic Harley Davidson models.

**Please note that GHD14H-3, GHD20H-3 and GHD30H-3 are HVT batteries with GEL technology instead of AGM technology.

LFP

MOTORCYCLE BATTERIES

LITHIUM LIFEPO4 TECHNOLOGY

ULTIMATE STARTING POWER. EXTREMELY LONG LIFE.

Landport LFP is a starter battery with lithium LiFePO4 technology which features extreme cranking performance, superior cycle life and ultra-light weight. This battery is completely sealed and 100% maintenance free which makes it ultra-safe and ready to use. It can be installed in multiple positions, even upside down. Landport LFP has a low rate of self-discharge which makes it ideal for seasonal use and long-term storage. Landport LFP is the perfect choice for present and future generation motorcycles and powersports vehicles and is ideal for racing purposes. Available in a range of 9 batteries with only 4 different dimensions which together cover all common battery types (easy adapter pads included)*.


*Not for model LFP01.



FEATURES

LITHIUM LIFEPO4 TECHNOLOGY
ULTIMATE STARTING POWER
EXTREME CYCLE LIFE (UP TO 2.000 CHARGE CYCLES)
ULTRA-LIGHT WEIGHT (1/3 OF SIMILAR LEAD-ACID BATTERY)
VERY LOW SELF-DISCHARGE
INSTALL IN ANY POSITION
100% MAINTENANCE FREE
READY TO USE!

OFFICIAL DISTRIBUTOR



power on command



MODELS AND SPECIFICATIONS

Model	Article number	Voltage (V)	Capacity Ah (10hr)	Energy (Wh)	CCA A (EN)	Length (mm)	Width (mm)	Height (mm)	Total height (mm)	Layout	Terminal
LFP01	ML LFP01	12	2	24	120	92	52	90	90		
LFP5	ML LFP5	12	1,6	19,2	105	107	56	85	85		
LFP7	ML LFP7	12	2	24	120	107	56	85	85		
LFP7Z	ML LFP7Z	12	2,4	28,8	144	107	56	85	85		
LFP9	ML LFP9	12	3	36	180	134	65	92	92		
LFP14	ML LFP14	12	4	48	240	134	65	92	92		
LFP16	ML LFP16	12	5	60	300	165	86	130	130		
LFP20	ML LFP20	12	6	72	330	165	86	130	130		
LFP30	ML LFP30	12	8	96	420	165	86	130	130		