





BRK600 is the newest, universal brake bleeder especially designed for a professional use.

BRK600 is equipped with a **robust integrated and independent pump** for the extraction of used oil.

Working even on hard-to-access trays is made easy using the long 7 meter spiral hose. An integrated filter protects the pump from dirt particles and various residues. Changing the brake oil on a professional level also includes washing the reservoir. For this the old, exhausted and dirty oil is extracted from the fluid reservoir.

The extracted oil is collected in the transparent 5 liter tank. BRK is equipped with a second high quality pump for injecting new oil.

BRK600 is also equipped with a continuous pressure regulator up to 4.2 Bar. The pressure regulator has a safety lock to avoid unintentional manipulations.

The bodywork of BRK600 is particularly robust, as well as all the details such as wheels, hoses and connectors, for a particularly intense and continuous use.







BRAKE BLEEDING ADUANCE SYSTEM

Technical Features:

Compatible Liquids: Pre DOT - DOT2 - DOT3

- DOT4 - DOT5 - DOT5.1 - DOT6 - DOT6.1 - LHM

Capacity of NEW fluid tank: 5 lt standard

(predisposition

fortanks up to 25 lt)

Capacity of USED fluid tank: 5 lt

Operating pressure: 0-4 bar

Pump flow: 1 lt/min

Pump flow: 1 lt/min
Lenght of charging pipe: 7.5 m
Lenght of suction pipe: 7.5 m

Lenght of power supply cable: 3 m

Power supply: 230V 50-60 Hz

Noise: < 70 dB (A)

Noise: < 70 dB (A)
Dimensions: 67x54x90H cm

Weight: 35 Kg

The working pressure can be set on the **pressure regulator** (secured against unintentional manipulation) and read on the pressure gauge.

The **7 meter length of the filling hose** is able to satisfy any type of requirement.



