

ŎO

000 00

Stampof Quality

IATF 16949 Company

Aboutus

Goldy Precision Stampings Pvt. Ltd. is a leading manufacturer of precision stampings and Sheet metal components and its subassemblies.

Goldy can stamp any type of sheet metal allied material from thickness 0.025 mm to 8 mm having a diameter from 3mm to 450 mm.

We have an in house Tool Design and Manufacturing capability. We use software like Pro E-Wildfre along with Pdx Extension, Autocad, Unigraphics to design the tools which are manufactured on state of art machines like Vertical Milling Center, CNC Wire Cut, EDM Drilling, Spark Erosion and conventional machines.

We manufacture precision components on High Speed Automatic Press Lines varying from 15 tons to 350 tons. Strokes per minute varies from 60/min to 1200/min.

Goldy believes in continuous improvement and follows IATF16949 standard to achieve international quality. Goldy's Quality Assurance & Control Department is equipped with advanced quality instruments like...

- Tesa Vision Scope
- Trimos Vectra Touch
- Mitutoyo Tool Maker Microscope
- Mitutoyo Micro Vickers Hardness Tester
- Mitutoyo Surface Roughness Tester
- Optical Sorting Machine



Shock Absorber Damping Values

Plain Disc Valves, Orifi e Valves, Recoil Deection Valves, Leak Valves, Leaf Springs



Product Range

Thickness 0.08 mm to 0.603 mm Diameter: 8 mm to 50 mm

Material: Spring Steel

Hardened & Tempered (Carbon 0.9 - 1.05%) Hardness 450 HV - 610 HV Special Stainless Steel Hardness 510 HV

Additional Processes Stress relieving, Centrifugal De-burring / fnishing



Transmission Components

Shim Packs, Rubber coated exhaust gasket, Copper gaskets, Ferrous and Non Ferrous gaskets, Spacers, Thrust washers, Retainer caps, Lock washer etc.







Thickness: 0.025 mm to 8 mm Diameter: 12 mm to 400 mm

Material : SAE 1010, SAE 1020 SAE, 1050, SAE 1065, SAE 1075, SAE 1080 Shimsteel.

Additional Processes

Heat Treatment: Hardening & Tempering (HRC 48 - 52) Carbonitriding (R15N 9-91) Case Depth (0.15 mm to 0.5 mm) Core Hardness (HRC 40)






ProductRange

Spring Steel Components

E-clips, E-rings, Snap rings, Circlips, Retainers, Retainer rings









Thickness: 0.15 mm to 3.5 mm Diameter: 3 mm to 85 mm

Material : SUS 310, 302, 304, 631 SAE 1075 / 80, EN 42 J

Hardness: 1/2 Herd 3/4 Hard, Additional Processes

Heat Treatment: Hardening & Tempering (HRC 48 - 52) Surface Treatment: Phosphating, Bluing, Blackodising



Gaskets

Non Asbestos gasket (Euro 3 norms compliant), Exhaust Gaskets, Oil Resistant gaskets Packing Gasket, Flange Gasket



Thickness: 0.4 - 4 mm Size: up to 500mm x 500mm

Material:
Non Asbestos Material
Rubber Coated Sheets
Oil Resistant Paper
Nitrile Butadene Rubber (NBR)



Brake System Components

Pad springs, push rods, push road Retainer, Retainer Guard, pad wear indicator, Shims.



Thickness 0.3 mm to 4 mm diameter 6 mm to 200 mm

Material: Low Carbon Steel SAE 1008-1020 High Carbon Steel SAE 1075 Stainless Steel (Harness 3.4 Hard, Full Hard)

Additional processes Surface Coating : ED Coating Stress Reliving / Stabilization



Sheet Metal Components / Assembly & Deep Drawn Components





Mounting Plates / Frames U-bend clip, Tub Liners wire Plate Metal forrum feet Metal Flange Motor Shell

Thickness: 0.3 to 7.5 mm

Material: Low Caron Steel SAE 1008 - 1020 Medium Carbon Steel SAE 1045

High Tensile Steel Additional Processes

Surface Coating : ED Coating, Cu-Ag, Cu-Ni, Zn-Fe Plating MIG Welding, TIG Welding, Pipe bending / flarin, Powder coating

Applications: Drag Racing Car, Electric Relays, Electric Motors, Modular Furniture.





Customers





































IATF 16949 Company

GOLDY PRECISION STAMPINGS PVT. LTD.

Corporate Office & Mfg. Plant -1: F-84/85, MIDC Satpur, Nashik - 422007. Maharashtra, India Mfg. Plant -2: F-85/1, MIDC Satpur, Nashik - 422007. Maharashtra, India Tel.: +91-253 2350885, 6604785 / 885 Fax: +91 - 253 2351412 E-mail: info@goldy.in



Idy.in

