



repairXtreme

The science of car refinishing



CHEMCO

The paint company

ROUGH
TRUCK BED LINER.



Unique textured paint Lizard skin for adventurous and creative people.

Lizard skin paint range is a distinguished paint product that gives a unique look and texture. **RX 5550** and **5555 – LIZARD SKIN** is a 2K polyurethane structured coating with excellent mechanical and chemical resistance.

Created with adventurous and young people in mind Ideal for application to truck bed liners, heavy duty surfaces on commercial vehicles, off-road vehicles and many other industrial structures that require the ultimate protection against adverse weather conditions, petrol, oil, water and salt.





Features

- ✓ Good adhesion to most surfaces
- ✓ High UV and weathering resistance
- ✓ Maintains flexibility
- ✓ Excellent shock and scratch resistance
- ✓ Excellent water resistance
- ✓ Provides sound dampening and noise reduction
- ✓ High resistance to fuels and oils
- ✓ Easy to clean

Substrate preparation

To achieve best results, good preparation is essential.

1. Clean and degrease the surface

2. Before painting remove all loose material and any rust from the surface that will be coated

3. Sand the surface with the P80 - P180 grit sandpaper

4. Re-clean the surface

For hard to reach areas, we recommend that you coat first with a suitable adhesion promoter for optimal adhesion.



repairXtreme
The science of car refinishing

Ultimate black or any other color

Available in black and tintable versions to produce any color by adding 10-15% of an acrylic topcoat or basecoat.



5550 LIZARD SKIN - BLACK	4 (vol.)	0,800 ml
7555 LIZARD SKIN Hardener	1 (vol.)	0.200 ml

Add one Lizard skin 7555 Hardener per bottle Lizard skin - Black.
Shake each bottle individually for two minutes just before applying.
Do not over-catalyze.



5555 LIZARD SKIN - COLOR	4 (vol.)	0,675 ml
7555 LIZARD SKIN Hardener	1 (vol.)	0,200 ml
solvent based toners	10 - 15% (vol)	0,125 ml

Add one Lizard skin 7555 Hardener per bottle of Lizard skin - Color.
Shake each bottle individually for two minutes just before applying.
Do not use waterbased systems to tint. Do not over-catalyze.





Application



UBS spray gun

nozzle: 3,0 - 4,0 mm (corse texture)
presure: 3 - 4 bar (45 - 60 PSI)
distance from object: min 40 cm
coats: 2 coats
1st and 2nd coat in even sweeping motion flash-off
beetween coats: 10 - 15 minutes / 20 C



HVLP gravity feed gun

nozzle: 1,8 - 2,0 mm (fine texture)
2,5 mm (corse texture)
presure: 2 bar (30 PSI)
distance from object: min 20 cm
coats: 2 - 3 coats
1st coat aplied as even wet coat, 2nd reduce presure to achive mist
flash-off beetween coats: 10 - 15 minutes / 20 C

In hot and/or humid conditions, you must apply lighter coats and allow longer flash times between coats. Lizard skin applied too heavily and too quickly may blister or crack after cure. The first coat should not achieve full coverage and subsequent coats should be applied in the same manner



Roll

For uniform appearance, complete all rolling while product is still wet. Texture can be increased with additional rolling after product starts to set up. To avoid trapping solvent do not over apply. Any pooled or over applied areas should be brushed or rolled out. Do not apply more than one coat.

Drying Times

Touch dry:	60 min / 20 C
Through dry:	5-7 days
Baking:	30 min / 60 C
I.R. Cure:	not recommended

About repairXtreme line

AUTOMOTIVE repairXtreme line - Automotive refinishing suited for independent body shops.

We understand car refinishing to be a science, not a simple trade.

repairXtreme is a young and dynamic brand offering a wide range of repair products to support all vehicle body repair and refinishing procedures. We focus on bringing new innovative products at a competitive price and to deliver stable quality and long-lasting durability.

Lizard skin is part of **repairXtreme** product range, which includes more than 500 products including clear coats, primers, bonding and sealing materials, hardeners, thinners.



CHEMCO is a privately owned, technology driven production facility based in Slovenia, which will be able to accompany you on large scale projects as well as with special products on demand.

Certified production

EU based ISO 9001 and ISO 14001 certified production of paint and coatings for surface protection according to ISO 12944. Production facilities of 4000 sq meters are equipped with reliable machines able to produce finished and packed products in packages from 0,2L to 10000 L.

Data-driven quality control with own laboratory

Quality control operation is performed by our laboratory staff for every batch before final packing is done. The data is gathered and stored electronically for any product shipped. Start-to-end production traceability gives our customers transparent and reliable supply.

Recognised internationally and trusted by partners all over the world.



<http://www.repairxtreme.com/>



CHEMCO d.o.o.Tržaška 132,
1000 Ljubljana, Slovenia
Tel.: **+386(0)14232900**
www.chemco.si

