









OAT LONG LIFE GREEN FORMULA

Engine radiator additive ready to use, 5 Years / 150,000 Mile Protection

5 IN 1 PROTECTION: OAT Long Life, Over Heating. Rust. Corrosion. Lubrication.

 Complies with all OEM manufacturers.
 Bio-Degradable. Ethylene Glycol Free. • Protects: Engine, water pump, hoses, radiator, radiator cap, thermostat and all plastic components of the cooling system. · Formulated with MFOAT (Multi-Functional Organic Acid Technology) •Safe to use with: Cast iron, steel, aluminum, copper, brass, magnesium and all late model alloys. • Easy blending with any GREEN colors Antifreeze / Coolant. •Do not add water - Ready to use. Complies with International ASTM D6211, D1384, • Boiling point: 235°F/112.8°C, 15psi radiator cap at sea level.

For more technical information refer to our TDS.



PART#: 901-32N **SIZE:** 32 OZ/946ML UPC#: 0 81905 41508 3

CASE PACK: 12

CASE WEIGHT: 27 LB/ 22.2 KG CASE DIM: 13.75"x 10.75" x 9.75" CASE CUBE: 0.83 FT3 / 0.023 M3

CASE PALLET: 66



900-60N 60 OZ / 1.8 L 0 81905 00601 4

38 LB/ 17.3 KG 14" x 11" x 9.75" 0.89 FT3 / 0.028 M3



900-01N 1 GAL / 3.79 L 0 81905 00001 2 50 LB / 22 KG 21" x 11" x 9" 1.32 FT3 / 0.037 M3



901-25N 2.5 GAL / 9.47 L 0 81905 06259 1 40 LB / 22 KG 13.5" x 9.5" x 13.5"

1.00 ft3 / 0.028 M3



901-05N 5 GAL / 19.95 L 0 81905 06129 7

44 LB / 19.95 KG

2.50 FT3 / 0.07 M3 36



901-55PN 55GAL /208.45 L 0 81905 03120 7 475 LB / 215, 46 KG 23.5" Ø x 35" H

4 Drums

OAT LONG LIFE RED FORMULA

Engine radiator additive ready to use, 5 Years / 150,000 Mile Protection

5 IN 1 PROTECTION: OAT Long Life, Over Heating. Rust. Corrosion. Lubrication.

• Complies with all OEM manufacturers. • Bio-Degradable. • Ethylene Glycol Free. • Protects: Engine, water pump, hoses, radiator, radiator cap, thermostat and all plastic components of the cooling system. • Formulated with POAT (Poly Organic Acid Technology)

• Safe to use with: Cast iron, steel, aluminum, copper, brass, magnesium, and all late model alloys. • Easy blending with any RED Antifreeze/Coolant propylene or ethylene glycol base. • Do not add water - Ready to use. Complies with international ASTM D1384, D3306, D4985. • Boiling point: 235°F/112.8°C, 15psi radiator cap at sea level.

For more technical information refer to our TDS.



PART#: 904-32N SIZE: 32 OZ/946ML

UPC#: 0 81905 05189 2 **CASE PACK**: 12

CASE WEIGHT: 27 LB/ 22.2 KG
CASE DIM: 13.75"x 10.75" x 9.75'
CASE CUBE: 0.83 FT³ / 0.023 M³

CASE PALLET: 66

5 = 1

904-60N 60 OZ / 1.8 L 0 81905 50712 2 8 38 LB/ 17.3 KG

38 LB/ 17.3 KG 14" x 11" x 9.75" 0.89 FT³ / 0.028 M³

66



904-28N 1 GAL / 3.79 L 0 81905 05019 2 6 50 LB / 22 KG 21" x 11" x 9" 1.32 FT³ / 0.037 M³



904-25N 2.5 GAL / 9.47 L 0 81905 09289 5 2 40 LB / 22 KG 13.5" x 9.5" x 13.5' 1.00 ft³ / 0.028 M³



904-05N 5 GAL / 19.95 L 0 81905 50705 4 1 44 LB / 19.95 KG

2.50 FT³ / 0.07 M³



94-55PN 55GAL /208.45 L 0 81905 50703 0 1

475 LB / 215, 46 KG 23.5" Ø x 35" H

4 Drums

MULTI-FUNCTIONAL UNIVERSAL YELLOW FORMULA

Engine radiator additive ready to use, 5 Years / 150,000 Mile Protection

4 IN 1 PROTECTION: Over Heating. Rust. Corrosion. Lubrication.

• Complies with all OEM manufacturers. • Bio-Degradable. • Ethylene Glycol Free. • Protects: Engine, water pump, hoses, radiator, radiator cap, thermostat and all plastic components of the cooling system. • Formulated with MFOAT (Multi-Functional Organic Acid Technology) •Safe to

use with: Cast iron, steel, aluminum, copper, brass, magnesium and all late model alloys. • Easy blending with any GREEN colors Antifreeze / Coolant. •Do not add water - Ready to use. Complies with International ASTM D6211, D1384. • Boiling point: 235°F/112.8°C, 15psi radiator cap at sea level.

For more technical information refer to our TDS.



PART#: 906-32N SIZE: 32 OZ/946ML UPC#: 0 81905 50709 2 CASE PACK: 12

CASE WEIGHT: 27 LB/ 22.2 KG
CASE DIM: 13.75"x 10.75" x 9.75"
CASE CUBE: 0.83 FT³ / 0.023 M³

CASE PALLET: 66



906-60N 60 OZ / 1.8 L 0 81905 50713 9 8 38 LB/ 17.3 KG 14" x 11" x 9.75" 0.89 FT³ / 0.028 M³



906-128N 1 GAL / 3.79 L 0 81905 50710 8 6 50 LB / 22 KG 21" x 11" x 9" 1.32 FT3 / 0.037 M³



906.25N 2.5 GAL / 9.47 L 0 81905 50707 8 2 40 LB / 22 KG 13.5" x 9.5" x 13.5" 1.00 ft³ / 0.028 M³



906-05N 5 GAL / 19.95 L 0 81905 50706 1 1 44 LB / 19.95 KG

2.50 FT³ / 0.07 M³ 36



906-55PN 55GAL /208.45 L 0 81905 50704 7 1 475 LB / 215, 46 KG 23.5" Ø x 35" H

4 Drums















NEW & IMPROVED HIGH PERFORMANCE DIESEL FORMULA

Made with OAT Long Life Technology, Silicate & Phosphate free Ready to use. 5 Years / 150,000 Mile Protection/ up to 15,000 hours. Available in Green, Red, Blue, Marine and Industrial Formulas

PROTECTION: Overheating, against rust, corrosion, oxidation & with electrolysis. Complies all OEM manufacturers. Environmentally Friendly, Bio-Degradable, and Ethylene Glycol Free. NEW FORMULA FOR: HEAVY DUTY DIESEL ENGINES, passengers cars, long haul trucks, buses, 4x4's, SUV, agricultural equipment, marine, construction equipment, stationary motors and industrial power generators. Formulated with HOAT, NOAT and OAT (Hybrid Organic Acid Technology) provides excellent protection to the entire cooling system for both light and heavy duty applications. Designed to provide 3 types of Mono-Molecular corrosion protection. Protects Wet cylinder sleeves from electrolysis. Piston liners, radiator, and water pump from surface



SIZE: 1 GAL / 3.79 L UPC#: 081905 91011 3

CASE PACK: 6 CASE WEIGHT: CASE DIM:

21" x 11" x 9" CASE CUBE:

CASE PALLET:

50 LB / 22 KG 1.32 FT³ / 0.037 M³

902|-128FR 1 GAL / 3.79 L 081905 91012 0 50 LB / 22 KG 21" x 11" x 9" 1.32 FT3 / 0.037 M3 45

scaling and cavitation. Hoses and polymer components from extreme heat conditions. Phosphate free and low TDS formula that prevents surface scaling of cooling components. Also protects high mileage and older engines. Compatible with all types of Antifreeze/Coolants, including Extended Long Life Antifreeze. Complies with International ASTM standards D6210, D2570, D 2809 and DI 384 TMC of ATA RP329/330/338. Boiling point: 235F/112.8C, 15psi radiator cap at sea level.

For more technical information refer to our TDS.

CASE PALLET: 66



PART#: 902-32N SIZE: 32 OZ/946ML UPC#: 0 81905 50708 5

CASE PACK: 12 CASE WEIGHT: 27 LB/ 22.2 KG CASE DIM: 13.75"x 10.75" x 9.75" CASE CUBE: 0.83 FT3 / 0.023 M3



902-60N 60 OZ / 1.8 L 0 81905 06229 4 38 LB/ 17.3 KG 14" x 11" x 9.75"

0.89 FT3 / 0.028 M3



902-128N 1 GAL / 3.79 L 0 81905 90201 9 50 LB / 22 KG 21" x 11" x 9" 1,32 FT3 / 0,037 M3



902-25N 2.5 GAL / 9.47 L 0 81905 06269 0 40 LB / 22 KG 13.5" x 9.5" x 13.5" 1.00 ft3 / 0.028 M3



902-05N 5 GAL / 19.95 L 0 81905 06219 5 44 LB / 19.95 KG

2.50 FT3 / 0.07 M3



902-55PN 55GAL /208.45 L 0 81905 03110 8 475 LB / 215, 46 KG 23.5" Ø x 35" H

4 Drums







HIGH PERFORMANCE FORMULA XXTREME

Engine radiator additive for gas saving ready to use

ALL IN ONE PROTECTION: Complies with European, Japanese, Korean, Asian, Brazilian, and American Industry regulations.

Eco-Protector Formula, Environmentally Friendly, Bio-Degradable, Ethylene Glycol Free,

Formulated with XXTREME Organic Acid Technology developed exclusively by Freezetone Products.

Provide XXTREME corrosion protection for both automotive

and basic heavy-duty diesel applications + XXTREME aluminum protection due to reserved alkalinity levels. Comply with International ASTM standards DI 384, D6210, D3306, D4985 and TMC of ATA RP329/330/338.

Neutral color is compatible with all Antifreeze/Coolant brands and color. Boiling point: 235F/112.8C, 1 5psi radiator cap at sea level.

For more technical information refer to our TDS.



PART#: 909-32N **SIZE:** 32 OZ/946ML UPC#: 0 81905 50928 7

CASE PACK: 12 CASE WEIGHT: 27 LB/ 22.2 KG CASE DIM: 13.75"x 10.75" x 9.75"

CASE CUBE: 0.83 FT3 / 0.023 M3

CASE PALLET: 66

60 OZ / 1.8 L 0 81905 50927 0

38 LB/ 17.3 KG 14" x 11" x 9.75" 0.89 FT3 / 0.028 M3



909-01FXXN 1 GAL / 3.79 L 0 81905 60413 5 50 LB / 22 KG 21" x 11" x 9" 1,32 FT3 / 0,037 M3



909-25N 2.5 GAL / 9.47 L 0 81905 50926 3 40 LB / 22 KG

13.5" x 9.5" x 13.5" 1.00 ft3 / 0.028 M3



909-05N 5 GAL / 19.95 L 0 81905 50925 6 44 LB / 19.95 KG

2.50 FT3 / 0.07 M3



909-55PN 55GAL /208.45 L 0 81905 50924 9

475 LB / 215, 46 KG 23.5" Ø x 35" H

4 Drums

FREEZETONE ORANGE COMPATIBLE WITH DEXCOOL®

- · Premixed- Ready to use-Do not add water.
- · Safe to use with DexCool®
- · Formulated with the newest OAT generation additives and inhibitors to protect rust, corrosion and electrolysis.
- 5 Years / 150,000 Mile Protection
- Meets or exceeds ASTM D3306, ASTM D4985, ASTM D6210, TMC RP 329, VW G11, G12, G12+ and G13.
- Protects freezing up to -34°F(-37°C) and boil-overs to 265F (130°C) *Using a 15 lb pressure cap at sea level.

PART#: 901N-128FR SIZE: 1 GAL / 3.79 L UPC#: 081905 70413 2

CASE PACK: 6

CASE WEIGHT: 50 LB / 22 KG CASE DIM: 21" x 11" x 9" CASE CUBE: 1.32 FT3 / 0.037 M3

CASE PALLET: 45



NEW GENERATION EUROPEAN & ASIAN FORMULAS



PART#: 901B-128FR SIZE: 1 GAL / 3.79 L UPC#: 081905 80201 2

CASE PACK:

CASE WEIGHT: 50 LB / 22 KG
CASE DIM: 21" x 11" x 9"
CASE CUBE: 1.32 FT³ / 0.037 M³

CASE PALLET: 45

901PI-128FR 1 GAL / 3.79 L 081905 91009 0

50.1

50 LB / 22 KG 21" x 11" x 9" 1.32 FT³ / 0.037 M³

45

901P-128FR 1 GAL / 3.79 L 081905 91010 6

50 LB / 22 KG 21" x 11" x 9" 1.32 FT³ / 0.037 M³

45

FREEZETONE BLUE, PINK & PURPLE

New Generation European & Asian Formulas

New European gasoline & light duty diesel powered vehicles requiring a nitrite, amine & phosphate (NAP) free, OAT engine coolant. 150,000 miles or 5 years. Safe to use with Aluminum radiators.

BMW, Jaguar, Mercedes-Benz, Mini, Smart, Volvo, Lexus, Toyota, Scion, Audi, Volkswagen, Porsche.

ASTM D3306, BS6580, VW TL774F, JIS K2234, ASTM D6210-10, ASTM D7583



DON'T USE WATER, USE FREEZETONE



FREEZETONE ANTIFREEZE / COOLANT

Available: 50/50 - 33% - 20% - XXTREME Heavy Duty - WATERLESS

- Five (5) different concentrations: 50/50, 33%, 20%, Waterless and XXtreme
- Meets or exceeds ASTM D3306, ASTM D4985, ASTM D6210, TMC RP 329, VW G11, G12, G12+ and G13.
- Meets or exceeds all of the following manufacturers' specifications: Case, Caterpillar, Cummins, Detroit Diesel / MTU, GM, Freightliner, Hino, International, Isuzu, John

Deere, Mitsubishi, Nissan, Toyota, Volvo and Mack PACCAR, Formulated with ethylene glycol based and the newest OAT generation additives and SCA's to protect rust, corrosion and electrolysis

- · Safe to use with DexCool®
- · Premixed- Ready to use-Do not add water

Ask your Freezetone sales team for more information about Antifreeze products

PART#:

SIZE:

UPC#:

CASE PACK:

CASE CUBE:

CASE PALLET:

CASE DIM:

CASE WEIGHT:



9192-128F 1 Gal/ 3.79 L 0 819056101 0

50 LB / 22 KG 21" x 11" x 9" 1.32 FT3 / 0.037 M3



9150-128N 1GAL / 3.79L 0 81905 61021 1

50/LBS / 22KG 21"x11" x 9" 1.32 FT3 / 0.037 M3



9120R-128 1GAL / 3.79L 0 81905 70221 3

50/LBS / 22KG 21"x11" x 9" 1.32 FT3 / 0.037 M3



9120N-128 1GAL / 3.79L 0 81905 70220 6

50/LBS / 22KG 21"x11" x 9" 1.32 FT3 / 0.037 M3



9120R-128HD 1GAL / 3.79L 0 81905 70224 4 50/LBS / 22KG 21"x11" x 9" 1.32 FT3 / 0.037 M3

ASK YOUR FREEZETONE SALES TEAM FOR MORE INFORMATION ABOUT ANTIFREEZE PRODUCTS

VR-12 THE ULTIMATE COOLING SYSTEM PROTECTION

Is a concentrate of OAT organic chemical components, mixed through a synergetic process, whose cutting edge design and conservationist concept, have created a product that protects your vehicle's cooling system, and saves you money, while you preserve the planet? Available Formulas: Antifreeze 50/50, Radiator Coolant, and Racing Coolant with UV Die.

Ask your Freezetone Sales Team how VR-12 can be part of your product supply.

For more technical information refer to our TDS.



PART#: 9VR-12 SIZE: 16 Oz / 473 ml UPC#: 081905 01153 7 CASE PACK: 12

CASE WEIGHT: 11 LB / 24.7 KG

CASE CUBE:

CASE DIM: CASE PALLET: 150



9120-128VR 1 GAL / 3.79 L 081905 60422 7 50 LB / 22 KG

21" x 11" x 9" 1.32 FT(3) / 0.037 M(3)



901-128VR 1 GAL / 3.79 L 081905 60324 4 50 LB / 22 KG

21" x 11" x 9" 1.32 FT(3) / 0.037 M(3)



904-128VR 1 GAL / 3.79 L 081905 61220 8

50 LB / 22 KG 21" x 11" x 9" 1.32 FT(3) / 0.037 M(3)



901P-128VR 1 GAL / 3.79 L

50 LB / 22 KG 21" x 11" x 9" 1.32 FT(3) / 0.037 M(3)

FREEZETONE AEROSOLS

A complete line of Mechanic "Best Friends" made with the best ingredients to works efficiently, they leave no residue, dry fast, chlorine free, acid free, professional formulations, safe on plastic, rubber, metals, and aluminum. Available in two sizes. Contact your Freezetone sales team for more information of how to order.

SUPER HEAVY DUTY BRAKE CLEANER

PART #: SIZE:

850-BK

BARCODE:

14 OZ / 414 ml 081905609284

BOX:

12 units



- · Cleans fast and dries fast
- · Leaves no residue
- · Removes brake fluid, grease and oil
- · Stops disc brake squeal
- Non-chlorinated

SUPER HEAVY DUTY CARBURATOR CLEANER

PART #:

850-CC

SIZE:

10 OZ / 296 ml 081905609291

BARCODE: BOX:

12 units



- · Removes gum & varnish
- · Smooths rough idling
- · Reduces hesitation by cleaning the vales and cylinders

SUPER HEAVY DUTY ELECTRICAL CONTACT CLEANER

PART #:

#. E.

SIZE:

BARCODE:

BOX:

10 OZ / 296 ml 081905610129

Dissolves dust, dirt,

grease...

850-10EC



- · Fast acting formula
- · Quick drying formula evaporates quickly
- · Cleans and protects sensitive electrical components and contacts
- · Harmless to most plastics
- ·Dissolves dust, dirt, grease, flux and other contaminants

SUPER HEAVY DUTY PENETRATING OIL

PART#:

850-BK

SIZE: BARCODE: 14 OZ / 414 ml

BOX:

081905609284 12 units



- Penetrates into gaps & displaces moisture
- ·Cleans and Lubricates
- ·Stops Squeaks & Eases Sticking

Parts

·Protects Against Rust & Corrosion

SUPER HEAVY DUTY ENGINE CLEANER

PART #:

BOX:

850-BK

SIZE:

14 OZ / 414 ml

BARCODE:

081905609284 12 units



- ·Professional formula cleans dirt, dust and road grime
- ·Can be used with engines with plastic
- ·Clean Engines, run cooler, look better and last longer

FREEZETONE BRAKE FLUID DOT 3 & DOT 4

Engine radiator additive ready to use

Contains corrosion and oxidation inhibitors. Lubricates and protects metal parts.

Freezetone brake fluid DOT-3 exceeds safety standards FMV-SS 116 and meets SAE J1703 and ISO-4925 standards. Minimum WET Boling Point 284 °F (140 °C). Minimum DRY Boling Point 450 °F (232 °C). Full synthetic, super heavy duty.

Sizes Available: 8oz (250ml), 10oz (300ml), 32oz (1lts) Industry colors available. Contact your Freezetone sales team for more information.

For more technical information refer to our TDS.

PART#: 8

UPC#:

CASE PACK:

800-12-3UK 12 OZ / 354 ml 0 81905 90408 2

DOT

CASE WEIGHT: 21 LB / 9.52 KG
CASE DIM: 17 x 11 x 6
CASE CUBE: 0.65 FT3 / 0.018 M3
CASE PALLET: 110

DOT³.

800-32-3UK 1 GAL / 3.79 L 0 81905 90409 9 6 50 LB / 22 KG 21" x 11" x 9" 1.32 FT³ / 0.037 M³

45



800-10-4 10 OZ / 300 ml 0 81905 605248 24 18 LB / 8.40KG 17 x 11 x 6 0.65 FT3 / 0.018 M3



800-8-3R 1 GAL / 3.79 L 0 81905 81018 5 6 50 LB / 22 KG 21" x 11" x 9" 1.32 FT³ / 0.037 M³ 45

FREEZETONE MULTI PURPOSE HEAVY DUTY GREASES

Freezetone Multi-Purpose Heavy Duty NLGI 2 Calcium Grease is an excellent quality Calcium based grease prepared from virgin refined base stocks which ensures smooth performance wherever grease is required. This grease has excellent mechanical stability, maintaining consistency even after severe working temperatures. The grease is resistant to water washing, protects against rust and is non-corrosive. Reduces operating temperatures in load zone of bearings. Resistance to water as shown in the Salt Water Spray test. Outstanding resistance to oxidation. High level of chemical stability

and are formulated with special additive combinations to provide excellent protection against wear, rust and corrosion, and providing operating viscosity at high and low temperatures. Formulated to withstand shock loads for use in bearing applications (NLGI GC-LB rated). Meets requirements of NLGI GC-LB. Recommended for mining and heavy manufacturing. Heavy duty chassis lubrication, ball joints, and universal joints. Ball and roller bearings. Heavy service industrial lubrication. Fifth wheel applications. Motorcycle Chains. Grass and Lawn equipment,

PART#:
SIZE:
UPC#:
CASE PACK:
CASE WEIGHT:
CASE DIM:
CASE CUBE:
CASE PALLET:



FR802-05A 5 GAL / 19.95 L 081905 90720 5 1 44 LB / 19.95 KG

2.50 FT³ / 0.07 M³ 36



FR802-05R 5 GAL / 19.95 L 081905 90722 9 1 44 LB / 19.95 KG

2.50 FT³ / 0.07 M³ 36



FR802-05B 5 GAL / 19.95 L 081905 90721 2 1 44 LB / 19.95 KG

2.50 FT³ / 0.07 M³ 36

FREEZETONE TRANSMISION FLUIDS

DEXRON 3 TYPE (H)

- · Freezetone Dexron III (H) Automatic Transmission Fluid is recommended as a replacement fluid for automatic transmissions meeting or exceeding original equipment manufacturers (OEM) DEXRON II, DEXRON II - E, DEXRON III - G, DEXRON III, H Revision, Automatic Transmission Fluid, or Ford MERCON fluids are specified.
- It is also recommended for Allison res 389, C-3, C-4 applications, and Caterpillar TO-2
- Excellent low temperature fluidity for good cold-start shifting
- · Suitable for most power steering units
- Resistance to foaming
- · Oxidation and thermal stability for long life

ATF TYPE (A)

- · FREEZETONE Automatic Transmission Fluid Type A is formulated primarily for add-on purposes. It blends smoothly with all original transmission fluids. This product may be used in automatic transmissions and power steering units of automobiles and light trucks manufactured by American European, Japanese and Korean manufacturers. Also Available MERCON LV, MERCON V, DEXRON VI
- For information of how to order please contact Freezetone Sales Team



PART#:

SIZE: UPC#:

CASE PACK: **CASE WEIGHT:**

801-32DX3H 1000 ML (1L) 0 81905 60726 6

33.5 LB / 14.9 KG



PART#: SIZE: UPC#: **CASE PACK:** CASE WEIGHT:

1000 ML (1L) 0 81905 60725 9

33.5 LB / 14.9 KG

FREEZETONE ENGINES OILS

Freezetone Heavy Duty 15W40 Cl4 Plus Synthetic Blend Diesel Engine Oil meet and exceed 2017 and prior model year on-highway and Tier 4 exhaust emission standards. It provides enhanced protection against war, oxidation, shear viscosity loss, low and high temperature degradation, soot related thickening as well as protection against particulate filter blocking and catalyst poisoning. Freezetone Heavy Duty 15W40 CI4 Plus Synthetic Blend Diesel Engine Oil meets or exceeds the (API) CI-4 and is compatible with all prior API classifications including CI-4 Plus, CI4 and CH4. Freezetone Heavy Duty 15W40 Cl4 Plus Synthetic Blend Diesel Engine Oil has been field tested and is recommended for American, Asian and European standards including ACEA E7, Caterpillar ECF-3, ECF-2, Cummins CES 20086, 81, Detroit Diesel 93K222, 93K218, Mack EOS-4.5, EO-O , MAN 3275, MB 228.3, Volvo VDS-3 and many other light and heavy duty engines.

Freezetone Heavy Duty 20W50 Cl4 Plus Synthetic Blend Diesel Engine Oil meet and exceed 2017 and prior model year on-highway and Tier 4 exhaust emission standards. It provides enhanced protection against war, oxidation, shear viscosity loss, low and high temperature degradation, soot related thickening as well as protection



PART#: SIZE: UPC#:

CASE PACK: CASE WEIGHT: CASE DIM:

CASE CUBE: CASE PALLET:

FR801SS-05-15W40PL 5 GAL / 19.95 L 0 81905 90405 1

44 LB / 19.95 KG

2.50 FT3 / 0.07 M3



FR801SS-05-20W50PL 5 GAL / 19,95 L 0 81905 90406 8

44 LB / 19.95 KG

2.50 FT3 / 0.07 M3

against particulate filter blocking and catalyst poisoning. Freezetone Heavy Duty 20W50 CI4 Plus Synthetic Blend Diesel Engine Oil meets or exceeds the (API) CI-4 and is compatible with all prior API classifications including CI-4 Plus, CI4 and CH4. Freezetone Heavy Duty 20W50 CI4 Plus Synthetic Blend Diesel Engine Oil has been field tested and is recommended for American, Asian and European standards including ACEA E7, Caterpillar ECF-3, ECF-2, Cummins CES 20086, 81, Detroit Diesel 93K222, 93K218, Mack EOS-4.5, EO-O , MAN 3275, MB 228.3, Volvo VDS-3 and many other light and heavy duty engines.

DEGREASERS & CLEANERS

Available in two formulas, Purple Thunder and Bio Degradable

- New concentrated formula, heavy duty, emulsifying, cleaner and degreaser.
- Caustic Soda FREE
- Can be used for heavy duty cleaning as well household purposes.
- Nonabrasive, corrosive or toxic.
- · Protects metal and metal finishes.
- Environmentally friendly and bio-degradable.
- · Can be use on marine and motor cycle
- · Trigger spay available in 1 liter bottles
- Aerosol available



Acrylionic technology, clear coat repair, cleans & repels dirt, guaranteed results, easy to use, environmentally friendly

WINDSHIELD WASHER

- METANOL FREE
- Cuts dirt, grime and bugs.
- · Eliminate smearing and line clock age.
- · With corrosion inhibitors to protect metals.



PART#: SIZE: UPC#: CASE PACK:

CASE WEIGHT: CASE DIM:

CASE CUBE: CASE PALLET:



950-32 32 OZ/ 946 ML 0 81905 30917 7

13.75" x 10.75" x 9.75" 0.83 FT3 / 0.023 M3



950-128 1 GAL / 3.79 L 0 81905 07128 9

50 LB / 22 KG 21" x 11" x 9" 1.32 FT3 / 0.037 M3



PART#: SIZE: UPC#: CASE PACK:





PART#: SIZE: UPC#: CASE PACK: CASE WEIGHT: CASE DIM: CASE CUBE:

CASE PALLET:

903-128 1 GAL / 3.79 L 0 81905 00002 9

50 LB / 22 KG 21" x 11" x 9" 1.32 FT3 / 0.037 M3



32 OZ/ 946 ML 0 81905 01269 5 27 LB / 22.2 KG 13.75" x 10.75" x 9.75" 0.83 FT3 / 0.023 M3

PURPLE LIGHTINIG DEAGREASER

Acrylionic technology, clear coat repair, cleans & repels dirt, guaranteed results, easy to use, environmentally friendly.



PART#: SIZE: UPC#: CASE PACK: CASE WEIGHT: CASE DIM:

CASE CUBE:

CASE PALLET:

950-14EZ-C 14 OZ/414ML 0 81905 61016 7 27 LB/ 22.2 KG

13.75"x 10.75" x 9.75" 0.83 FT³ / 0.023 M³



32 OZ/946ML 0 81905 61017 4 27 LB/ 22.2 KG 13.75"x 10.75" x 9.75" 0.83 FT3 / 0.023 M3



950-128EZ/D 1 GAL / 3.79 L 0 81905 61018 1 50 LB / 22 KG 21" x 11" x 9" 1.32 FT3 / 0.037 M3



THE FUTURE OF COOLANT IS HERE





PRIVATE LABELING AVAILABLE ON ALL PRODUCTS

CERTIFICATIONS AND MEMBERSHIPS





















automechanika

ENGLISH E-CATALOG



FREEZETONE PRODUCTS USA

7986 NW 14 ST. DORAL, FL 33126

PHONE +1 (305) 640-0414 FAX +1 (305) 640-0454



ESPAÑOL E-CATALOG

INFO@FREEZETONE-USA.COM

WWW.FACEBOOK.COM/FREEZETONEUSA

WEB SITE: WWW.FREEZETONE-USA.COM

All and TM marks are registered marks and trademarks of FREEZETONE PRODUCTS USA, all rights reserved. © 2020