

LOXY[®]



Decorative
overlay
film

DECORATIVE OVERLAY FILM – LD38 SERIES

RECOMMENDED WASHING TREATMENT

All products are tested according to parameters stated in the ISO 6330.

Below is additional guidelines.

- » Use of colored washing program, and detergent for delicate or colored garments are recommended.
- » No pre-soaking or pre-wash program.
- » Avoid use of high alkaline chemicals, like stain removal etc.
- » Do not over dry, temperature of garment should not exceed 70° C.

HANDLING AND STORAGE

Proper inventory control will ensure that your tape maintains optimal shelf life (up to 2 years).

- » Store in cool, dry area in original package
- » Avoid high temperatures
- » Avoid high humidity conditions (<75 %)
- » Use FIFO (first in first out) stock methods

RECOMMENDED APPLICATION CONDITIONS

Loxy decoration films can be applied using heat transfer press or seam sealing machine.

Application temperature: 150–180 °C

Pressure: 2,55 kg/cm² / 2,5 lb/cm²

Application time: 9 seconds

PROPERTIES

Elastic – ideal for strechable fabrics such as lycra or similar.

Non-elastic – use this quality for fabrics that do not require stretch.

Flame Retardent – ideal for the oil & gas industry.

Easily appliable – A film that will stick to the fabric before heating.

ARTICLE	LD38.CT	LD38	LD38.CAD	LD38.FR.CT	LD38.FR	LD38FR.CAD
Flame Retardent				✓	✓	✓
Non-elastic	✓			✓		
Elastic		✓	✓		✓	✓
Easy Appliable			✓			✓
Application temperature	150–180 °C	150–180 °C	150–180 °C	150–180 °C	150–180 °C	150–180 °C
Pressure	2,55 kg/cm ² 2,5 lb/cm ²	2,55 kg/cm ² 2,5 lb/cm ²	2,55 kg/cm ² 2,5 lb/cm ²	2,55 kg/cm ² 2,5 lb/cm ²	2,55 kg/cm ² 2,5 lb/cm ²	2,55 kg/cm ² 2,5 lb/cm ²
Application time	9 seconds	9 seconds	9 seconds	9 seconds	9 seconds	9 seconds
Standard width	51 cm	51 cm	51 cm	51 cm	51 cm	51 cm
Service temperature	-40 – 70 °C	-40 – 70 °C	-40 – 70 °C	-40 – 70 °C	-40 – 70 °C	-40 – 70 °C
Recommended washing	60 °C	60 °C	60 °C	60 °C	60 °C	60 °C
Tumble dry	✓	✓	✓	✓	✓	✓
Standard color	03-06-16-18	03-06-16-18	03-06-16-18	03-06-16-18	03-06-16-18	03-06-16-18
Optional colors	✓	✓	✓	✓	✓	✓

LOXY

Where ele

LOXY



LOXY adds value in textile products. Through flexibility and innovation, honed by generations in the extreme Norwegian nature, we develop world leading products in close cooperation with our clients.



LOXY AS
Sørliveien 72
N-1788 Halden,
Norway

E-mail: post@loxy.no
Phone: +47 69 19 53 90
Fax: +47 69 19 57 68
www.loxy.com