

Pmflex™



ANTI-UV Range

Thanks to the use of technologically advanced solutions, we present the range Pmflex Anti-UV, resistant to UV rays and atmospheric agents, suitable for outdoor installations and photovoltaic systems directly exposed to sunlight.

Anti-UV products are made with specific materials and additives, tested in climate chamber with UV lamp, as specified by the norms CEI EN 50289 and CEI EN 50618 (former CEI 20-91). The chamber reproduces with intense UV light and with repeated rain and drying cycles the climatic conditions that the product will encounter outside. Pmflex Anti-UV products are also Halogen Free, in accordance with the European standard EN 50642.



xRigid PP HF UV 750N

CODE		PACK
IRLHFUV16	16 mm, Black, Anti-UV, 750 N, 3 m bar	102 m
IRLHFUV20	20 mm, Black, Anti-UV, 750 N, 3 m bar	102 m
IRLHFUV25	25 mm, Black, Anti-UV, 750 N, 3 m bar	60 m
IRLHFUV32	32 mm, Black, Anti-UV, 750 N, 3 m bar	30 m
IRLHFUV40	40 mm, Black, Anti-UV, 750 N, 3 m bar	30 m
IRLHFUV50	50 mm, Black, Anti-UV, 750 N, 3 m bar	15 m



xFlex Speed HF UV

CODE		COIL
ICTANUV16RT24	16 mm, Black, Anti-UV, 750 N	100 m
ICTANUV20RT20	20 mm, Black, Anti-UV, 750 N	100 m
ICTANUV25RT12	25 mm, Black, Anti-UV, 750 N	100 m
ICTANUV3225RT24	32 mm, Black, Anti-UV, 750 N	25 m
ICTANUV4025RT20	40 mm, Black, Anti-UV, 750 N	25 m
ICTANUV5025RT8	50 mm, Black, Anti-UV, 750 N	25 m



xInstall UV coupling for pliable and rigid pipes

CODE		PACK
SML16N	16 mm, Black, Anti-UV	50 pcs
SML20N	20 mm, Black, Anti-UV	50 pcs
SML25N	25 mm, Black, Anti-UV	25 pcs
SML32N	32 mm, Black, Anti-UV	25 pcs
SML40N	40 mm, Black, Anti-UV	10 pcs
SML50N	50 mm, Black, Anti-UV	10 pcs



xFlexWire Pre-wired conduit with cable H1Z2Z2-K Anti-UV

CODE		COIL
U2Z2Z2K40NN	20 mm, Black, H1Z2Z2-K 2x4 Bk Bk, Anti-UV, Cca-s1b,d2,a1	100 m
U2Z2Z2K40NR	20 mm, Black, H1Z2Z2-K 2x4 Bk Rd, Anti-UV, Cca-s1b,d2,a1	100 m
U2Z2Z2K40NRT	20 mm, Black, H1Z2Z2-K 2x4 Bk Rd, Anti-UV, Cca-s1b,d2,a1 + H07Z1-K 1x4 Y/G, Cca s1b,d1,a1	100 m
U2Z2Z2K60NN	20 mm, Black, H1Z2Z2-K 2x6 Bk Bk, Anti-UV, Cca-s1b,d2,a1	100 m
U2Z2Z2K60NR	20 mm, Black, H1Z2Z2-K 2x6 Bk Rd, Anti-UV, Cca-s1b,d2,a1	100 m
U2Z2Z2K60NRT	20 mm, Black, H1Z2Z2-K 2x6 Bk Rd, Anti-UV, Cca-s1b,d2,a1 + H07Z1-K 1x6 Y/G, Cca s1b,d1,a1	100 m