

Leidy Series - Track Light



MHT8986

Light distribution
3000K CRI 90

MHT8986				17°
h (m)	E0°	(lx)	Φ (m)	
1		4994	0.30	
2		1248	0.60	
3		554.9	0.91	
4		312.1	1.21	
5		199.8	1.51	



MHT8966-20W

Light distribution
3000K CRI 90

MHT8966-20W				41°
h (m)	E0°	(lx)	Φ (m)	
1		5438	0.75	
2		1360	1.51	
3		604.3	2.26	
4		339.9	3.01	
5		217.5	3.76	



MHT8966-30W

Light distribution
3000K CRI 90

MHT8966-30W				41°
h (m)	E0°	(lx)	Φ (m)	
1		7867	0.74	
2		1967	1.48	
3		874.1	2.23	
4		491.7	2.97	
5		314.7	3.71	

Control Type



Luminaire specifications

Mode	Power	Lumen	CCT	BA.	Light Source	Driver	IP	CRI
MHT8986	12W	1397	3000K	17 °	Bridgelux	KEGU	20	90
MHT8966-20W	20W	2680	3000K	41°	Bridgelux	VLINCA	20	90
MHT8966-30W	30W	3900	3000K	41°	Bridgelux	VLINCA	20	90


Frame finishing colour



Colour temperature range



Colour Rendering Index



Beam angle

