


## TEHNICAL SPECIFICATIONS SEAL













nergency light model	•Emergency and
model with an emergency mode	Standard model
	Stanuaru mouet


- Emergency model with 1.5h autonomy
- Mechanical protection grade IP67, IK10
- Excellent thermal management
- Different mounting options
- Water resistant
- No glare effect
- High lumen output 3 000 lm to 6 500 lm
- Maintenance free

Standard model High quality non corosive linear LED lamp		Emergency light model Standard model with an emergency mode		
SEAL	650-230-25		1250-230-25	
Order No.	standard model - 1001831 emergency model - 1001833		standard model - 1002201 emergency model - 1002204	
<b>Electrical Characteristics</b>				
Nominal Voltage	230VAC		230VAC	
Operating Voltage	100 - 230VAC		100 - 230VAC	
Total Power	~25W		~55W	
Power Factor	>0.97 at 230VAC		>0.97 at 230VAC	
Operating Temperature	-20°C to +50°C		-20°C to +50°C	
Light Technology Character	istics			
Initial Total Lumens	3000lm; minimum 450lm in emergency mode		6500lm; minimum 450lm in emergency mode	
Emergency Light	1.5h autonomy, 8h charging time, NiCad Battery			
Luminary Efficacy	~120lm/W			
ССТ	~5000K			
CRI	80 - 85			
Illumination Angle	120°			
Protection & Construction				
IP and IK Protection	IP67, IK10			
Protections	OVP, OTP			
Luminary Inner Protective Cover	PMMA 2.5mm			
Removable Protective Cover	Polycarbonate 2.5 – 3mm			
Housing	PMMA, PA6, PC, ABS			
Gasket	Silicone gasket			
Cable entry	6 - 13mm			
Fixture Weight		kg as emergency 3.5kg, 3.9kg as emergency ght option		
Lifespan(on 25°C)	50 000 hours			

#### datal.com

## POLAR CURVE

### SEAL models



SEAL models	Beam Angle
650	120°
1250	120°
650 EM	120°
1250 EM	120°

### DIMENSIONS, CONNECTION



Seal	650/650 EM	1250/1250 EM
Α	650mm	1250mm
В	ø90mm	ø90mm
С	105mm	105mm
D	400-550mm	1000-1150mm
Е	2 x ø6mm	2 x ø6mm









\*available mounting types in table below

# **ACCESSORIES**

Protective Transparent Cover for Seal 650mm 1001962		Mounting Bracket with nut and screw 1002032	4	Mounting Bracket with Cable Suspension 1002306
Protective Transparent Cover for Seal 1250mm 1002305	2	Magnetic Mounting Bracket 1002033		Hook Eye Set 1001856
Bottom Cap 1001450	3	Mounting Bracket with Chain Suspension 1002037		Custom-made Bracket on Request

