

UL 758 Style Certification List							
Style No	Conductor	Operating Voltage	Operating Temperature	Insulation	Covering	Shield	Use
1007	32 AWG - 16 AWG (Solid or Stranded)	300 V	80°C	Extruded PVC	N/A	N/A	Internal wiring of appliances or where exposed to oil at a temperature not exceeding 60 deg C or 80 deg C, whichever is applicable. Tags may indicate the following: 600 V Peak - For Electronic Use Only.
1015	30 AWG - 2000 kcmil (Solid or Stranded)	600 / 750 V	80, 90 or 105°C	Extruded PVC	N/A	N/A	Internal Wiring of Appliances Tags may also indicate the following: 2,500 V peak - for electronic use only.
1061	30 AWG - 14 AWG (Solid or Stranded)	300 V	80 °C	Extruded SRPVC	N/A	N/A	Internal Wiring in Electric Bookkeeping, Accounting, Time-Recording Machines, or Electronic Equipment if within a chassis or protected from mechanical injury.
1569	30 AWG - 2 AWG (Solid or Stranded)	300 V	80, 90 or 105°C	Extruded PVC	Optional Extruded PVC	N/A	Internal wiring of appliances or electronic equipment where not subjected to movement or mechanical damage. Tag may also indicate the following, "600 Volts Peak for Electronic Use Only."
2464	Related to core style specification	300 V	80 °C	Extruded PVC (JACKET)	Optional	Optional	Internal wiring or external interconnection of electronic equipment.
3071	18 AWG - 13 AWG (Solid or Stranded)	600 V	200 °C	Extruded SR	FiberGlass Braid	N/A	Internal wiring of appliance
3135	26 AWG - 12 AWG (Solid or Stranded)	600 V	200 °C	Extruded SR	N/A	N/A	Internal wiring of appliances where totally enclosed.
3266	32 AWG - 10 AWG (Solid or Stranded)	300 V	125°C	Extruded XLPE	N/A	N/A	Internal Wiring. Tags may indicate the following: 600 Volts Peak - For Electronic Use Only.
3271	30 AWG - 2000 kcmil (Solid or Stranded)	600 / 750 V	125°C	Extruded XLPE	N/A	N/A	For use as Motor Leads or Internal Wiring of appliances. Tags may indicate the following: 2500 volt peak - For Electronic Use Only.
3512	0.3 - 250 sq mm (Solid or Stranded)	600 V	200°C	Extruded SR	N/A	N/A	Internal wiring of appliances where totally enclosed.
3513	0.5 - 250 sq mm (Solid or Stranded)	600 V	200°C	Extruded SR	FiberGlass Braid	N/A	Internal wiring
3529	26 AWG - 750 kcmil (Solid or Stranded)	600 V	150°C	SR	N/A	N/A	Internal wiring of appliances where totally enclosed
3530	26 AWG - 750 kcmil (Solid or Stranded)	600 V	150 or 200 °C	Extruded SR	N/A	N/A	Internal wiring of appliances where totally enclosed
3535	20 AWG - 500 kcmil (Solid or Stranded)	600 V	150°C	Extruded SR	Same as for type SFF Fixture wire	N/A	Internal wiring of appliances
3644	30 AWG - 1000 kcmil (Solid or Stranded)	1000 V	150 or 200 °C	Extruded SR	N/A	N/A	Internal wiring of appliances where totally enclosed
3645	30 AWG - 750 kcmil (Solid or Stranded)	1000 V	150 or 200 °C	Extruded SR	Extruded SR, or acrylic based emulsion finished polyaramid or glass braid.	N/A	Internal Wiring of Appliances or Electronic Equipment.
3398	32 AWG - 10 AWG (Solid or Stranded)	300 V	150°C	Extruded XLPE	Optional - Extruded XLFRPE, 10 mils minimum average, 8 mils minimum at any point.	N/A	Internal wiring where not subjected to movement or mechanical damage. Tags may indicate the following: 600 V peak - for electronic use only.
4389	Related to core style specification	600 V	150 or 200 °C	Extruded SR (Jacket)	Optional	Optional	External interconnection of high temperature cooking appliances. Where not subject to mechanical abuse and where the acceptability of the combination is to be determined by UL.
3661	16 AWG - 750 kcmil (Solid or Stranded)	1100 V	180°C	Extruded SR	Optional	N/A	Internal wiring
3662	1.5 to 400 sq. Mm (Solid or Stranded)	4200 V	180°C	Extruded SR.	Optional, non-metallic.	N/A	Internal wiring
3663	16 AWG - 800 kcmil (Solid or Stranded)	7200 V	180°C	Extruded SR.	Optional, non-metallic.	N/A	Internal wiring
3664	1.5 to 400 sq mm (Solid or Stranded)	15000 V	180°C	Extruded SR.	Optional. Non-extruded, non-metallic.	N/A	Internal wiring

*** Liste 03.11.2017 tarihinde hazırlanmıştır. Bilgi amaçlıdır. Bilgilerin girdi olarak kullanılmak istenmesi durumunda Style Page'den güncelliğinin kontrol edilmesi gerekmektedir.

"1569" için Style Page: <http://iq.ul.com/awm/stylepage.aspx?Style=1569>

Diğer style sayfalarına ulaşmak için son 4 haneye incelemek istediğiniz style numarasını yazınız.