



2021

Product Catalogue



Contents

03 Ledlink Profile

05 Landscape Lighting

- 07 Under Ø20 mm
- 09 Ø20~30 mm
- 11 Ø30~60 mm
- 13 Waterproof Lens
- 15 Color Mixing Lens
- 16 Windowsill Lens

17 Commercial Lighting

- 19 V-CUT Series
- 21 Ultra-Thin Hybrid Lens
- 24 Zoom Lens
- 25 Ø20~50 mm
- 27 Ø50~80 mm
- 29 Ø80~100 mm

31 Street Lighting

- 33 2 in 1 / 4 in 1 / 6 in 1 / 8 in 1
- 35 12 in 1
- 37 16 in 1 / 20 in 1
- 39 Others

41 Area Lighting

- 43 4in1 / 6 in 1 / 8in1
- 43 12in1 / 16in1 / 18in1
- 45 Linear Lens

49 Automotive Lighting

- 51 Head Lamp / Tail Lamp
 - Lateral Linear Lens
 - Daytime Running Light
 - Reading Lamp
 - Motorcycle Head Lamp
- 53 Automotive Lighting Equipment

Ledlink Optics Inc., established in March 2008, is a professional company in designing and manufacturing optics for the LED lighting companies. We cooperate with our strategic partners of LED manufactures including Cree, Edison, Lumileds, Nichia, Osram, Samsung, Seoul...etc.

Our company mission is to help our customers to optimise optics performance for excellent LED lighting products. Lenses are available in a wide variety of package with numerous beam pattern options and dimension, such as residential lighting, commercial lighting, street lighting, architectural lighting and automotive lighting. You will find a most suitable solution at Ledlink.

- **2008**
 - Ledlink Established in Taipei
 - Dongguan Factory Established
- **2009**
 - ISO 9001/14001 Certification
 - Dongguan Second Factory
- **2010**
 - UL Certification
- **2011**
 - Third Factory Expansion in Dongguan
 - Yangzhou Ledlink Expansion
 - Listed in Emerging Market
 - Awarded the 16th Place of Deloitte
 - IATF16949 Certification
 - Technology Fast 500 Asia Pacific 2011
- **2012**
 - IPO in OTC Taiwan
- **2013**
 - Yangzhou Factory Mass Production
- **2015**
 - Supplying to Automotive Lighting Manufacturers



Headquarter
TAIPEI, TAIWAN

CEO
Telung Tang

Employees
90

Capital
USD 17 Million

Main Function
Administration
Financial
Oversea Sales
Marketing
RD



Factory
DONGGUAN

Employees
450

Capital
USD 28 Million

Area
33000 m²

Injection Machines
200 Sets



Factory
YANGZHOU

Employees
210

Capital
USD 20 Million

Area
30000 m²

Injection Machines
100 Sets

Landscape Lighting

- 07 Under Ø20 mm
- 09 Ø20~30 mm
- 11 Ø30~60 mm
- 13 Waterproof Lens
- 15 Color Mixing Lens
- 16 Windowsill Lens



Landscape Lighting

Under Ø20 mm

*All dimensions are in millimeters.



Part No	Dimensions	Angle	LED Size	Tape
 LL01ZZ-DRTxL06-M1	Ø10.24×7	15°/20°/25°/38° 60°/20°×40°	3535	-
 LL01CR-DFxL06-M2-T	Ø13.5×7.35	25°/40°/60°/80° 100°/30°×65°	3535	●
LL01LU-DFxL06-M2-T			3045	
 LL01CR-BDFxL06-M2-T	Ø13.5×7.35	25°/40°/60°/80° 100°/30°×65° 30°×70°	2525	●
LL01LU-BDFxL06-M2-T			3045	
LL01OS-BDFxL06-M2-T			3030	
LL01CR-AAFxxL02-M2-T	Ø13.5×7.35	25°/45°/60°	3535	●
LL01HS-AAFxxL02-M2-T	Ø13.5×7.35			
LL01OS-AAFxxL02-M2-T	Ø13.5×7.35		3030	
LL01NI-AAFxxL02-M2-T	Ø13.5×8.05		5050	
 LL01ZZ-DBIxxL06-M2	Ø15.3×9.1	30°/45°/60° 30°×60°	5050	-
 LL01NI-BYKxxL19-T	16×16×8	20°/30°/40°/60° 25°×45°	2525 3030 3535	●
 LL01CR-HQxxL06-M2	Ø16×10.3	15°/25°/30°/40° 60°/80°/25°×45°	3535	-
LL01CR-SNxxL06-M2-T	Ø16.3×10.3		3535	●
LL01ZZ-HQxxL06-M2-T	Ø16.1×9.9		3030/3535	
 LL01CR-OTxxL06-M2	Ø16.6×10.4	32°/40°/60°/80°	3535	-





Landscape Lighting

Ø20~30 mm

* All dimensions are in millimeters.



	Part No	Dimensions	Angle	LED Size	Tape
	LL01LU-AA2065L06-M2	Ø21×12.6	20°×65°	1LA5	-
	LL01CR-AA2065L06-M2-T	Ø21×11.4		3535	●
	LL01CR-SQ××L06-M2-T	Ø21×13.9	40°/60°/80°	5050	●
	LL01OS-MQ××L06-M2	Ø21.05×14.75	15°/25°/40°/60°	3030	-
	LL01CR-AFC××L06-M2-T	Ø21.3×12.45	10°/15°/25°/30°/40° 50°/60°/80°/10°×35° 10°×45°/10°×60° 15°×30°/20°×45° 15°×60°/30°×60°	3535	●
	LL01OS-AFC××L06-M2-T	Ø21.3×12.35		3030	●
	LL01CR-WX××L06-M2	Ø21.3×12.35		3535	-
	LL01OS-VS××L06-M2	Ø21.3×12.35		3030	-
	LL01ZZ-YR××L06-M2	Ø21.3×12.35		3045	-
	LL01JR-AFC××L06-U2	Ø21.9×12.35		3535	-
	LL01CR-CRI1055L02-M2	22×22×9.8	10°×55°	3030 3535	-
	LL01ZZ-DTL×××L06-M2	Ø22.1×14.76	Wall Washing Height 1M/2M/3M	3030 3535	-
	LL01CR-DQD06L06	Ø22.5×17.7	6°	3535	-

	Part No	Dimensions	Angle	LED Size	Tape
	LL01ZZ-EX××L06-U2	Ø22.4×9.63	10°/15°/25° 40°/60°/110° 30°×65°/30°×85°	3535	-
	LL01ZZ-EX××L06-M2-T	Ø22.4×9.63			●
	LL01CR-EX××L06-M2-T	Ø23×10.63		3030	●
	LL01OS-EX××L06-M2-T	Ø22.4×9.63			●
	LL01LU-EX××L06-M2-T	Ø22.4×9.63		3045	●
	LL01CR-OS××L06-M2-T	Ø22.4×9.13		2525	●
	LL01CR-BEX××L06-M2-T	Ø 22.4×9.13	25°/40°/60°	2525	●
	LL01CR-NE××L06-M2	Ø23.5×15.8	15°/17°/25°/40°/60° 80°/10°×45°/25°×45°	3535	-
	LL01CR-CNE××L06-M2-T	Ø23.5×15.8			●
	LL01NI-NE××L06-M2-T	Ø21.4×15.8			●
	LL01NI-ANE××L02-M2-T	Ø23.5×15.8	10°/20°/30°/55°	3535	●
	LL01CR-BNE××L06-M2	Ø23.5×15.8	25°/40°/60°/35°×70°	2525	-
	LL01NI-BNE××L06-M2-T	Ø21.4×15.8		3535	●
	LL01XP-FL××L06-M2-T	Ø24.3×11.6	10°/25°/40°/60° 30°×65°	3535	●
	LL01LU-FL××L06-M2-T	Ø24.3×11.6		3045	●
	LL01CR-FL××L06-M2	Ø24.3×12.15		7090	-
	LL01ZZ-FL××L06-M2	Ø24.3×11.5		5050	-
	LL01ZZ-AFL××L02-M2	Ø24.3×12.3	35°/50°/70°	7090	-
	LL01CR-AFL××L02-M2-T	Ø24.3×11.8		9090	●
	LL01LU-AFL××L02-M2-T	Ø23.6×12.5		7070	●
	LL01CR-CSS1226L06	24×24×13.6	12°×26°	3030 3535 3737	-



Landscape Lighting

Ø30~60 mm


*All dimensions are in millimeters.



	Part No	Dimensions	Angle	LED Size	Tape
	LL01CR-WIxxL02-M2-T	Ø32.8×18	15°/25°/40°	5050	●
	LL01CR-DGxxL06-M2	Ø32.8×18	20°/30°/40°/50° 60°/100°/30°×85°	5050/7090	-
	LL01CR-ADGxxL06-M2-T	Ø32.8×18		5050	●
	LL01XP-DGxxL06-M2	Ø32.8×18		3535	-
	LL01LU-DGxxL06-M2	Ø32.8×17.3		7070	-
	LL01MH-DGxxL06-M2-T	Ø32.8×18		5050	●
	LL01CR-BLUxxL06-T	Ø35×20.1	3°/5°/5°×20°	3535/5050	●
	LL01CR-BLUxxL06-M2-T	Ø38.2×22.2	3°/5°/5°×20°	3535	●
	LL01CR-BLUxxL06-M2-T + LL01CR-DLXxxL02	Ø38.2×22.2	15°/25°/38°/10°×35°	3535	●
	LL01LU-DQP02L06	Ø35×20.1	2°	2020	-
	LL01LU-DQP02L06-M2	Ø38.2×21.3			
	LL01CR-ZExxL02-M2-T	Ø37.1×20.7	20°/30°/45°	9090	●
	LL01CR-EFF05L06-Mx-T	Ø37.5×18.5	5°	3535	●
	LL01ZZ-DBGxxL06-M2-T	Ø37.5×20	10°/15°/24°/36°/60° 15°×55°	5050	●
	LL01ED-AYxxL06-M2	Ø46×27.1	10°/38°	5050	-
	LL01ED-FGxxL06-M2			7070 9090	-

	Part No	Dimensions	Angle	LED Size	Tape
	LL01CR-PVxxL02-M2	Ø47.2×25.65	45°/60°/80°	5050 7070 9090	-
	LL01ZZ-AHAxxL06	Ø50×25.4	5°/10°	3535/5050/3045	-
	LL01ZZ-AHAxxL06-M2-T	Ø52×27	5°/10°	3535/5050	●
	LL01ZZ-AHAxxL06-M2-T + LL01ZZ-DCKxxL52	Ø52×27	10°/15°/20°/30°/40°/60°	3535/5050	●

Note Lens with Diffusion Sheet



AHA Series
Ø52×27mm



BLU Series
Ø38.2×22.2mm

Landscape Lighting

Waterproof Lens

*All dimensions are in millimeters.



	Part No	Dimensions	Angle	LED Size	Tape
	LL01ZZ-DCJ××L06	Ø15×8.7	30°/40°/60° 30°×50°	5050	-
	LL01ZZ-DBT××L06	Ø15×8.5	24°/36°/60°/30°×50°	2835 3030	-
	LL01ZZ-DBW××L06	Ø15.5×7.15	24°/30°/40°/60° 25°×45°/30°×60°	3030	-
	LL01OS-DMO2040L46	Ø16×8.5	20°×40°	3030	-
	LL01OS-BFV××L06	Ø20.8×12.35	10°/15°/25°/30° 10°×40°	2525 3045 3535 3030	-
	LL01ZZ-DGW××L06	Ø22×12	15°/20°/30°/45° 15°×45°	3030 3535	-
	LL01OS-DPP××L46	Ø22.5×12.4	10°/25°/40°	3030	-
	LL01ZZ-DCC××L06	Ø22.5×12.4	10°/15°/24°/36°/60° /10°×15°/10°×30° 10°×45°/10°×60°	3535	-

	Part No	Dimensions	Angle	LED Size	Tape
	LL01ZZ-DBO××L06	Ø22.5×12.4	15°/24°/30°/40°/60° 15°×30°/15°×45° 15°×60°	3030 3535	-
	LL01ZZ-DDO××L06	Ø22.5×13.3	15°/24°/30°/40°/60° 15°×30°/15°×45° 15°×60°	3030	-
	LL01CR-CAX××L06	20.5×20.5×13.8	10°×90°/25°×90°	3030 3535	-
	LL01CR-CAX3585L02	24×19×10.51	35°×85°	3535	-



Landscape Lighting

Color Mixing Lens

*All dimensions are in millimeters.

	Part No	Dimensions	Angle	LED Size	Tape
	LL01CR-YJxL02-M2-T	Ø21×13.9	25°/40°/60°	5050	•
	LL01CR-WYxL02-U2	Ø21×14.25	80°/100°	5052	-
	LL01CR-DYJxL06-U2	Ø21×14.25	25°/40°/60° 15°×30°/25°×60°	5052	-
	LL01ZZ-YLxL06-M2	Ø25×15	10°/20°/30° 15°×50°	3030	-
	LL01ZZ-YTxL06-M2				-
	LL01ED-CVxL06-M2	Ø21.1×15	15°/25°/45°	1LA5	-
	LL01ED-AFDxL06	Ø26×15.5	15°/20°	3535/5050	-
	LL01CR-DVY15L06	Ø35×20.1	15°	5050	-
	LL01ED-BCQxL06-M1	Ø38.1×20.2	15°/30°/40°/60°	5050	-
	LL01CR-BCQxL06-M1	Ø38.1×20.9	15°×30°/20°×55° 30°×50°	7090	-
	LL01CR-ANWxL06	Ø45×26.3	10°/20°/30°	7090/Ostar RGBW	-
	LL01CR-BJHxL06		10°/30°	5050	-



Windowsill Lens


Linear Light Distribution for Decorative Lighting



NEW CZP / DEZ Series



Simulation



Distribution



Dimensions

LL01CR-CZP03115L52	55×40×28 mm
LL01CR-CZP05100L52	55×40×28 mm
LL01CR-DEZ10115L06	25×20×15 mm

LED

3535/5050 (CZP Series)
3535/5050 (DEZ Series)



CZP Series




Commercial Lighting

- 19 V-CUT Series
- 21 Ultra-Thin Hybrid Lens
- 24 Zoom Lens
- 25 Ø20~50 mm
- 27 Ø50~80 mm
- 29 Ø80~100 mm







Commercial Lighting


V-CUT Series




Note Available with Positioning Structure.

Part No	FWHM	DxH	LED Size	Connector
Athena Series				
 LL01CR-DAW10L02	10°	Ø45×9.85	LES Ø6	LL01CIZA120H2 (CREE CXA1310/ CITIZEN CLU701)
 LL01CR-DAWxxL02	15°/24°/38° 10°×60°/30°×60°	Ø45×11.35 (With Lens)		
 LL01CR-DKW10L02	10°	Ø45×10.85		
 LL01CR-DKWxxL02	Note 15°/24°/38° 10°×60°/30°×60°			
 LL01CR-DAX10L02	10°	Ø60×13.27	LES Ø9	LL01CIYZ120H2 (CREE CXA15xx/ CITIZEN CLU711)
 LL01CR-DAXxxL02	15°/24°/38° 10°×60°/30°×60°	Ø60×14.77 (With Lens)		
 LL01CR-DKX10L02	10°	Ø60×14.77		
 LL01CR-DKXxxL02	Note 15°/24°/38° 10°×60°/30°×60°			
 LL01CR-DAY10L02	10°	Ø75×15.1	LES Ø9~9.8	LL01CRWF15H2 (CREE CXA1520/ CITIZEN CLU028)
LL01CR-DAYxxL02	15°/24°/38° 10°×60°/30°×60°	Ø75×16.6 (With Lens)		
LL01CR-DKY10L02	10°	Ø75×16.6		
LL01CR-DKYxxL02	Note 15°/24°/38° 10°×60°/30°×60°			
LL01CR-DAZ10L02	10°	Ø90×20	LES Ø14.5	LL01CRWC15H2 (CREE CXA1830/ CITIZEN CLU038)
LL01CR-DAZxxL02	15°/24°/38° 10°×60°/30°×60°			
LL01CR-DKZ10L02	10°			
LL01CR-DKZxxL02	Note 15°/24°/38° 10°×60°/30°×60°			

Part No	FWHM	DxH	LED Size	Connector
Apollo Series				
 LL01CR-DAHxxL06	15°/24°/36°	Ø54.7×30	LES Ø9~13.5	LL01CRWF15H2 (CREE CXA1520/ CITIZEN CLU028)
 LL01CR-CZXxxL06	15°/24°/38°	Ø71.8×44.8	LES Ø12	LL01CRWC15H2 (CREE CXA1830/ CITIZEN CLU038)
Zeus Series				
 LL01CR-CTZxxL52-C	24°/36°	Ø35×29	5050	-
 LL01CR-CTYxxL52-C	24°/36°	Ø50×37.35	5050	-

Part No	DxH	Assembly Lens	FWHM	LED Size
Hera Series - Anti-Glare Cover				
 LL01CR-CUG38L14	Ø67.5×25.13	LL01CR-CEW38L52	38°	LES Ø6
 LL01CR-CUE34L14	Ø112×41.69	LL01CR-CEN38L52	34°	LES Ø9
 LL01CR-CUF34L14	Ø123×42.03	LL01CR-CEO38L52	34°	LES Ø12

Assembly Instruction



Athena Series
DKW/DKX/DKY/DKZ

Hera Series
CUG/CUE/CUF

Zeus Series
CTZ/CTY

Commercial Lighting



Ultra-Thin Hybrid Lens

*All dimensions are in millimeters.



Part No	FWHM	DxH	Target LED	Connector	Snap Lock Solder-Free Connector
 LL01CR-CHQxxL02	24°/38°/45°	Ø35×10.5	LES Ø8~11	LL01A00CSLB2 (Cree CXA15xx CXB15xx)	LL01A00CWFB2 (Cree CXA13xx) LL01A00CWGB2 (Luminus CHM-6/CXM-6/Citizen CLU70x)
 LL01CR-CEWxxL02 Note	12°/24°/38°/45° 60°/27°×31° 36°×62°/38°×64°	Ø50×15	LES Ø8~11		
 LL01CR-DJCxxL06-M2 Note	30°×50°	Ø53.48×16.75	LES Ø8.9	-	-
 LL01CR-CENxxL02	12°/24°/38° 45°/60°	Ø70×17.5	LES Ø6~19	LL01A00CSKB2 (Cree CXA18xx)	LL01A00CWHB2 (Nichia 108B)
 LL01CR-CFExxL02	12°/24°/38°	Ø70×17.5	LES Ø6~19	LL01NIWZ24H2 (Nichia 108B)	LL01A00CWDB2 (Cree CXA15xx)
 LL01CR-CEOxxL02	12°/24°/38°	Ø90×19.5	LES Ø8.6~19	-	LL01A00CWEB2 (Citizen CLL03x)


Note Set Up Instruction



Snap Lock Solder-Free Assembly Instruction



Note CEW / DJC Series Lighting Effects



Commercial Lighting

Ultra-Thin Hybrid Lens

*All dimensions are in millimeters.


	Part No	FWHM	D×H	Target LED	Connector
	LL01ZZ-DYFxxL02-M2	15°/24°/38°/60°	Ø35×12.35	LES Ø4.5~9.8	LL01A00XVWB2 (CITIZEN CLU028 / CLU701 / CREE CXA1310) LL01A00XVXB2 (BRIDGELUX DS400 V4 HD)
	LL01ZZ-DUUxxL02-M2	15°/24°/38°	Ø45×14.7	LES Ø6~14.5	LL01A00CWJB2 (CREE 13xx / CITIZEN CLU701 / LUMILEDS L2C1 1202)
	LL01ZZ-CPRxxL46	24°/38°	Ø47×8.5	5050 LES Ø6~10	-
	LL01CR-CGIxxL52	24°/36°	24°: Ø53.5×8.7 36°: Ø53.5×6.7	LES Ø8.9	-
	LL01ZZ-DZKxxL02-M2	15°/24°/38°/60°	Ø62×22.7	LES Ø6~16	LL01A00CWNB2 (CITIZEN CLU711) LL01A00CXCBB2 (CREE CXA18xx) LL01A00CXDB2 (CREE CXA15xx) LL01A00CXEB2 (CITIZEN CLU028 / CLU701)
	LL01ZZ-DUVxxL02-M2	15°/24°/38°	Ø70×22.7	LES Ø6~14.5	LL01A00CWNB2 (CREE CAX15xx/18xx / CITIZEN CLU028)
	LL01ZZ-CPQxxL46	24°/38°	Ø74.4×13	7070 LES Ø8.9~16	-



Zoom Lens

	Part No	FWHM	D×H	Target LED	Connector
	LL01CT-DZM6015L06	15°~65°	Ø50×26.5	LES Ø6	-
	LL01CI-DZP6018L06	19°~60°	Ø70×35	LES Ø11	-

Assembly Instruction






Commercial Lighting

Ø20~50 mm

*All dimensions are in millimeters.



	Part No	FWHM	Dimensions	LED Size	Connector
	LL01ED-ACAxxL14	24°/38°	Ø29.9×12	7070 LES Ø8~12	-
	LL01NI-QI25L06-M2	25°	Ø30×17	LES Ø6.7~8.7	-
	LL01BR-DXQxxL06-M2	15°/24°/38°	Ø30×17	LES Ø4.5	-
	LL01CI-DXQxxL06-M2			LES Ø6	
	LL01CR-ABGxxL02	24°/38°/55°	Ø34×15.7	5050/7070/9090 LES Ø6~9	-
	LL01CR-BJL40L02	40°	Ø35×12.55	LES Ø6~13.2	-
	LL01DY-DTS10L52-M2	10°	Ø35×17.5	LES Ø2.8	LL01CIZA120H2 (TOYONIA M04/M05)
	LL01CI-DZUxxL06-M2	15°/24°/38°/60°	Ø35×20.9	LES Ø6	LL01A00XVWB2 (CITIZEN CLU701)
	LL01SP-AVA40L06	40°	Ø42×9.65	LES Ø4~18.5	-

	Part No	FWHM	Dimensions	LED Size	Connector
	LL01DY-DTT10L52-M2	10°	Ø43×27	LES Ø4	LL01CIZA120H2 (TOYONIA M04/M05)
	LL01WT-BSSxxL46	24°/32°	Ø44×12.2	LES Ø6~13.2	-
	LL01ED-ABY24L02	24°	Ø44×14.1	5050/7070 LES Ø4~9.8	-
	LL01CR-AQHxxL02	38°/45°	Ø44×14.1	5050/7070 LES Ø4~9.8	-
	LL01NI-BNXxxL02	38°	Ø44×14.6	3030 LES Ø6~9.9	-
	LL01CI-ZNxxL06	25°/40°	Ø44.4×11	LES Ø6	-
	LL01ZZ-DRXxxL06-M2	15°/24°/38°	Ø44.5×20.5	LES Ø6	LL01A00CWJB2 (CREE 13xx/ LL01A00CXHB2 (CITIZEN CLU701)
	LL01CI-WLxxL02	40°	Ø49.2×9.5	LES Ø6~16	-

Commercial Lighting

Ø50~80 mm

*All dimensions are in millimeters.



Part No	FWHM	Dimensions	LED Size	Connector
 LL01CR-CTK××L02-P	10°/15°	Ø49.5×7.8	3535 LES Ø6~6.7	-
 LL01CR-ABH××L02	40°/60°	Ø50×10.4	7070/9090 LES Ø6~16.2	-
 LL01CI-ZO××L06	25°/40°	Ø60×15.2	LES Ø9.8~13.5	-
 LL01ZZ-DRY××L06-M2	15°/24°/38°	Ø68.5×28.5	LES Ø9~9.8	LL01A00CXFB2 (CREE CXA15××) LL01A00CWMB2 (CREE CXA18××) LL01A00CXGB2 (CITIZEN CLU028)
 LL01CI-AAK××L06	25°	Ø68.8×19	LES Ø13.5~14.5	-
 LL01CI-ZM××L06	40°	Ø68.8×19.18	LES Ø13.5~14.5	-
 LL01CT-BBX××L06	24°/38°	Ø69×22.7	LES Ø9.8~14.6	-
 LL01CI-WN××L02	40°	Ø72×12.9	LES Ø8.9~16	-

Part No	FWHM	Dimensions	LED Size	Connector
 LL01ZZ-DRZ××L06-M2	15°/24°/38°	Ø74.5×28.5	LES Ø9~12	LL01A00CXDB2 (CREE CXA15××) LL01A00CXCБ2 (CREE CXA1830) LL01A00CXEB2 (CITIZEN CLU028)
 LL01ED-ABX××L06	24°/38°	Ø75.8×24.35	9090 LES Ø8~24.2	-
 LL01CR-BAY××L06	24°/38°	Ø76×22.5	LES Ø8.6~24.2	LL30A00SULB2 (Can be compatible with Ø25mm LED)
 LL01CT-AMY××L06	24°/38°	Ø76×23	LES Ø12~24.2	
 LL01CT-AZW××L02-P	12°/15°/24°/38°	Ø76.1×12.7	LES Ø9~19	LL30A00SUNB2-M2 (CITIZEN CLL020-1203)
 LL01CT-AOF××L06-M2	24°/38°	Ø76.4×16.7	LES Ø6~19	-



Commercial Lighting

Ø80~100 mm

*All dimensions are in millimeters.

Part No	FWHM	Dimensions	LED Size	Connector
 LL01CT-AZN××L02-P	15°/24°/38°	Ø88.5×15	LES Ø6~19	LL01A00SUFB2 (Citizen CLL030)
 LL01CT-BZN15L02-P	15°	Ø88.5×15	LES Ø9~19	LL38A00SUQB2-M2 (Citizen CLL030)
 LL01ED-ASA××L06-P	12°/24°/38°	Ø90.6×22	LES Ø8.6~26.5	LL38A00CSFM2 (Can be compatible with Ø20mm LED)
 LL01CT-APG××L06-M2	24°/38°	Ø90.8×22	LES Ø6~26.5	-
 LL01CI-WM××L02	40°	Ø92.5×27.5	LES Ø11.2~18.4	-



Street Lighting

- 31 2 in 1 / 4 in 1 / 6 in 1 / 8 in 1
- 33 12 in 1
- 35 16 in 1 / 20 in 1
- 37 Others



Street Lighting

2 in 1 / 4 in 1 / 6 in 1 / 8 in 1

*All dimensions are in millimeters.



	Curve	Type	Part No	FWHM	Dimensions	LED	Gasket
		II	LL02CR-AUV45135L52	45°×135°	50×24.8×8.53	5050	-
			LL02CR-AUH45135L52				
		II	LL04CR-BXJ80150L02	80°×150°	50×50×7.05	3030 3535 5050	-
		III	LL04CR-BXJ45155L02	45°×155°	50×50×6.95		
		III	LL04CR-BXJ95165L19	95°×165°	50×50×4.2		
		IV	LL04CR-BXJ65165L19	65°×165°	50×50×6.97		
		V	LL04CR-BXJ60L02	60°	50×50×7.3		
		V	LL04CR-BXJ90L02	90°	50×50×7.3		
		I	LL04CR-CGM85135L02	85°×35°	50×50×6.9	3030 3535	-
		I	LL04CR-AU45135L46	45°×135°	50×50×8.3	5050	-
		V	LL04CR-CXE165L19	165°	50×50×5.82	3030 3535	-

	Curve	Type	Part No	FWHM	Dimensions	LED	Gasket
		V	LL04CR-CXR165L52	165°	50×50×6.68	3030 3535	-
		II	LL04CR-CFN35155L02	35°×155°	50×50×6.5	3030 3535	-
		II	LL04LU-CFN90150L06	90°×150°	50×50×5.72	5050	-
		II	LL04LU-CFN110150L06	110°×150°	50×50×5.76	5050	-
		III	LL04LU-CFN70150L06	70°×150°	50×50×5.85	5050	-
		III	LL04CR-CFN60155L02	60°×155°	50×50×7.3	3030 3535	-
		II	LL04ZZ-WAU35140L52	35°×140°	65×65×9.9	3030 3535 5050	1
		Under Design	LL06ZZ-DUP70150L06	70°×150°	50×50×5.76	5050	-
		Under Design	LL06ZZ-DUP100150L06	100°×150°	50×50×5.86		
		I	LL08BR-DCB35140L52	35°×140°	118.26×70.26×9.69	3030 5050	2

1 LL01A00SVX2 2 LL01A00SWX2

Street Lighting

12 in 1

*All dimensions are in millimeters.



	Curve	Type	Part No	FWHM	Dimensions	LED	Gasket
		I	LL12ZZ-CRC40135L19	40°×135°	50×50×5.3	3030 3535	-
		II	LL12ZZ-CRC45145L19	45°×145°	50×50×5.3		
		II	LL12ZZ-CRC45155L19	45°×155°	50×50×5.3		
		III	LL12ZZ-CRC60145L19	60°×145°	50×50×4.9		
		III	LL12ZZ-CRC60155L19	60°×155°	50×50×5.1		
		IV	LL12ZZ-CRC75140L19	75°×140°	50×50×4.43		
		V	LL12ZZ-CRC150L19	150°	50×50×4.05		
		II	LL12SS-AU85135L19	85°×135°	50×50×4.31	3030 3535	-
		II	LL12OS-EL50130L02	50°×130°	158.4×50.3×9.1	5050	-


	Curve	Type	Part No	FWHM	Dimensions	LED	Gasket
		II	LL12CR-CUQ60145L19 Vertical	60°×145°	173×71.4×8.15	3030 3535 5050	1
		II	LL12CR-CUQ70140L19 Horizontal	70°×140°	173×71.4×9.04		
		II	LL12NI-CUQ65150L06 Vertical	65°×150°	173×71.4×8.88		
		III	LL12CR-CUQ85155L19 Vertical	85°×155°	173×71.4×8.58		
		IV	LL12LU-CUQ15050L19 Horizontal	150°×50	173×71.4×8.4		
		IV	LL12CR-CUQ15155L19 Vertical	15°×155°	173×71.4×8.87		
		V	LL12CR-CUQ150L19	150°	173×71.4×8.63		
		II	LL12NI-CUQ55150L06 Vertical	Design is under modification			
		II	LL12NI-CUQ15055L06 Horizontal	Design is under modification			
		II	LL12NI-CUQ65145L06 Vertical	Design is under modification			

1 LL01A00RSOX2

Street Lighting

16 in 1

*All dimensions are in millimeters.

	Curve	Type	Part No	FWHM	Dimensions	LED	Gasket
		I	LL16ZZ-DVV25145L19	25°×145°	50×50×4.18	LES Ø2.6	-
		II	LL16ZZ-DVV45140L19	45°×140°	50×50×4.17		
		II	LL16ZZ-DVV45155L19	45°×155°	50×50×3.92		
		III	LL16ZZ-DVV60145L19	60°×145°	50×50×3.78		
		III	LL16ZZ-DVV60155L19	60°×155°	50×50×3.68		
		IV	LL16ZZ-DVV70160L19	70°×160°	50×50×3.63		
		V	LL16ZZ-DVV150L19	150°	50×50×3.8		
		I	LL16SE-BQL45145L51	45°×145°	167.6×73.6×7.6	5050	-



20 in 1

	Curve	Type	Part No	FWHM	Dimensions	LED	Gasket
		II	LL20ZZ-DTD70155L46	70°×155°	270×70×10.61	5050	
		III	LL20ZZ-DTD90150L46	90°×150°			
		III	LL20ZZ-DTD20140L46	20°×140°			
		IV	LL20ZZ-DTD110150L46	110°×150°			
 LL01AOXRWUX2							



Street Lighting

Others


*All dimensions are in millimeters.



	Curve	Type	Part No	FWHM	Dimensions	LED	Gasket
		I	LL18SE-CBZ50150L51	50°×150°	198×68×7.6	3030	①
			LL22SE-CBZ50150L51		238×68×7.6	4040	②
			LL28SE-CBZ50150L51		158.3×98.03×7.6	5050	③
			LL36SE-CBZ50150L51		188×98×7.6		④
		I	LL11SE-DFY40130L52-W	40°×130°	80×60×7.13		-
			LL22SE-DFY40130L52-W		109×119×9.5	3535	-
			LL28SE-DFY40130L52-W		100×100×9.1		⑤
		II	LL18HM-CSP60130L46	60°×130°	211×83×4.5	3030	-
		I	LL30NI-CTJ60145L51	60°×145°	107×84×5	3030	-
		II	LL30NI-CTX70150L51	70°×150°	134×68.5×6.07	3030	-
		I	LL38OS-CRR40145L46	40°×145°	229.4×70×13.4	3030	-
		II	LL38OS-CRR55155L46	55°×155°	229.4×70×13.4		
		II	LL40OS-CPJ75140L51	75°×140°	100×40×3.46	3030	-
		I	LL48NI-CTX70150L46	70°×150°	230×60×6.64	3030	-
		III	LL48NI-CTX60155L46	60°×155°	230×60×6.64		

① LL01A0XRQX2 ② LL01A0XRVX2 ③ LL01A0XRVSX2 ④ LL01A0XRVTX2 ⑤ LL01A00SXZ2

	Curve	Type	Part No	FWHM	Dimensions	LED	Gasket
		II	LL84BR-DCN45150L46	45°×150°	200×70×5	3030	-
		II	LL140SE-CKT45130L51	45°×130°	272.6×123.6×9.2	3030	-



Area Lighting

- 43 4 in 1 / 6 in 1 / 8 in 1
- 44 12 in 1 / 16 in 1 / 18 in 1
- 45 Linear Lens



Area Lighting

4 in 1 / 6 in 1 / 8 in 1

*All dimensions are in millimeters.



	Part No	Dimensions	FWHM	LED Size	Gasket
	LL04CR-CECxxL06	50×50×10	9°	3030	-
		50×50×8.5	25°/50°	3535	
	LL04CR-CXRxxL52	50×50×12.86	25°/60°	5050	-
		50×50×12.99	40°		
		50×50×6.68	165°		
	LL04CR-DBJ2090L52	50×50×12.6	20°×90°	3535 5050	-
	LL04CR-DJL05L06	50×50×25.45	5°	3535	-
	LL06ZZ-DUP60L06	50×50×7.13	60°	5050	-
	LL06ZZ-DUP90L06	50×50×6.73	90°		
	LL06ZZ-DUP150L06	50×50×6.26	150°		
	LL08CR-CYTxxL52	50×50×7.4	30°	3535	-
		50×50×7	55°		
		50×50×6.93	90°		
	LL08NI-DNN60L06	118.8×71.4×11.23	60°	5050	1
	LL08NI-DNN90L06	118.8×71.4×8.75	90°		
	LL08NI-DNN150L06	118.8×71.4×8.75	150°		

1 LL01A00RTAX2

12 in 1 / 16 in 1 / 18 in 1

	Part No	Dimensions	FWHM	LED Size	Gasket
	LL12CR-CUQxxL19	173×71.4×13.15	30°	3535 5050	1
		173×71.4×11.28	60°		
		173×71.4×8.81	90°		
		173×71.4×8.63	150°		
	LL12ZZ-CRCxxL19	50×50×6.3	25°/55°	3030	-
		50×50×3.8	90°		
		50×50×4.05	150°		
	LL12SS-CRCxxL19	50×50×9.6	10°	3535	-
		50×50×6.28	25°		
		50×50×5.63	55°		
		50×50×4.91	90°		
	LL16ZZ-DVVxxL19	50×50×6.3	25°	3030	-
		50×50×7.3	55°		
		50×50×3.8	90°		
		50×50×3.8	150°		
	LL18ZZ-DZR60L02	173×71.4×11.28	60°	5050	1
	LL18ZZ-DZR90L02	173×71.4×8.8	90°		
	LL18ZZ-DZR150L02	173×71.4×8.45	150°		

1 LL01A00RSOX2


Area Lighting

Linear Lens

*All dimensions are in millimeters.




Curve	Part No	FWHM	Dimension	LED Size	Gasket
	LL01NI-CRO15L06	15°	280×26.63×11.7	2835 3030 5630	-
	LL01NI-CRO30L06	30°	280×26.63×11.7		
	LL01NI-CRO45L06	45°	280×26.63×11.7		
	LL01NI-CRO60L06	60°	280×26.63×9.45		
	LL01NI-CRO100L06	100°	280×26.63×9.59		
	LL01NI-CRO3090L06	30°×90°	280×26.63×9.45		
	LL01NI-CRO3595L06	35°×95°	280×26.63×11.86		
	LL01NI-CRO70125L06	70°×125°	280×26.63×10.49		
	LL01NI-CRO110145	110°×145°	280×26.63×10		




	Curve	Part No	FWHM	Dimension	LED Size	Gasket
		LL01ZZ-DYB60L06	60°	1140×26.14×6.2	2835 3030 3535 5630	-
		LL01ZZ-DYB90L06	90°	1140×26.14×6.2		
		LL03ZZ-CRO3090L06	30°×90°	286×61×9.45	2835 3030 5630	-
		LL03ZZ-CRO3595L06	35°×95°	286×61×11.4		
		LL03ZZ-CRO6090L06	60°×90°	286×61×9.45		
		LL03ZZ-CRO70125L06	70°×125°	286×61×9.9		
		LL03ZZ-CRO100L06	100°	286×61×9.45		
		LL24NI-CRO60L06	60°	280×26.63×9.45	2835 3030 5630	-
		LL24NI-CRO90L06	90°			

CRO Series Sectional View

LL01NI-CRO××L06




LL03NI-CRO××L06



LL24NI-CRO××L06





Area Lighting

Linear Lens

*All dimensions are in millimeters.



	Curve	Part No	FWHM	Dimension	LED Size	Gasket
		LL33LU-DOA25L52	25°	321×79×9.07	2835 3030 5630 5050	1
		LL33LU-DOA60L52	60°	321×79×9.4		
		LL33LU-DOA90L52	90°	321×79×9.07		
		LL44ZZ-DCP30L52	30°	280×62×9.35	2835 3030 3535	-
		LL44ZZ-DCP60L52	60°	280×62×8.1		
		LL44ZZ-DCP90L52	90°	280×62×7.5		
		LL44ZZ-DCP20110L52	20°×110°	280×62×9.07		
		LL44ZZ-DCP70120L52	70°×120°	280×62×8.63		

1 LL01A00RTBX2





Automotive Lighting

- 51 Head Lamp
 - Tail Lamp
 - Lateral Linear Lens
 - Daytime Running Light
 - Reading Lamp
 - Motorcycle Head Lamp
- 53 Automotive Lighting Equipment



Automotive Lighting

Overview



Tail Lamp



Lateral Linear Lens



Daytime Running Light



Head Lamp



Reading Lamp



Motorcycle Head Lamp



Automotive Lighting Equipment

Goniophotometer for Automotive and Signal Lights

Function

With this system, Ledlink is able to validate light distribution quality quickly in house for signal light, automotive lighting, marine lighting, agricultural vehicles lighting, retroreflector...etc. It fully meets the requirement of relevant standards including national standard, SAE, JIS, ECE...etc.

Testing Range

Horizontal Rotation Range of Luminaires	-180°~+180°
Vertical Rotation Range of Luminaires	-120° ~+120°
Adjustable Range (Z Axis)	0~380mm
Maximum Loading	35kg
Photometry Range	0.0001 lx~200000 lx

Accuracy

Accuracy of angle	0.03°
Everfine Class A detector	f1' <3%

Measurement

Fixing the lamp and adjust the center with laser positioning point; lighting up the lamp till the heat stable and starting measurement.

Testing Room

Length	27.5 meters
Width	7 meters



Control system
(Measurement Station,
Power Supply, Photometer)



Spectrometer



Detector



Testing Room

www.ledlink-optics.com

service@ledlink-optics.com

Ledlink Optics, Inc

Taiwan HQ

15F, No.655, Bannan Rd., Chung-Ho Dist.,
New Taipei City, Taiwan 235

Ledlink Optics (Dongguan) Co., Ltd

Dongguan Factory

No.5, TianKeng Industrial Dist., HengLi Town, DongGuan City,
GuangDong Province, China 523478

Ledlink Optics (Yangzhou) Co., Ltd

Yangzhou Factory

No.180, LinJiang Rd., YangZhou City, Jiangsu Province, China 225009

