

jd LED Garden Light JD-G023

Used in high strength aluminum material,
surface anit-ageing electrostatic
spray processing,super resistance to corrosion.
UV resistant lens



CE CB

With lens

Without lens

技术参数Specification

产品型号	Product Code	JD-G023-30W	JD-G023-60W	JD-G023-100W	JD-G023-150W
灯珠电流	Electric Current (mA)	50mA 5050/67mA 3030	54mA 5050/67mA 3030	63mA 5050/84mA 3030	94mA 5050/119mA 3030
LED数量	LED Quantity	24pcs 5050/72pcs 3030	48pcs 5050/144pcs 3030	64pcs 5050/192pcs 3030	64pcs 5050/192pcs 3030
额定功率	Rate Power	30W	60W	100W	150W
色温	ColorTemperature	6500/4000/3000K	6500/4000/3000K	6500/4000/3000K	6500/4000/3000K
灯具光效	Luminous Flux	160lm/w(5050) 150lm/w(3030)	160lm/w(5050) 150lm/w(3030)	160lm/w(5050) 150lm/w(3030)	150lm/w(5050) 140lm/w(3030)
输入电压	InputVoltage	AC100-240V	AC100-240V	AC100-240V	AC100-240V
频率	Frequency Range	50/60Hz	50/60Hz	50/60Hz	50/60Hz
显色指数	ColorTemperature	RA75	RA75	RA75	RA75
工作环境温度	Temperatureof working condition	-40℃-50℃	-40℃-50℃	-40℃-50℃	-40℃-50℃
工作环境湿度	humidity of working condition	20%-90%	20%-90%	20%-90%	20%-90%
LED 寿命	LED life time	70000h	70000h	70000h	70000h
防护等级	Protestion Grade	IP66	IP66	IP66	IP66
安装管径	Installation Pipe Dia	Φ60mm/Φ76mm	Φ60mm/Φ76mm	Φ60mm/Φ76mm	Φ60mm/Φ76mm
安装高度	Installation Height	3-5m	4-6m	7-9m	10-12m
净重	NetWeight	10kg	10.3kg	10.6kg	10.9kg
毛重	GrossWeight	12kg	12.3kg	12.6kg	12.9kg
产品尺寸	ProductSize	600x600x589mm	600x600x589mm	600x600x589mm	600x600x589mm
包装尺寸	Packing Size	755x635x120mm	755x635x120mm	755x635x120mm	755x635x120mm

注：包装尺寸为外尺寸
本表所示技术参数均在环境温度25℃，湿度35%的实验室环境中测得。

Packing size is outer size of box
All parameters are measured at 25℃ ambient temperature, 35% humidity experimental environment.

Active Night

Built-in night lowering, the luminaire is automatically dimmed according to the following intervals.
100% light ~ 21.00
70% light 21: 00 ~ 00: 00
50% light 00: 00 ~ 04: 00
70% light 04: 00 ~ 06: 00
100% light 06.00 ~
The luminaire needs at least 3 days to activate the night lowering

1. Dimmable or Non-dimmable two options.
2. Traditional design suit European market.
3. Die-casting Aluminium cap and body Ik09
4. Mitsubishi Milky PC and transparent PC UV resistant.
light disbution uniform and dazzle light.
5. Black and silver two color options.
6. Wattage adjustable.

Applications (foroutdooruse):

Gardens, parks, school gardens, residential areas, farms, parking and other public areas.

AC100-240V 输入电压 Input Voltage	Hz 50/60 频率范围 Frequency Range	PF >0.92 功率因数 Power Factor	<15% 总谐波失真 THD	CRI 75 显色指数 Color Rendering Index	40-45℃ 工作环境温度 Temperature of Working Condition	10-90% 工作环境湿度 Humidity of Working Condition	70000h 使用寿命 Life Time	IP66 防护等级 Protection Grade
-------------------------------------	--	-------------------------------------	----------------------	--	--	---	-----------------------------	----------------------------------