

LED Sports Light

HL-SP06-500W/600W








Five-year warranty



Features:

- >IP66 waterproof rating, 5 years warranty.
- >Modular design, simple maintenance and convenient assembly and disassmbly.
- >High strength structure coated with corrosion resistant polyester powder, real anti-corrosion.
- >Multiple options for beam angle, ensure venues are multi-used.
- >Color temperature optional
- >Certified product CE, RoHS, DLC, FCC, UL.
- >Widely used in stadium, sports field, high mast lighting, light tower, ports... Applicable for most places.

Photometric Diagrams 30°~60°Optional










Radiator

With fin heat sinks, increased heat dissipation and a longer life for SD series sports lighting.

The back cover has a cooling effect (the power is placed on the back cover, and the heat generated is conducted to the back cover to dissipate heat)



Laser Aiming Devices (Optional)

The Laser Aiming Device gives you precision control in angling and aiming each sport light to its exact optimal position.



Application








Bracket

The whole lamp can be adjusted in angle by changing the bracket.





LED SPORTS LIGHT

HL-SP06-500W/600W

Specifications

Electrical Data

500W/600W Wattage

INVENTRONICS/MEANWELL **PowerSupply** AC90-305V/AC100-277V Input Voltage

50/60Hz **Power Frequency** >95% **Power Efficiency** 0.95 **Power Factor Total Harmonic Distortion** <15%



Optical Data

Lumen Version

LED Type

Efficiency 150lm/W(500W), 140Lm/W(600W)

Luminous Flux 75,000Lm/ 84,000Lm CCT 4000K,5000K,5700K

CRI >70Ra System Efficiency >90% **Beam Angle** 30°/40°/60°

Others


IP66 -30~45℃ Operating temperature


Die-cast aluminum **Heat Radiator**

Lens Material

Control Method 0-10V Light Control **Carton Dimension** 500*405*415mm

Net Weight 12.5kg(500W),15KG(600W) **Fixture Dimension** 450*450*355mm (1pcs) **Gross Weight** 14.5kg(500W), 17KG(600W)

















Packing including

- 1.1pcs led sports light
- 2.1pcs product user manual

Address: Building A, Jinkaijin Industrial Park, Shilongzai, Shiyan, Bao'an, Shenzhen, China

Tel: +86 755-23031787 Fax: +86 755-23057895