



04 UFO

No matter how dark the road is, there will be light.



UFO01 · UFO02 · UFO03 · UFO04

UFO-01

UFO luminaires for high spans are designed for general lighting of production and storage facilities, gyms, skating rinks, retail and exhibition areas, hypermarkets.


The luminaires are an energy-efficient replacement for luminaires with traditional DRL, DNaT, MGL light sources, have a long service life, do not require lamp replacement and additional operating costs.



DOB VERSION

SUPER SLIM DESIGN





2835 SMD with lens



Super slim design



**Die-casting
aluminum body**



IP65



Warranty: 3 years

IP rating: 65

Lumen efficiency:

100lm/w, 130lm/w

CRI: 70



Code	TR-U01-100W	TR-U01-150W	TR-U01-200W
Rated power	100W	150W	200W
Luminous efficiency	100lm/w, 130lm/w		
Color temperature	CW(6500K), NW(4000K), WW(3000K)		
Color rendering index	>70		
SDCM	<6		
IP rating	IP65		
IK rating	IK06		
Electrical class	Class I		
Working temperature	-20°C to 45°C (Ta 35°C)		
Lifespan	30000 hrs		
Beam angle	90°/110°		
Input Voltage	220-240V/100-277V AC 50-60Hz		
Power factor	0.9		
Surge protection rating	L/N—2000V; L/G, N/G—2000V		
Installation	Hanging Hook Installation		
Body material	Aluminum Die casting body, tempered glass cover		
Size	235*85mm	285*85mm	315*85mm

UFO-02

This rugged series LED high-bay light features a 50,000-hour long lifespan, an IP65 ,IK 06 protection, and the highest power efficiency (150lm/w) available on the market. The product is ideal for general, task, and accent lighting, especially those with high-ceiling (5m and above). The series high-bay lights come in 3 options: 100W, 150W and 200W.



SEPARATED DRIVER

DIE CASTING ALUMINUM BODY





2835 SMD



Die-casting aluminum body



Separate driver



Fast Heat Dissipation



Warranty: 5 years **IP:** 65

Lumen efficiency: 150 lm/w **Ra**70

Beam angle: 90°

Color: Black/Grey/Sliver

Main Material: Die casting aluminum



Code	TR-U02-100W	TR-U02-150W	TR-U02-200W
Lumen output	15000lm	22500lm	30000lm
Rated power	100W	150W	200W
Luminous efficiency	150lm/w		
Color temperature	CW(6500K), NW(4000K), WW(3000K)		
Color rendering index	>70		
SDCM	<6		
IP rating	IP65		
IK rating	IK06		
Electrical class	Class I		
Working temperature	-20 °C to 45 °C (Ta 35 °C)		
Lifespan	50000 hrs		
Beam angle	90°		
Input Voltage	85-305V AC 50-60Hz		
Power factor	0.9		
Surge protection rating	L/N—4000V; L/G, N/G—4000V		
Installation	Hanging Hook Installation		
Body material	Aluminum Die casting body, tempered glass cover		
Size	235*85mm	285*85mm	315*85mm

UFO-03

Super slim designing UFO luminaires are designed for general lighting of production and storage facilities, gyms, retail, hypermarkets. The luminaires have a long service life, do not require lamp replacement and additional operating costs. This series high-bay lights come in 4 options: 100w, 150w, 200w, 250w.



DOB VERSION

SUPER SLIM DESIGN





2835 SMD



**Self-clean
arc backside design**



Die-cast aluminum body



Super slim design

Warranty: 3 years


IP rating: 65

Lumen efficiency:


100lm/w; 130lm/w

CRI: 70

Illuminance at a Distance



Luminous Intensity Distribution Curve (200W)



Code	TR-U03-100W	TR-U03-150W	TR-U03-200W	TR-U03-250W
Rated power	100W	150W	200W	250W
Luminous efficiency	100lm/w, 130lm/w			
Color temperature	CW(6500K), NW(4000K), WW(3000K)			
Color rendering index	>70			
SDCM	<6			
IP rating	IP65			
IK rating	IK06			
Electrical class	Class I			
Working temperature	-20°C to 45°C (Ta 35°C)			
Lifespan	30000 hrs			
Beam angle	90°			
Input Voltage	100-277V/220-240V AC 50-60Hz			
Power factor	0.9			
Surge protection rating	L/N—2000V; L/G, N/G—2000V			
Installation	Hanging Hook Installation			
Body material	Aluminum Die casting body, tempered glass cover			
Size	265*40mm	290*41mm	317*42mm	365*44mm

UFO-04

This series UFO highbay light with separated brand driver, features a 50,000 hours long lifespan, an IP65, IK06 protection and the highest lumen efficiency of 200lm/w. Widely used to workshops, warehouses, logistics centers, exhibition halls, supermarket...



SEPARATED BRAND DRIVER(SOSEN/MEAN WELL)

HIGH LUMEN EFFICIENCY (200LM/W)





Brand LED



Performance safety



Die-cast heatsink



Brand driver


Warranty: 5 years

IP rating: 65


Lumen efficiency: 200lm/w

CRI: 70

Illuminance at a Distance



Luminous Intensity Distribution Curve (200W)



Code	TR-U04-100W	TR-U04-150W	TR-U04-200W	TR-U04-240W
Lumen output	20000lm	30000lm	40000lm	48000lm
Rated power	100W	150W	200W	240W
Luminous efficiency	200lm/w			
Color temperature	CW(6500K), NW(4000K), WW(3000K)			
Color rendering index	>70			
SDCM	<6			
IP rating	IP65			
IK rating	IK06			
Electrical class	Class I			
Working temperature	-20°C to 45°C (Ta 35°C)			
Lifespan	50000 hrs			
Beam angle	60°/90°/120°			
Input Voltage	85-305V/200-480V AC 50-60Hz			
Power factor	0.95			
Surge protection rating	6kV			
Installation	Hanging Hook Installation			
Body material	Aluminum Die casting body, tempered glass cover			
Size	248*158mm	308*168mm	360*174mm	360*174mm