



LED Downlight Light- Commercial Options

Due to the environmental protection policy, now many customers are seeking to replaceable luminaires for their house, offices, hotels, etc., so the modular design of lighting products are become more and more popular in the market. Rayven team just launch a new range LED Modular Design Downlight, which with 3 size of LED module, and come with different design of bezel: Round / Square, and different cutout size of bezels to cover all the market needed.


For these range of commercial downlight, they can come with standard single power, or with twin power supply, single color temperature and color temperature changeable, up to 120lm/W, CRI>90, SDCM<3, with 5 years warranty.

Moreover, with Rayven drivers can offer professional DALI 2.0 control, 0-10V Dimming, Triac Dimming, as well as Smart controlled by Zigbee, WiFi & Bluetooth.

DALI+ builds on the proven and sophisticated DALI lighting-control features in wired (DALI-2 and D4i) options, and offers access to the same rich set of data from control gear, luminaires and sensors. DALI+ devices communicate using existing DALI commands, but these are carried over a wireless and/or IP-based medium rather than the dedicated pair of wires used by DALI-2 and D4i.


The DALI Alliance operates the DALI-2 and D4i certification programs to boost levels of cross-vendor interoperability. As lighting continues to evolve and converge with the IoT, the consortium says it is also driving the standardization of wireless and IP-based connectivity solutions.

In support of the technology's advancement, the DALI Alliance has published a new DiiA Specification, which supports DALI+ across different carriers and will lead to certification of interoperable DALI+ devices. The first certification program will be DALI+ with Thread, a low-power, IP-based, wireless-mesh networking protocol.




DALI 2.0

All the range of LED downlights can come with DALI 2.0 control, we can offer DALI DT6 & DT8 dimming driver solutions.




Smart Control


Since Tuya Smart Control now is more and more popular in the market, of course for these LED ceiling lights also can be made into Smart Control, such as Zigbee, WiFi & Bluetooth, just to replace a Rayven Smart Driver to control on the Dimming, Color changing, group control and smart scene, etc., just to offer a Smart-Life to you.




F Series Antiglare light UGR<19




| | | | | |
|------------------|--------------------------------------|------------|-------------|-------------|
| Model | RAV12DLF41 | RAV20DLF61 | RAV30DLF81 | RAV40DLF81 |
| Power | 10W/ 12W | 20W/ 25W | 30W/35W | 35W/ 40W |
| Lumen | 120LM/W | | | |
| Beam angle | 60° | | | |
| CCT Change | 3000K/4000K/5000K | | | |
| CRI | Ra>90 | | | |
| UGR | <19(2H) | | | |
| SDCM | SDCM <3 | | | |
| Lifespan | 50,000hrs | | | |
| Voltage | 220-240VAC | | | |
| Product size | Ø143*H78mm | Ø143*H78mm | Ø185*H105mm | Ø226*H110mm |
| Dimmable option | Triac Dim, DALI Dim, 0-10V Dim | | | |
| ERP 2.0 | Yes | | | |
| IP-class | IP54 | | | |
| IK-class | IK03 | | | |
| Insulation Class | Class II | | | |
| Material | Aluminum | | | |
| Environment | Indoors | | | |
| Installation | Shopping malls, showcases, showrooms | | | |
| Warranty | 3 years/5 years | | | |
| Approval | CE, SAA, ERP, UKCA | | | |



Low UGR Downlight




| Model | RAV12DLG41 | RAV20DLG61 | RAV30DLG81 |
|------------------|--------------------------------------|------------|------------|
| Power | 10W/12W | 15W/20W | 30W/35W |
| Lumen | 120LM/W | | |
| Beam angle | 100° | | |
| CCT Change | 3000K/4000K/5000K | | |
| CRI | Ra>80 Ra>90 | | |
| SDCM | SDCM <3 | | |
| Lifespan | 50,000hrs | | |
| Voltage | 220-240VAC | | |
| Product size | Φ143*70mm | Φ192*70mm | Φ220*70mm |
| Dimmable option | Triac Dim, DALI Dim, 0-10V Dim | | |
| ERP2.0 | Yes | | |
| IP-class | IP40, IP44 | | |
| IK-class | IK03 | | |
| Insulation Class | Class II | | |
| Material | Aluminum | | |
| Environment | Indoors | | |
| Installation | Shopping malls, showcases, showrooms | | |
| Warranty | 3 years/5 years | | |
| Approval | CE, SAA, ERP, UKCA | | |




Size: Ø143*H70mm
Ø192*H70mm
Ø220*H70mm


F Series Rectangular Wall-washer



| Model | RAV30SLF51 | RAV40SLF51 | RAV50SLF51 |
|------------------|--------------------------------------|------------|------------|
| Power | 20W/25W | 35W/40W | 50W |
| Lumen | 120LM/W | | |
| Beam angle | 120° | | |
| CCT Change | 3000K/4000K/5000K | | |
| CRI | Ra>90 | | |
| UGR | <19(2H) | | |
| SDCM | SDCM <3 | | |
| Lifespan | 50,000hrs | | |
| Voltage | 220-240VAC | | |
| Product size | 240*157*92mm | | |
| Dimmable option | Triac Dim, DALI Dim, 0-10V Dim | | |
| ERP2.0 | Yes | | |
| IP-class | IP40 | | |
| IK-class | IK03 | | |
| Insulation Class | Class II | | |
| Material | Aluminum | | |
| Environment | Indoors | | |
| Installation | Shopping malls, showcases, showrooms | | |
| Warranty | 3 years/5 years | | |
| Approval | CE, SAA, ERP, UKCA | | |



G Series Scoop Wall-washer



| | | | | |
|------------------|---|------------|------------|------------|
| Model | RAV30SLG51 | RAV30SLG61 | RAV40SLG81 | RAV50SLG81 |
| Power | 20W/30W | 35W/40W | 35W/40W | 50W |
| Lumen | 120LM/W | | | |
| Beam angle | 24°&45° | | | |
| CCT Change | 3000K/4000K/5000K | | | |
| CRI | Ra>90 | | | |
| UGR | <19(2H) | | | |
| SDCM | SDCM <3 | | | |
| Lifespan | 50,000hrs | | | |
| Voltage | 220-240VAC | | | |
| Product size | Ø157x110mm Ø190x130mm Ø247.2*178.3mm Ø247.2*178.3mm | | | |
| Dimmable option | Triac Dim, DALI Dim, 0-10V Dim | | | |
| Flicker Free | Yes, New ERP | | | |
| Dual power | Yes | | | |
| IP-class | IP40 | | | |
| IK-class | IK03 | | | |
| Insulation Class | Class II | | | |
| Material | Aluminum | | | |
| Environment | Indoors | | | |
| Installation | Shopping malls, showcases, showrooms | | | |
| Warranty | 3 years/5 years | | | |
| Approval | CE, SAA, ERP, UKCA | | | |

