

LED Linear Trunking System

160 LM/W



30°



60°



90°



120°




Asymmetric-R



Asymmetric-L



25° Double







LED Linear Trunking System

E Line IP40

Fast and smooth Installation

E-line can be quickly and easily set up by installers of all ability levels, thanks to its clearly definable components and simple click together assembly.




CONTENT

Applications

- 002-003** Industry
- 004-005** Shop & Retail

Product detail

- 006** Explosion Drawing
- 007-012** LED module
- 013-015** Trunking
- 016-017** Accessory



Applications

Industry

Warehouse - Swedan

Linear trunking system is an efficient, flexible and versatile system providing lighting solutions for various applications of industry, commerce, office, etc. Thanks to its seamless linkable function, linear trunking sy-stem from Recolux is perfect in being installed in broad warehouses. It provides many lighting options wi-th various luminaire elements, optics, functional modules to meet different lighting requirements.

In this case, the luminaire is 12.0 meters away from the ground, using a 60W 30 degree lens.

Project Request



Quantity	Recolux Code	Description
10	RE-TNC-B1-05W	7 wires Feed In Box,White
200	RE-TKA9-05W-00	E-Line 2876mm trunking 7 x 2.5 mm²,white
156	RE-RSL5S3-60P1SP-S1-00	E-Line LED Module 35°,32-60W, 9,000 lm, 5,000 K, non-dimmable,White
10	RE-TNC-B0-00W	Feed End Box ,White
244	RE-15-FF	1438mm PC Blind cover
300	RE-SMK	Steel suspension



Applications

Industry

Production Workshop-Germany

E-Line is the newest design on LED lighting for trunking, which provides the optimized lighting solution for commercial and industrial lighting applications. Reliable lighting systems from Recolux help improve safety and energy conservation, as well as productivity and efficiency. In this case, customer demands seamless connection. To provide better services for our customers, we are committed to constantly upgrading our products. This light is easy to install within 43s. This advantage brings convenience to our customers.

Project Request



Quantity	Recolux Code	Description
24	RE-TNC-B1-07W	7 wires Feed In Box ,white
242	RE-TKA9-07W-00	E-Line 2876mm trunking 7 x 2.5 mm²,white
30	RE-TKA5-07W-00	E-Line 1438mm trunking 7 x 2.5 mm²,white
278	RE-RSL5S5-68P1WD-T4-00	E-Line LED Module 90°,68W, 10,200 lm, 5,000 K, DALI dimmable, white
246	RE-15-FF	1438mm PC Blind cover
24	RE-TNC-B0-00W	Feed End Box,white
546	RE-DMK	Chain suspension



Applications

Shop & Retail


Supermarket - Spain

As a true all-rounder, the Recolux E-Line system is ideal for perfectly illuminating Supermarket. A presence and daylight-dependent control is also possible. This exploits the potential for sustainable energy savings in building management.

The continuous lighting modular system consists of only a few basic elements that offer a tailor-made solution for almost every task due to their combination possibilities. The configuration of the lighting system is simple and adapted to the respective project requirements. During the later installation of the lights, the electrician is happy: almost all parts are only snapped, plugged or fixed via integrated closures.

The current LED-Technology of system components ensures outstanding energy efficiency. Corridors and shelves are perfectly illuminated.

Project Request



Quantity	Recolux Code	Description
34	RE-EC	End cap,Black
17	RE-RC-05-00	5 wires Feed In connector
176	RE-TKA9-05B-00	E-Line 2876mm trunking 5 x 2.5 mm²,Black
14	RE-TKA5-05B-00	E-Line 1438mm trunking 5 x 2.5 mm²,Black
366	RE-RSL5S3-60N1NR-T1-03	E-Line LED Module 60° ,42-60W, 9,000 lm, 4,000 K, Non dimmable, Black
180	RE-SMK	Steel suspension




Applications

Shop & Retail

Auto Supply Shop

E-line provide higher light power. It will be more than 500lux in the ground, This enables us to achieve a very beautiful photograph that gives the high-quality automobiles an appropriate appearance.

Project Request



Quantity	Recolux Code	Description
12	RE-EC	End cap,white
6	RE-RC-05-00	5 wires Feed In connector
40	RE-TKA9-05W-00	E-Line 2876mm trunking 5 x 2.5 mm²,white
6	RE-TKA5-05W-00	E-Line 1438mm trunking 5 x 2.5 mm²,white
86	RE-RSL5S3-60P1WD-S1-00	E-Line LED Module 90° ,32-60W, 9,000 lm, 5,000 K, Non dimmable, white
120	RE-SMK	Steel suspension





Surface mounted kits

Chain suspension

Steel suspension kits



cap

connector

Feed In Box

1438mm Trunking

2876mm Trunking

L

T

X

End BOX



30°

60°

90°

25° L or R


DS25°

120°



Sensor

Track Rail




blank cover




90°



MOUNTING



The Recommended Installation Heigh 3-5m




Datasheet



TYPE	POWER (W)	LUMEN (LM)	EFFICACY (LM/W)	CCT (K)	CRI (RA)	Driver (Brand)	Voltage (V)	Function	Dimensions (mm)	WEIGHT (kg)
RSL5S3-60W2WD-S1	60W adjust 50W 42W 32W by switch	Max 7800	130	3000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60N1WD-S1	60W adjust 50W 42W 32W by switch	Max 9000	160	4000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60P1WD-S1	60W adjust 50W 42W 32W by switch	Max 9000	160	5000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60C1WD-S1	60W adjust 50W 42W 32W by switch	Max 9000	160	6000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60W2WD-T1	60W adjust 55W 45W 42W by resistor	Max 7800	130	3000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-60N1WD-T1	60W adjust 55W 45W 42W by resistor	Max 9000	160	4000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-60P1WD-T1	60W adjust 55W 45W 42W by resistor	Max 9000	160	5000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-60C1WD-T1	60W adjust 55W 45W 42W by resistor	Max 9000	160	6000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5P3-68W2WD-T1	16W to 68W by resistor	Max 9400	140	3000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5P3-68N1WD-T1	16W to 68W by resistor	Max 12,000	180	4000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5P3-68P1WD-T1	16W to 68W by resistor	Max 12,000	180	5000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5P3-68C1WD-T1	16W to 68W by resistor	Max 12,000	180	6000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5S5-72W2WD-A3	72W adjust 68W 64W 60W by switch	Max 8200	120	3000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S5-72N1WD-A3	72W adjust 68W 64W 60W by switch	Max 9600	140	4000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S5-72P1WD-A3	72W adjust 68W 64W 60W by switch	Max 9600	140	5000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S5-72C1WD-A3	72W adjust 68W 64W 60W by switch	Max 9600	140	6000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S3-68W2WD-T4	16W to 68W by resistor	Max 8800	130	3000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5S3-68N1WD-T4	16W to 68W by resistor	Max 10,200	160	4000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5S3-68P1WD-T4	16W to 68W by resistor	Max 10,200	160	5000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5S3-68C1WD-T4	16W to 68W by resistor	Max 10,200	160	6000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1




Narrow




60°(SP)




MOUNTING





The Recommended Installation Heigh 5-10m




Datasheet										
TYPE	POWER (W)	LUMEN (LM)	EFFICACY (LM/W)	CCT (K)	CRI (RA)	Driver (Brand)	Voltage (V)	Function	Dimensions (mm)	WEIGHT (kg)
RSL5S3-60W2NR-S1	60W adjust 50W 42W 32W by switch	Max 7800	130	3000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60N1NR-S1	60W adjust 50W 42W 32W by switch	Max 9000	160	4000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60P1NR-S1	60W adjust 50W 42W 32W by switch	Max 9000	160	5000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60C1NR-S1	60W adjust 50W 42W 32W by switch	Max 9000	160	6000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60W2NR-T1	60W adjust 55W 45W 42W by resistor	Max 7800	130	3000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-60N1NR-T1	60W adjust 55W 45W 42W by resistor	Max 9000	160	4000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-60P1NR-T1	60W adjust 55W 45W 42W by resistor	Max 9000	160	5000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-60C1NR-T1	60W adjust 55W 45W 42W by resistor	Max 9000	160	6000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5P3-68W2NR-T1	16W to 68W by resistor	Max 9400	140	3000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5P3-68N1NR-T1	16W to 68W by resistor	Max 12,000	180	4000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5P3-68P1NR-T1	16W to 68W by resistor	Max 12,000	180	5000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5P3-68C1NR-T1	16W to 68W by resistor	Max 12,000	180	6000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5S5-72W2NR-A3	72W adjust 68W 64W 60W by switch	Max 8200	120	3000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S5-72N1NR-A3	72W adjust 68W 64W 60W by switch	Max 9600	140	4000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S5-72P1NR-A3	72W adjust 68W 64W 60W by switch	Max 9600	140	5000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S5-72C1NR-A3	72W adjust 68W 64W 60W by switch	Max 9600	140	6000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S3-68W2NR-T4	16W to 68W by resistor	Max 8800	130	3000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5S3-68N1NR-T4	16W to 68W by resistor	Max 10,200	160	4000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5S3-68P1NR-T4	16W to 68W by resistor	Max 10,200	160	5000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5S3-68C1NR-T4	16W to 68W by resistor	Max 10,200	160	6000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1




30°(SP)



MOUNTING



The Recommended Installation Height 6-12m




Datasheet



TYPE	POWER (W)	LUMEN (LM)	EFFICACY (LM/W)	CCT (K)	CRI (RA)	Driver (Brand)	Voltage (V)	Function	Dimensions (mm)	WEIGHT (kg)
RSL5S3-60W2SP-S1	60W adjust 50W 42W 32W by switch	Max 7800	130	3000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60N1SP-S1	60W adjust 50W 42W 32W by switch	Max 9000	160	4000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60P1SP-S1	60W adjust 50W 42W 32W by switch	Max 9000	160	5000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60C1SP-S1	60W adjust 50W 42W 32W by switch	Max 9000	160	6000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60W2SP-T1	60W adjust 55W 45W 42W by resistor	Max 7800	130	3000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-60N1SP-T1	60W adjust 55W 45W 42W by resistor	Max 9000	160	4000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-60P1SP-T1	60W adjust 55W 45W 42W by resistor	Max 9000	160	5000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-60C1SP-T1	60W adjust 55W 45W 42W by resistor	Max 9000	160	6000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5P3-68W2SP-T1	16W to 68W by resistor	Max 9400	140	3000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5P3-68N1SP-T1	16W to 68W by resistor	Max 12,000	180	4000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5P3-68P1SP-T1	16W to 68W by resistor	Max 12,000	180	5000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5P3-68C1SP-T1	16W to 68W by resistor	Max 12,000	180	6000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5S5-72W2SP-A3	72W adjust 68W 64W 60W by switch	Max 8200	120	3000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S5-72N1SP-A3	72W adjust 68W 64W 60W by switch	Max 9600	140	4000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S5-72P1SP-A3	72W adjust 68W 64W 60W by switch	Max 9600	140	5000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S5-72C1SP-A3	72W adjust 68W 64W 60W by switch	Max 9600	140	6000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S3-68W2SP-T4	16W to 68W by resistor	Max 8800	130	3000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5S3-68N1SP-T4	16W to 68W by resistor	Max 10,200	160	4000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5S3-68P1SP-T4	16W to 68W by resistor	Max 10,200	160	5000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5S3-68C1SP-T4	16W to 68W by resistor	Max 10,200	160	6000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1




Frosted




120° (FF)



MOUNTING



The Recommended Installation Heigh 2-6m




Datasheet



TYPE	POWER (w)	LUMEN (LM)	EFFICACY (LM/W)	CCT (K)	CRI (RA)	Driver (Brand)	Voltage (v)	Function	Dimensions (mm)	WEIGHT (kg)
RSL5D3-60W2FFS1	60W adjust 50W 42W 32W by switch	Max 7000	120	3000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5D3-60N1FF-S1	60W adjust 50W 42W 32W by switch	Max 8200	140	4000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5D3-60P1FF-S1	60W adjust 50W 42W 32W by switch	Max 8200	140	5000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5D3-60C1FF-S1	60W adjust 50W 42W 32W by switch	Max 8200	140	6000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5D3-60W2FF-T1	60W adjust 55W 45W 42W by resistor	Max 7000	120	3000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5D3-60N1FF-T1	60W adjust 55W 45W 42W by resistor	Max 8200	140	4000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5D3-60P1FF-T1	60W adjust 55W 45W 42W by resistor	Max 8200	140	5000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5D3-60C1FF-T1	60W adjust 55W 45W 42W by resistor	Max 8200	140	6000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-68W2FF-T1	16W to 68W by resistor	Max 8800	130	3000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5S3-68N1FF-T1	16W to 68W by resistor	Max 10,000	160	4000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5S3-68P1FF-T1	16W to 68W by resistor	Max 10,000	160	5000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5S3-68C1FF-T1	16W to 68W by resistor	Max 10,000	160	6000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5D5-72W2FF-A3	72W adjust 68W 64W 60W by switch	Max 8000	110	3000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5D5-72N1FF-A3	72W adjust 68W 64W 60W by switch	Max 9300	130	4000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5D5-72P1FF-A3	72W adjust 68W 64W 60W by switch	Max 9300	130	5000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5D5-72C1FF-A3	72W adjust 68W 64W 60W by switch	Max 9300	130	6000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5D3-68W2FF-T4	16W to 68W by resistor	Max 8000	120	3000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5D3-68N1FF-T4	16W to 68W by resistor	Max 9600	140	4000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5D3-68P1FF-T4	16W to 68W by resistor	Max 9600	140	5000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5D3-68C1FF-T4	16W to 68W by resistor	Max 9600	140	6000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1




Double asymmetric




25° Double



MOUNTING






The Recommended Installation Heigh 2-4m




Datasheet										
TYPE	POWER _(W)	LUMEN _(LM)	EFFICACY _(LM/W)	CCT _(K)	CRI _(RA)	Driver _(Brand)	Voltage _(V)	Function	Dimensions _(mm)	WEIGHT _(kg)
RSL5S3-60W2DS-S1	60W adjust 50W 42W 32W by switch	Max 7800	130	3000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60N1DS-S1	60W adjust 50W 42W 32W by switch	Max 9000	160	4000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60P1DS-S1	60W adjust 50W 42W 32W by switch	Max 9000	160	5000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60C1DS-S1	60W adjust 50W 42W 32W by switch	Max 9000	160	6000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60W2DS-T1	60W adjust 55W 45W 42W by resistor	Max 7800	130	3000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-60N1DS-T1	60W adjust 55W 45W 42W by resistor	Max 9000	160	4000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-60P1DS-T1	60W adjust 55W 45W 42W by resistor	Max 9000	160	5000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-60C1DS-T1	60W adjust 55W 45W 42W by resistor	Max 9000	160	6000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5P3-68W2DS-T1	16W to 68W by resistor	Max 9400	140	3000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5P3-68N1DS-T1	16W to 68W by resistor	Max 12,000	180	4000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5P3-68P1DS-T1	16W to 68W by resistor	Max 12,000	180	5000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5P3-68C1DS-T1	16W to 68W by resistor	Max 12,000	180	6000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5S5-72W2DS-A3	72W adjust 68W 64W 60W by switch	Max 8200	120	3000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S5-72N1DS-A3	72W adjust 68W 64W 60W by switch	Max 9600	140	4000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S5-72P1DS-A3	72W adjust 68W 64W 60W by switch	Max 9600	140	5000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S5-72C1DS-A3	72W adjust 68W 64W 60W by switch	Max 9600	140	6000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S3-68W2DS-T4	16W to 68W by resistor	Max 8800	130	3000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5S3-68N1DS-T4	16W to 68W by resistor	Max 10,200	160	4000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5S3-68P1DS-T4	16W to 68W by resistor	Max 10,200	160	5000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5S3-68C1DS-T4	16W to 68W by resistor	Max 10,200	160	6000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1



Asymmetric L or R




MOUNTING




The Recommended Installation Height 2-4m



Datasheet										
TYPE	POWER (W)	LUMEN (LM)	EFFICACY (LM/W)	CCT (K)	CRI (RA)	Driver (Brand)	Voltage (V)	Function	Dimensions (mm)	WEIGHT (kg)
RSL5S3-60W2LR-S1	60W adjust 50W 42W 32W by switch	Max 7800	130	3000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60N1LR-S1	60W adjust 50W 42W 32W by switch	Max 9000	160	4000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60P1LR-S1	60W adjust 50W 42W 32W by switch	Max 9000	160	5000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60C1LR-S1	60W adjust 50W 42W 32W by switch	Max 9000	160	6000K	>80	OSRAM	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.65
RSL5S3-60W2LR-T1	60W adjust 55W 45W 42W by resistor	Max 7800	130	3000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-60N1LR-T1	60W adjust 55W 45W 42W by resistor	Max 9000	160	4000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-60P1LR-T1	60W adjust 55W 45W 42W by resistor	Max 9000	160	5000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5S3-60C1LR-T1	60W adjust 55W 45W 42W by resistor	Max 9000	160	6000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.7
RSL5P3-68W2LR-T1	16W to 68W by resistor	Max 9400	140	3000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5P3-68N1LR-T1	16W to 68W by resistor	Max 12,000	180	4000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5P3-68P1LR-T1	16W to 68W by resistor	Max 12,000	180	5000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5P3-68C1LR-T1	16W to 68W by resistor	Max 12,000	180	6000K	>80	Tridonic	AC 220-240V	Non-Dimmable	1438 x 65 x 27	1.9
RSL5S5-72W2LR-A3	72W adjust 68W 64W 60W by switch	Max 8200	120	3000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S5-72N1LR-A3	72W adjust 68W 64W 60W by switch	Max 9600	140	4000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S5-72P1LR-A3	72W adjust 68W 64W 60W by switch	Max 9600	140	5000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S5-72C1LR-A3	72W adjust 68W 64W 60W by switch	Max 9600	140	6000K	>80	AGT	AC 220-240V	1-10V	1438 x 65 x 27	2.1
RSL5S3-68W2LR-T4	16W to 68W by resistor	Max 8800	130	3000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5S3-68N1LR-T4	16W to 68W by resistor	Max 10,200	160	4000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5S3-68P1LR-T4	16W to 68W by resistor	Max 10,200	160	5000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1
RSL5S3-68C1LR-T4	16W to 68W by resistor	Max 10,200	160	6000K	>80	Tridonic	AC 220-240V	DALI	1438 x 65 x 27	2.1






5-Pole



7-Pole




11-Pole



Tool-free installation




Datasheet



Connector for quick connection between Trunking rail and led module





Datasheet



White:

TYPE	WIRES (m)	Dimensions (mm)	WEIGHT (kg)
TKA2-05W-00	5 x2.5 mm²	578x 65 x 65	0.85
TKA2-07W-00	7 x2.5 mm²	578x 65 x 65	0.95
TKA5-05W-00	5 x2.5 mm²	1438x 65 x 65	1.59
TKA5-07W-00	7 x2.5 mm²	1438x 65 x 65	1.65
TKA5-11W-00	11 x2.5 mm²	1438x 65 x 65	1.95
TKA9-05W-00	5 x2.5 mm²	2876x 65 x 65	2.85
TKA9-07W-00	7 x2.5 mm²	2876x 65 x 65	2.98
TKA9-11W-00	11 x2.5 mm²	1438x 65 x 65	3.25

Black:

TYPE	WIRES (m)	Dimensions (mm)	WEIGHT (kg)
TKA2-05B-00	5 x2.5 mm²	578x 65 x 65	0.85
TKA2-07B-00	7 x2.5 mm²	578x 65 x 65	0.95
TKA5-05B-00	5 x2.5 mm²	1438x 65 x 65	1.59
TKA5-07B-00	7 x2.5 mm²	1438x 65 x 65	1.65
TKA5-11B-00	11 x2.5 mm²	1438x 65 x 65	1.95
TKA9-05B-00	5 x2.5 mm²	2876x 65 x 65	2.85
TKA9-07B-00	7 x2.5 mm²	2876x 65 x 65	2.98
TKA9-11B-00	11 x2.5 mm²	1438x 65 x 65	3.25

Installation







Max.8M



Hold Time
5s~30min




Mounting Height
15m Max.



Automatic
Dimming











5
Years
Guarantee



Type	Description	Length	Weight
RE-SENSOR-00	Merrytek, 1-10V Microwave Sensor suitable for ceiling heights from 3 to 15 m	1438mm	1.05kg
RE-SENSOR-03	Merrytek, 1-10V Microwave Sensor suitable for ceiling heights from 3 to 15 m	578mm	0.5kg




Type	Description	Length	Weight
RE-TR15-07	690mm track, white,for 3-circuit track adapter	1438mm	2.1kg
RE-TR06-07	300mm track, white,for 3-circuit track adapter	578mm	2.1kg



Other accessories and fixing components

Serial number	Type	Description	Weight (kg)
01	TNC-B1-05W-00	Feed In Box , 5 * 2.5 mm2 wires , white	0.72
01	TNC-B1-07W-00	Feed In Box , 7 * 2.5 mm2 wires , white	0.74
01	TNC-B1-05B-00	Feed In Box , 5 * 2.5 mm2 wires , Black	0.72
01	TNC-B1-07B-00	Feed In Box , 7 * 2.5 mm2 wires , Black	0.74
02	TNC-L1-07W-00	Left 'L' Node Connectors,7 * 2.5 mm2 wires , white	1.05
02	TNC-L2-07W-00	Right 'L' Node Connectors,7 * 2.5 mm2 wires , white	1.07
03	TNC-T1-07W-00	Left 'T' Node Connectors,7 * 2.5 mm2 wires , white	1.8
03	TNC-T2-07W-00	Right 'T' Node Connectors,7 * 2.5 mm2 wires , white	1.8
04	TNC-X1-07W-00	'X' Node Connectors,7 * 2.5 mm2 wires , white	2.5
05	TNC-B0-05W-00	Feed End Box , no wire , white	0.31
05	TNC-B0-07W-00	Feed End Box , no wire , Black	0.31
06	EC-02	End Cap white	0.016
06	EC-03	End Cap Black	0.016
07	RC-05-00	Feed In connector , 5 * 2.5 mm2 wires with male connector	0.037
07	RC-07-00	Feed In connector , 7 * 2.5 mm2 wires with male connector	0.045
08	RC-05-01	Feed in connector , 7 * 2.5 mm2 wires with female connector	0.037
08	RC-07-01	Feed In connector , 7 * 2.5 mm2 wires with female connector	0.045
09	RE-15-FF	1438mm PC bland cover	0.158
09	RE-15-AL	1438mm Aluminum bland cover	0.875



Other accessories and fixing components		
Serial number	Production	Weight (kg)
01	Surface Mounted Kits Suspension Kits	0.014
02	Chain suspension kits without chain	0.03
03	Steel suspension kits	0.55
04	Chain suspension kits	0.193