CH1327Z Series



Product Description

The CH1327Z T5 LED tube lamp provides exceptional LED lighting with reduced energy and maintenance costs. This lamp has a long rated lifetime of 30,000 hours. And it does not require a ballast to work with and offers a built-in linear driver. The lamp is widely used in supermarkets, offices, hospital and other commercial or public palces.

Tube Features

- * Direct connect to AC220-240V.
- * Simple rewiring installation allows lamps to operate on main line voltage
- * Exceptional efficacy 150LPW
- * High-transmittance glass tube with PET film coated outside; or Glass+powder inside
- * High transmittance
- * No mercury and no UV
- * THD: 3rd<86% 5th<61% According with IEC 61000-3-2:2019 Flicker requirement: PST≤1 SVM≤0.4



Product Specification									
Product	Lamp Power(W)	DF	Efficacy (Im@4000K)	CCT (K)	CRI	Socket	Dimension (mm)	Beam Angle(°)	Lifetime (hrs)
CH1327Z	7(HE14)	>0.9	150	3000/4000/6500	80	G5	φ19*549	180	30000
CH1327Z	10(HE21)	>0.9	150	3000/4000/6500	80	G5	φ19*849	180	30000
CH1327Z	16(HE28)	>0.9	150	3000/4000/6500	80	G5	φ19*1149	180	30000
CH1327Z	18(HE35)	>0.9	150	3000/4000/6500	80	G5	φ19*1449	180	30000
CH1327Z	26(HO54)	>0.9	150	3000/4000/6500	80	G5	φ19*1149	180	30000
CH1327Z	26(HO49)	>0.9	150	3000/4000/6500	80	G5	φ19*1449	180	30000
CH1327Z	36(HO80)	>0.9	150	3000/4000/6500	80	G5	φ19*1449	180	30000