

CH2355V/SV Series

T5 Series

Integrated-fixture



Product Description

CH2355V/SV widely used in offices, hotels, shopping malls, subways, home, and other places for general lighting and backlighting.

Fixture Features

- * Using high quality SMD led chips,integrated design without dark areas that create the unique appearance.
- * Built-in non-isolated driver, complies with CE, safety regulations.
- * No mercury allowing for non-hazardous waste disposal
- * No UV rays or IR emitting virtually
- * Over 50% energy savings vs traditional fluorescent fixtures
- * High quality PC fixture
- * THD: 3rd<86% 5th<61% According with IEC 61000-3-2:2019
Flicker requirement: PST≤1 SVM≤0.4



RoHS CE

Product Model								
Product	Lamp Power(W)	DF	Lumen (lm@4000K)	CCT (K)	CRI	Dimension (mm)	Beam Angle(°)	Lifetime (hrs)
CH2355V/SV	4	>0.7	400	3000/4000/6500	83	313x22x30	150	30000
CH2355V/SV	6	>0.7	600	3000/4000/6500	83	543x22x30	150	30000
CH2355V/SV	8	>0.7	800	3000/4000/6500	83	573x22x30	150	30000
CH2355V/SV	10	>0.7	1000	3000/4000/6500	83	873x22x30	150	30000
CH2355V/SV	14	>0.7	1400	3000/4000/6500	83	1173x22x30	150	30000
CH2355V/SV	16	>0.7	1600	3000/4000/6500	83	1173x22x30	150	30000
CH2355V/SV	18	>0.7	1800	3000/4000/6500	83	1473x22x30	150	30000

V2109