

## **Product Description**

The CH3335 LED panel provides exceptional LED lighting with reduced energy and maintenance costs. And it can widely used in offices, hotels, shopping malls. subways, halls, schools, hospitals, hallway and lounge, conference room etc.

## **Features**

- \* The light module adopt straight down type, no light guide plate
- \* No yellowing(LGP), more reliable performance
- \* New construction design, more thinner and lighter
- \* CH3335:Exceptional efficacy: 80/100/120/140 LPW.
- \* Aluminum alloy frame with a superior heat dissipation performances
- \* THD: 3rd<86% 5th<61% According with IEC 61000-3-2:2019 Flicker requirement: PST≤1 SVM≤0.4



Product Specification								
Product I	Lamp Power(W)	DF	Lumen (Im@4000K)	CCT (K)	CRI	Dimension (mm)	Beam Angle(°)	Lifetime (hrs)
CH3335	14	>0.9	1400	3000/4000/6500	83	295x595x32	110	30000
CH3335	38	>0.9	3800	3000/4000/6500	83	295x1195x32	110	30000
CH3335	38	>0.9	3800	3000/4000/6500	83	595x595x32	110	30000
CH3335	50	>0.9	5000	3000/4000/6500	83	595x1195x32	110	30000
CH3335-UG	SR 38	>0.9	3800	3000/4000/6500	83	295x1195x32	90	30000
CH3335-UG	SR 38	>0.9	3800	3000/4000/6500	83	595x595x32	90	30000

