

CH5329V/SV/IB Series

Ceiling Mount Lamp



Application area:

CH5329V can be used in corridor, washroom, kitchen, bedroom, basement, garage and so on.
CH5329SV is with sensor, used in corridor, garage, warehouse where need the automatic energy saving lighting. CH5329IB intelligent series widely used in offices, hotels, shopping malls, subways, home, and other places for general.

Lamp features:

- * PMMA Optical lens, uniform light.
- * High lumen LED chip, non-isolated driver;
- * Cold-reduced sheet body + PMMA cover,
- * Concise shape.
- * CH5329IB: Brightness and color dimmable with WIFI.
- * THD: 3rd < 86% 5th < 61% According with IEC 61000-3-2:2019
Flicker requirement: PST ≤ 1 SVM ≤ 0.4



RoHS CE

Product Specification

Product	Lamp Power(W)	DF	Lumen (lm@4000K)	CCT (K)	CRI	Dimension (mm)	Beam Angle(°)	IP	Lifetime (hrs)
CH5329V/SV	12	>0.7	960	3000/4000/6500	83	φ 270x68	120	20 or 44	30000
CH5329V/SV	18	>0.7	1440	3000/4000/6500	83	φ 328x77	120	20 or 44	30000
CH5329V/SV	24	>0.7	1920	3000/4000/6500	83	φ 380x90	120	20 or 44	30000
CH5329IB	18	>0.7	1440	3000-6500	83	φ 328x77	120	20 or 44	30000
CH5329IB	24	>0.7	1920	3000-6500	83	φ 380x90	120	20 or 44	30000

V2109