

HL-CA018 Linear Pendant Light Specification



Feature

-Professional appearance design, simple and elegant.

-High quality, energy-efficient LED Lighting for environmental protection.

-Anodized aluminum profile with good heat sink.

-Built-in power supply, no flicker.

-For offices, conference rooms, supermarkets, home lighting, etc.



Model	HL-CA018
Size	L1200*W50*H70mm
Nominal Power	75W
Lm	7140lm
Beam Angle	120°
Input Voltage	AC200-240V
CCT	2700-6500k
CRI	>80
Protection Grade	IP40
Certification	CE, ROSH
Warranty	3 years
Color	Black





Installation



Step 1: Use an electric drill tool to drill a hole at a suitable position on the cement wall



Step 3: In order to make the hanging rope more stable, tighten the wall end of the nut using a wrench tool





Step 4: Adjust the distance and height of the lamp by connecting the T-shaped slider to the screw fitting at the lower end. and the installation is complete.

Packing



HL-CA018

L680mm*W1250mm*H1180mm

8 PCS

Notices

1. The power supply must be turned off before installation.

2. Make sure the product is mounted under the surface of the object to be installed, and finally turn on the power to light up.

3. This product is for indoor use only.

4. The product is not responsible for damage caused by accidental factors or improper use.