



## CXTZ02


### QUICK INFO

<b>Material</b>	Aluminium Die Cast
<b>Finish</b>	Powder Coated
<b>Lamp Type</b>	LED Track Light
<b>Wattage</b>	38W Max
<b>CRI</b>	90
<b>Class</b>	1
<b>Lumen Output (lm)</b>	4940*
<b>CCT</b>	3000K/4000K/5000K/6500K
<b>Power Switching</b>	18W/25W/32W/38W
<b>Driver</b>	Built-in
<b>Heat sink</b>	Unibody Die Cast Aluminium
<b>Installation Orientation</b>	Track Mounted
<b>Light Source Type</b>	COB
<b>Optics</b>	Lens
<b>Dimension</b>	160x157mm
<b>Cutout Diameter</b>	N/A
<b>Recess Depth</b>	N/A
<b>Beam Angle</b>	24° 42° 55°
<b>Colour</b>	<input type="checkbox"/> RAL-9003 <input checked="" type="checkbox"/> RAL-9005 <input type="checkbox"/> RAL-9006 <input type="checkbox"/> Customizable

### LUX Illuminance Curve\*(42°)

Height	Beam LUX	Diameter
1.0m	8032lx	77.47cm
2.0m	2008lx	154.94cm
3.0m	892.5lx	232.41cm
4.0m	502.0lx	309.88cm
5.0m	321.3lx	387.35cm

Note: The curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



### APPLICATIONS





## CXWM01


### QUICK INFO

<b>Material</b>	Aluminium Die Cast
<b>Finish</b>	Powder Coated
<b>Lamp Type</b>	LED Wall-washer Light
<b>Wattage</b>	38W Max
<b>CRI</b>	90
<b>Class</b>	2
<b>Lumen Output (lm)</b>	4940*
<b>CCT</b>	3000K/4000K/5000K/6500K
<b>Power Switching</b>	18W/25W/32W/38W
<b>Driver</b>	Remote
<b>Heat sink</b>	Unibody Die Cast Aluminium
<b>Installation Orientation</b>	Recessed Mounted
<b>Light Source Type</b>	COB
<b>Optics</b>	Lens
<b>Dimension</b>	154x128mm
<b>Cutout Diameter</b>	140mm
<b>Recess Depth</b>	128mm
<b>Beam Angle</b>	24° 42° 55°
<b>Colour</b>	<input type="checkbox"/> RAL-9003 <input checked="" type="checkbox"/> RAL-9005 <input type="checkbox"/> RAL-9006 <input type="checkbox"/> Customizable

### LUX Illuminance Curve\*(24°)

Height	Beam LUX	Diameter
1.0m	15041lx	46.95cm
2.0m	3760lx	93.91cm
3.0m	1671lx	140.86cm
4.0m	940.1lx	187.82cm
5.0m	601.7lx	234.77cm

Note: The curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



### APPLICATIONS





## CXGS01


### QUICK INFO

<b>Material</b>	Aluminium Die Cast
<b>Finish</b>	Powder Coated
<b>Lamp Type</b>	LED Gimbal Light
<b>Wattage</b>	38W Max
<b>CRI</b>	90
<b>Class</b>	2
<b>Lumen Output (lm)</b>	4940*
<b>CCT</b>	3000K/4000K/5000K/6500K
<b>Power Switching</b>	18W/25W/32W/38W
<b>Driver</b>	Remote
<b>Heat sink</b>	Unibody Die Cast Aluminium
<b>Installation Orientation</b>	Recessed Mounted
<b>Light Source Type</b>	COB
<b>Optics</b>	Lens
<b>Dimension</b>	200x120mm
<b>Cutout Diameter</b>	142mm
<b>Recess Depth</b>	120mm
<b>Beam Angle</b>	24° 42° 55°
<b>Colour</b>	<input type="checkbox"/> RAL-9003 <input checked="" type="checkbox"/> RAL-9005 <input type="checkbox"/> RAL-9006 <input type="checkbox"/> Customizable


### LUX Illuminance Curve\*(24°)

Height	Beam LUX	Diameter
1.0m	15041lx	46.95cm
2.0m	3760lx	93.91cm
3.0m	1671lx	140.86cm
4.0m	940.1lx	187.82cm
5.0m	601.7lx	234.77cm

Note: The curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



### APPLICATIONS





## CXDE02-T


### QUICK INFO

<b>Material</b>	Aluminium Die Cast
<b>Finish</b>	Powder Coated
<b>Lamp Type</b>	LED Down Light
<b>Wattage</b>	38W Max
<b>CRI</b>	90
<b>Class</b>	2
<b>Lumen Output (lm)</b>	4940*
<b>CCT</b>	3000K/4000K/5000K/6500K
<b>Power Switching</b>	18W/25W/32W/38W
<b>Driver</b>	Remote
<b>Heat sink</b>	Unibody Die Cast Aluminium
<b>Installation Orientation</b>	Recessed Mounted
<b>Light Source Type</b>	COB
<b>Optics</b>	Lens
<b>Dimension</b>	154x120mm
<b>Cutout Diameter</b>	140 mm
<b>Recess Depth</b>	120mm
<b>Beam Angle</b>	<span>24°</span> <span>42°</span> <span>55°</span>
<b>Colour</b>	<input type="checkbox"/> RAL-9003 <input checked="" type="checkbox"/> RAL-9005 <input type="checkbox"/> RAL-9006 <input type="checkbox"/> Customizable


### LUX Illuminance Curve\*(55°)

Height	Beam LUX	Diameter
1.0m	4742lx	103.82cm
2.0m	1185lx	207.65cm
3.0m	526.9lx	311.47cm
4.0m	296.4lx	415.29cm
5.0m	189.7lx	519.11cm

Note: The curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



### APPLICATIONS



## ELANOR TILT

**Cion**  
Innovative Illumination



**CB**

**IP20**

