



Polar system has a low glare rating (UGR <16), thereby protecting against excessive fatigue and gradual deterioration of vision. Led Modules easy replace for environmental protection, reduce inventory and maintenance costs. Different sizes can be customized according to engineering requirements

Features

- Unique appearance, different from panel light in market
- High brightness with 140lm/w
- Lower UGR <16
- The module can be removed by click
- Module detachable, easy to maintain and saving the maintain
- 2-4 modules are available, meet to different project requirement
- 80° lighting distribution provide comfortable lighting
- Different sizes can be customized according to engineering requirements



Specifications

Item	Qty module	Size(mm)	Power (W)	Lumen (lm/w)	Beam Angel	Colour Temperature		
ESPA-595x595-24W	2pcs	595x595x18	24	120	80°	3000K/4000K/6500K		
ESPA-595x595-30W	2pcs	595x595x18	30	120	80°	3000K/4000K/6500K		
ESPA-595x595-36W	3pcs	595x595x18	36	120	80°	3000K/4000K/6500K		
ESPA-595x595-40W	3pcs	595x595x18	40	120	80°	3000K/4000K/6500K		
ESPA-595x595-60W	4pcs	595x595x18	60	120	80°	3000K/4000K/6500K		
ESPA-595x595-80W	4pcs	595x595x18	80	120	80°	3000K/4000K/6500K		
Item	UGR	IP	IK	Driver	DF	CRI	Input Voltage	Warranty
ESPA-595x595-24W	<16	20	08	Flicker free	>0.9	>80/>90	220-240V	5years
ESPA-595x595-30W	<16	20	08	Flicker free	>0.9	>80/>90	220-240V	5years
ESPA-595x595-36W	<16	20	08	Flicker free	>0.9	>80/>90	220-240V	5years
ESPA-595x595-40W	<16	20	08	Flicker free	>0.9	>80/>90	220-240V	5years
ESPA-595x595-60W	<16	20	08	Flicker free	>0.9	>80/>90	220-240V	5years
ESPA-595x595-80W	<16	20	08	Flicker free	>0.9	>80/>90	220-240V	5years

295x1195x18MM/620x620x18MM under request
Special sizes can be customized

Equipment/Accessories:

Suspension kit and surface mounted frame available as separate accessory

Product Details Review.



Areas of application :

- Office buildings
- Educational
- Cultural
- EntertainmentIndustrial and medical facilities
- Homes and private apartments

